
RS/6000

AIX - Cornerstone For Project Monterey, The future Of UNIX





CATALOG

U.S. Version

WINTER 2000

NEW!



Page 7

The new HA-S80: Unmatched power with the ultimate in high availability.

NEW!



Page 16

The new Model B50: The compact. low-cost server of choice for Internet and Application Service Providers.

NEW!



Page 36

Enterprise Storage Server: Fast, intelligent, universal data access anywhere, anytime.

Page 2 Special Offers

Page 4 Order Information

Page 5 Contents

Page 77 Index

Special Offers

Special Offers

A BOX OF e-solutions

Net.Commerce Start Now

GET YOUR E-COMMERCE SITE UP AND RUNNING FAST

Go into e-business on the Web in less than 30 days, with Net.Commerce Start Now: everything you need to open an online store. This fully integrated solution from IBM includes your choice of RS/6000 servers — 43P Model 140, Model F50, HA50 or HA-H70 — packed with the features and options, and backed by the service and support, you need to succeed in e-business. Net.Commerce Start Now also includes:

- 100 catalog and search capabilities
- Your company's own "look and feel"
- Quick and easy transactions
- Shopping cart and help facilities
- Secure online credit card ordering
- Automated sales tax and shipping calculations
- Automated registration with 20 leading search engines
- Customer relationship management capabilities
- Business Partner implementation, customization and site development services

e-business



TO FIND OUT MORE ABOUT NET.COMMERCE START NOW, CALL I 800 426-7777 AND MENTION PRIORITY CODE 10854019.

THE POWER OF AIX 4.3.3

LET THE NEW AIX 4.3.3 SUPERCHARGE YOUR E-BUSINESS

Move up to the latest version of AIX and give your e-business better performance, scalability, manageability, serviceability, security and interoperability than ever before. AIX 4.3.3 can scale to 24-way SMP systems with 64GB of memory and features improved cache affinity, JFS backup and concurrent RAID mirroring and striping capabilities, a new AIX Fast Connect feature, enhanced Java facilities, a special AIX Bonus Pack and much more. It even includes an announced plan to deliver a Linux application execution environment.

VIEW AIX 4.3.3 DOCUMENTATION THROUGH A DYNAMIC UNIFIED GUI

Now a new unified library GUI lets you search, navigate and read the dynamic AIX documentation installed on your system and makes it easy for you to integrate your own HTML materials.

GET FREE NOTIFICATION OF AIX SOFTWARE SUBSCRIPTION UPGRADES

Register today to have product upgrade notifications automatically sent to you via e-mail. Upgrades can then be ordered and shipped online.

CREATE POWERFUL E-BUSINESS SOLUTIONS WITH WEBSPHERE APPLICATION SERVER



With WebSphere Application Server, and the AIX Solution Series for New e-business based on it, you can

quickly turn static Web sites into powerful e-business solutions and deliver advanced hosting services to your customers.

FEE-BASED SERVICE EXTENSIONS **AVAILABLE FOR AIX 4.2 USERS**

Even though AIX 4.2 will no longer be marketed after December of 1999, IBM Global Services is offering fee-based service extensions to AIX 4.2 users who need them on special bid through local representatives.

It's easy to order with IBM



Phone

Call 800 426-2255 (800 IBM-CALL), Monday-Friday 8AM - 8PM (ET)



Fax

800 242-6329 (800 2 IBM-FAX)

Write your customer number, name and phone number on one of your company's purchase orders and fax it to us.



Internet and e-mail

Internet: Enter your ordering information and e-mail:

ibm direct@vnet.ibm.com

www.ibm.com/Shop

Shop IBM on the Web and order right online. Placing an order on Shop IBM is a snap. Find your product, click "Order Now" and follow the easy instructions. And you can Shop IBM 24 hours a day. We accept credit cards, purchase orders and checks to complete your purchase.



Mail

Send purchase order to:

IBM Direct

Dept. RC100 P.O. Box 2690 Atlanta, GA 30301



Local IBM Representative

Your local IBM Marketing team will continue to support you with any IBM product you select from this catalog. For the marketing representative nearest you, dial **800 426-4968.**



Your IBM Business Partner

You may find it convenient to order your catalog products through your IBM Business Partner*. Their knowledge of your organization and its current computing environment may help you to quickly select and install the best IBM products for your needs. Prices for products available from Business Partners may vary.

Everything you need... fast

Free shipping

You pay no shipping charges on most products in this catalog (for normal delivery). No shipping fees means more money back into your business!

Free QuickShip 2-day delivery

Many products in this catalog are eligible for QuickShip delivery. Place your order by 1:00PM (ET), Monday-Friday, and we'll ship your products the same day, delivering them within 48 hours. Next day and Saturday deliveries subject to charge. For details, see pages 48-49.

"Test-Drive" our software

Your business demands flexibility and cost-efficiency. That's why IBM lets you try out selected software from this catalog before actually buying it! Selected items come with a special no-risk test period so you can thoroughly "test-drive" your new application.

Backed by IBM

Every IBM product in this catalog is backed by an IBM Limited Warranty. For IBM hardware products, if the product does not perform as specified during its warranty period, IBM will repair it or replace it. If we are unable to do either of these, we will refund your money. The warranty period for RS/6000* products is one year and includes 7-day-a-week, 24-hour service.

See the IBM Limited Warranty for full details and limitations. Complete documentation regarding warranties is available by calling 800 426-2255. Non-IBM products are provided on an "as is" basis, but may be covered by the appropriate manufacturer's warranty. IBM makes no representations or warranties, expressed or implied, regarding the Year 2000 readiness of non-IBM products.

One-stop financing

IBM Global Services offers Preferred Rate Financing for RS/6000 hardware, software, maintenance, training and services provided by IBM and IBM Business Partners. See page 76 for more information.

Free up your cash with leasing

IBM Global Services may improve your cash flow and create a hedge against inflation. A host of low-interest lease plans on IBM hardware, software and services are available. Turn to page 76.

FCC Classifications:

This catalog contains products classified under Federal Communications Commission (FCC) regulations. Product classifications are defined as follows:

FCC Class A - Suitable for non-residential use. See product documentation for complete FCC statements.

FCC Class B - Suitable for home or office use. See product documentation for complete FCC statements. NOTE: Installing an FCC Class A adapter in an FCC Class B system changes the system classification to FCC Class A and makes it unsuitable for use in a residential environment.

Agreements and Warranties

The IBM products featured in this catalog are offered under the terms of either the IBM Customer Agreement (ICA) or the IBM International Program License Agreement (IPLA). Program warranty information is included with the program or in the IBM Customer Agreement. Tivoli** products featured in this catalog are licensed under the terms of the ICA and Addendum for Tivoli products. Complete documentation regarding licensing terms, warranties, current prices, contracts, volume discounts and technical product descriptions are available by phone, fax or mail. Simply dial 800 426-2255.

Delivery to Puerto Rico and the U.S. Virgin Islands

Due to the extra costs of delivery, a 7% surcharge is added to all hardware

(purchase or leasing) and software orders in Puerto Rico and the U.S. Virgin Islands.

Availability and Limitations:

The software and hardware products in this catalog are available through February 29, 2000, unless otherwise noted. The most current edition of the IBM Direct RS/6000 catalog supersedes any previous edition of this catalog. Prices and charges in this catalog are subject to change without notice and do not include applicable sales taxes. IBM is not responsible for printing errors in this catalog which result in pricing or information inaccuracies. All orders are subject to normal IBM credit approval.

Questions? We're always ready to help

Our RS/6000 sales specialists are just a phone call away with the latest product information, pre-sales advice and order placement. Just dial 800 426-2255 with any questions you may have about our products and services. We'll help you select and configure the right solutions for your needs.

Charge it

You can easily charge your purchases under \$10,000 to the personal or corporate card of your choice: American Express, MasterCard or Visa.

Not looking to buy? Rent it

Are you facing a peak business period or short-term workload beyond the scope of your current computing resources? Our short-term hardware rental option is the perfect solution. It also lets you try out needed IBM hardware before making a purchase decision. See page 76.

Product info at your fingertips

The latest RS/6000 product information is available at:

- Internet WWW site www.rs6000.ibm.com
- Our 24-hour-a-day Fax service at 800 426-4329 (FAX DOC numbers appear under product names throughout the catalog.)

Federal discounts

Are you a federal agency eligible for IBM discounts? We'll be happy to work within your current Federal contract and discount structure. Just call IBM Direct and ask for the Federal Team on discounts.

If you don't see it, call

The programs and products available in this catalog represent only a portion of the RS/6000 hardware and software from IBM.

Volume discounts

Many business customers enjoy significant savings through IBM volume discounts. If you're one of them, we'll be happy to honor your existing discount arrangements. Just give us a call.

Watch for these icons:







Custom QuickShip Service

can ship your product







Prices

product or



Update

Newly announced model

Recently Prices on the updated product recently been

Warranty of your

QuickShip Service can ship your product within



Software

updates

Software





P-R-0-M-0

Contents

6-7 Power lineup chart

8 e-business Solutions

- 9 Web Application Server Solution
- 10 e-Collaboration Server Solution
- 11 Electronic Commerce Solution
- 12 Security Solutions
- 13 Service Provider Solutions

8

e-business solutions

14 Hardware

- 14 43P Workstations/Servers
- 17 RS/6000 SMP Servers
- 20 RS/6000 SMP Enterprise Servers
- 26 RS/6000 SP
- 28 Add-ons and Upgrades
- 29 Graphics Accelerators
- 31 Graphics Peripherals

14

Hardware

34 Storage

- 34 Disk Drives
- 38 Tape Drives

34

Storage

42 Peripherals

- 42 Printers
- 44 Adapters and Cables
- 50 Displays

42

Peripherals

51 Software

- Operating System 52
- Data Management
- Systems Management
- 62 Connectivity
- 65 Application Development

51

Software

72 Services/Education

- 72 IBM Global Services
- 75 AIX Computer-Based Training (CBT) Courses

76 IBM Global Finanacing

72 Services/ **Education**

77 Index

77 Index

THE MODEL S80; MISSION CRITICAL APPLICATION PERFORMER

RS/6000 ENTERPRISE SERVER MODEL S80

The new 6- to 24-way RS/6000 Enterprise Server Model S80 employs the latest 64-bit copper microprocessor technology to deliver more than three times the performance of its predecessor – performance designed to meet any mission-critical ERP, supply chain management, data warehouse/data mart or e-business application challenge. A 24-way

S80 outperforms Sun systems with up to 64 microprocessors, making it the most powerful UNIX server ever. What's more, an entry-level S80 costs less than competing high-end SMP servers from either Sun or Hewlett-Packard.

SEE PAGE 24

RS/6000 HA-S80 CLUSTERED SERVER



Your mission-critical applications must always be up and running in top form. The RS/6000 Model HA-S80 Clustered Server combines two specially configured S80s with IBM's high-performance 7133 Serial Disk System and award-winning High Availability Cluster Multi-processing (HACMP) for AIX software to deliver the ultimate in high-availability performance.

RECORD-SETTING S80 PERFORMANCE BENCHMARKS

No matter what the yardstick, the S80 measures up as the best-performing UNIX server on the market today. It's the world champ for online transaction processing, with a single system surpassing all cluster and SMP results in the TPC-C benchmark. It's clearly the fastest Web server: a 12-way S80 turned in 66 percent better SPECweb 96 benchmark results than an HP 9000 N-Class server.* And when it comes to ERP, 24-way S80 outperforms 64-bit Sun E10000 servers in key Baan and SAP benchmarks. For more information on the S80 performance leadership, visit:

HTTP://WWW.RS6000.IBM.COM/RESOURCE/FEATURES/1999/S80.HTML

*All results as of December 2, 1999, TPC results viewable at www.tpc.org/new_result/ttperf.idc SPECweb96 benchmarks viewable at www.specbench.org

RS/6000 MODEL B50 SERVER

With outstanding price performance, this compact low-cost server is designed specifically for Internet and Application Service

Providers and has a wide range of packaged solutions. Pack up to 20 B50s into a standard 2-meter rack enclosure to handle all of your Web hosting, firewall, caching, messaging, e-commerce and other appliance applications. The B50 is available with either AIX or Linux, provides additional disk expansion via an IBM 2104, and features easy plug-in serviceability.

discription.

ERP PERFORMANCE PROTECTION PLAN



Now when you buy an IBM ERP Solution for Baan, Oracle, Peoplesoft or SAP from an IBM Business Partner, you can be sure that it will meet your specified performance expectations during the initial 24 months – or IBM will give you a no-charge performance upgrade. The new 2-year ERP Performance Protection Plan is the first such plan of its kind in the industry.

FOR MORE INFORMATION VISIT
HTTP://WWWRS6000.IBM.COM/SOLUTIONS/ERP/ERP_SOLUTION_SERIES.HTML

Only available in the US.

POWERS SMP HIGH NODE



!!!!!!!!

The new up to 8-way POWER3 SMP High Node is ideal for the full range of I/O- and memory-intensive scientific, technical and commercial applications. It delivers 4 times more processors and memory capacity and 8 times the peak memory bandwidth of SMP Thin and Wide Nodes. Plus, it can be configured with up to 473.2GB of internal storage and a maximum of 53 I/O slots per node.

SEE PAGE 27

2104 EXPANDABLE STORAGE PLUS

Internet Service Providers (ISPs) and other Model B50 users will appreciate the economy and large capacity of the rack-mountable 2104 Expandable Storage Plus storage drawer (or deskside tower).



This low-cost 5.1"-high unit utilizes 80MB/s Ultra2 SCSI (LVD) technology and can house 10 hot-swappable disk drives (9.1GB, 18.2GB or 36.4GB) for a maximum total capacity of 364GB per drawer, or terabytes per rack. Attachment is via supported RS/6000 SCSI adapters with RAID 0, 1 and 5 options.

SEE PAGE 16



Fax Doc 4001





RS/6000 servers	43P Model 140'	43P Model 150	43P I
Machine type	7043	7043	
WORKSTATION/SERVER	workstation/server	workstation/server	works
PACKAGING	tower	tower	
MICROPROCESSOR TYPE	PowerPC 604e	PowerPC 604e	
# processors/system	1	1	
Clock rates available (standard/option)	233/332MHz	375MHz	
SYSTEM MEMORY (STANDARD/MAXIMUM)	64MB/768MB	128MB/1GB	2
Memory type	64-bit ECC DIMM	64-bit ECC DIMM	64-1
Data/instruction (L1) cache	32KB/32KB	32KB/32KB	6
Level 2 (L2) cache	1MB	1MB	
Memory slots	6	4	
RELIABILITY, AVAILABILITY, SERVICEABILITY			
Service processor	No	No	
Hot-swappable disks (internal)	No	No	
CAPACITY			
Slots available	3PCI (32-bit) + 2 PCI/ISA (32-bit)	5 PCI (32-bit)	3 PCI (32
PCI bus speed	33MHz	33MHz	
Disk/media bays	5	5	
Minimum/maximum internal disk	91GB/54.6GB	9.1GB/54.6GB	9
STORAGE INTERFACES			
SCSI-2 F/W RAID-5	No	No	
Ultra SCSI SE and Ultra SCSI Differential	Yes	Yes	
SSA 8-way JBOD/2-way RAID EL	Yes ^h	Yes°	
PCI 3-channel Ultra SCSI RAID	No	Yes°	
Gigabit Fibre Channel	No	No	
PCI 2-Channel Ultra 2 SCSI	or I-lewlett-Perkerd	Yes	
COMMUNICATIONS AND CONNECTIVITY		120000000000000000000000000000000000000	
EIA RS232D/EIA RS422A	Yes	Yes	
Token-Ring 4/16Mbps	Yes	Yes	
Ethernet* 10Mbps	Yes	Yes	
Ethernet 10/100Mbps	Yes	Yes	
Gigabit Ethernet	No	No	
FDDI 100Mbps	Yes	Yes	
ATM 155Mbps	Yes	Yes	
ISDN	Yes	Yes	
X.25 prima visitados our senidados evis	2 harana Ves	Yes	e supraemant
SDLC	Yes	Yes	
BSC	Yes	No	
SP System Attachment	VII SIGNATURE NO XIA	No	
ESCON' Control Unit (Host Attach)	No	No	
ESCON Emulation (Tape Attach)			
HIPPI	No	No	
Direct Talk	Yes	Yes	
GRAPHICS ACCELERATORS AVAILABLE	GXT 130P, 2000P	GXT130P, 2000P, 3000P	GXT13
Benchmarks (see page 13)	STREET THE ORDER OF STREET		
SPEC'web96	-/-		2
SPECint_base95	8.29°/12.2	14.5	
SPECfp_base95	5.48°/5.99	9.76	
SPECint95	9.24°/12.9	15.1	
SPECfp95	5.75°/6.21	10.1	
SPECint_base_rate95	POPE OF TO CHURCH SAID	-	
SPECfp_base_rate95	66 nercent better SPECyteb		
TPC-C':tpmC: \$/tpmC	es ERP 24 year 980 ontraction	-4	
TDO 11:0 1 ON-11 (9 2022)			
TPC-H*:QppH.QthH (@ 300GB)	DATE OF STREET OF STREET STREET, STREET STREET, STREET		
TPC-H:\$/QphD (@ 300GB)	3.9 ° /5.3	6.0	
Relative OLTP performance			

N/A=Not Applicable ⁶=Statement of Direction #=Dual buses *Shared memory *Per processor *MES only *May not be achievable with upgraded 233MHz syr *Up to 512 available via special order *Via microcode driver download













P Model 260' 7043 orkstation/server deskside POWER3 1 or 2 200MHz 256MB/8GB* 64-bit ECC DIMM 64KB/2KB* 4MB* 2 Yes No (32-bit) + 2 PCI (64-bit) 33/50MHz 5 91GB/546GB No Yes	Model B50' 7046 server rack drawer POWERPC 604e 1 375MHz 128MB/1GB 64-bit ECC DIMM 32KB/32KB 1MB 4 No No No 2 PCI (32-bit) 33MHz 2/2 91GB/364GB No Yes Yes No Yes	Model F40' 7025 workstation/server tower PowerPC 604e 1 or 2 233MHz 64-bit ECC DIMM 32KB/32KB* 1MB* 8 Yes (option) Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 22 91GB/3366GB Yes Yes No No	Model F50' 7025 server tower PowerPC 604e 1, 2, 3 or 4 166/332MHz 128MB/3GB* 64-bit ECC DIMM 32KB/32KB* 256KB* 2 Yes Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 18/4 91GB/336.6GB Yes Yes Yes Yes Yes	## Model H50' 7026 **server* **rack drawer* **PowerPC 604e 1, 2, 3 or 4 332MHz 128MB/3GB** 64-bit ECC DIMM 32KB/32KB** 256KB** 2 **Yes **7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 13/3 91GB/2274GB No **Yes Yes Yes Yes Yes	Model H70' 7026 server rack drawer PowerPC RS64-11 1, 2, 3 or 4 340MHz 128MB/8GB* 64-bit ECC DIMM 64KB/64KB* 4MB* 2 Yes Yes 8 PCI (4 32-bit + 4 64-bit) 33/50MHz 13/3 91GB/254.8GB No Yes Yes Yes	Model R 7015 server rack draw Dual PowerPC 2, 4, 6 or 8 200MHz 256MB/4G 72-bit JEDEC \$ 32KB/32KE 2MB* 4 Yes No 15 Micro Char N/A 4 91GB/273C No No No
orkstation/server deskside POWER3 1 or 2 200MHz 256MB/8GB* 64-bit ECC DIMM 64KB/32KB* 4MB* 2 Yes No (32-bit) + 2 PCI (64-bit) 33/50MHz 5 91GB/546GB No Yes	Server rack drawer POWERPC 604e 1 375MHz 128MB/1GB 64-bit ECC DIMM 32KB/32KB 1MB 4 No No No 2 PCI (32-bit) 33MHz 2/2 91GB/364GB No Yes Yes Yes No No No No Yes Yes No No No No No No Yes Yes No No No No No No No N	## Workstation/server tower	**Server** **tower** PowerPC 604e 1, 2, 3 or 4 166/332MHz 128MB/3GB** 64-bit ECC DIMM 32KB/32KB** 256KB** 2 **Yes **Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 18/4 91GB/3366GB **Yes **Yes	Server rack drawer PowerPC 604e 1, 2, 3 or 4 332MHz 128MB/3GB* 64-bit ECC DIMM 32KB/32KB* 256KB* 2 Yes Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 13/3 91GB/2274GB No Yes Yes Yes	Server rack drawer PowerPC RS64-11 1, 2, 3 or 4 340MHz 128MB/8GB* 64-bit ECC DIMM 64KB/64KB* 4MB* 2 Yes Yes 8 PCI (4 32-bit + 4 64-bit) 33/50MHz 13/3 91GB/254.8GB No Yes Yes	Server rack draw Dual PowerPC 2, 4, 6 or 8 200MHz 256MB/4G 72-bit JEDEC \$ 32KB/32KE 2MB* 4 Yes No 15 Micro Chai N/A 4 91GB/273C No No Ves
deskside	rack drawer POWERPC 604e 1 375MHz 128MB/1GB 64-bit ECC DIMM 32KB/32KB 1MB 4 No No 2 PCI (32-bit) 33MHz 2/2 91GB/364GB No Yes Yes No	tower PowerPC 604e 1 or 2 233MHz 64MB/1GB* 64-bit ECC DIMM 32KB/32KB* 1MB* 8 Yes (option) Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 22 91GB/336.6GB Yes Yes No	tower PowerPC 604e 1, 2, 3 or 4 166/332MHz 128MB/3GB* 64-bit ECC DIMM 32KB/32KB* 256KB* 2 Yes Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 18/4 91GB/336.6GB Yes Yes Yes Yes	rack drawer PowerPC 604e 1, 2, 3 or 4 332MHz 128MB/3GB* 64-bit ECC DIMM 32KB/32KB* 256KB* 2 Yes Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 13/3 91GB/2274GB No Yes Yes Yes Yes	rack drawer PowerPC RS64-11 1, 2, 3 or 4 340MHz 128MB/8GB* 64-bit ECC DIMM 64KB/64KB* 4MB* 2 Yes Yes 8 PCI (4 32-bit + 4 64-bit) 33/50MHz 13/3 91GB/254.8GB No Yes Yes Yes	rack draw Dual PowerPC
1 or 2 200MHz 256MB/8GB* 64-bit ECC DIMM 64KB/32KB* 4MB* 2 Yes No (32-bit) + 2 PCI (64-bit) 33/50MHz 5 91GB/54.6GB No Yes	1 375MHz 128MB/1GB 64-bit ECC DIMM 32KB/32KB 1MB 4 No No 2 PCI (32-bit) 33MHz 2/2 91GB/364GB No Yes Yes No	1 or 2 233MHz 64MB/1GB* 64-bit ECC DIMM 32KB/32KB* 1MB* 8 Yes (option) Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 22 91GB/336.6GB Yes Yes No No	1, 2, 3 or 4 166/332MHz 128MB/3GB* 64-bit ECC DIMM 32KB/32KB* 256KB* 2 Yes Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 18/4 91GB/336.6GB Yes Yes Yes Yes	1, 2, 3 or 4 332MHz 128MB/3GB* 64-bit ECC DIMM 32KB/32KB* 256KB* 2 Yes Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 13/3 91GB/2274GB No Yes Yes Yes	1, 2, 3 or 4 340MHz 128MB/8GB* 64-bit ECC DIMM 64KB/64KB* 4MB* 2 Yes Yes 8 PCI (4 32-bit + 4 64-bit) 33/50MHz 13/3 91GB/254.8GB No Yes Yes Yes	Dual PowerPC 2, 4, 6 or 8 200MHz 256MB/4GI 72-bit JEDEC \$ 32KB/32KE 2MB* 4 Yes No 15 Micro Char N/A 4 91GB/273C No No No Yes
200MHz 256MB/8GB* 64-bit ECC DIMM 64KB/32KB* 4MB* 2 Yes No (32-bit) + 2 PCI (64-bit) 33/50MHz 5 91GB/54.6GB No Yes	375MHz 128MB/1GB 64-bit ECC DIMM 32KB/32KB 1MB 4 No No No 2 PCI (32-bit) 33MHz 2/2 91GB/364GB No Yes Yes No	233MHz 64MB/1GB* 64-bit ECC DIMM 32KB/32KB* 1MB* 8 Yes (option) Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 22 91GB/336.6GB Yes Yes No No	166/332MHz 128MB/3GB* 64-bit ECC DIMM 32KB/32KB* 256KB* 2 Yes Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 18/4 91GB/336.6GB Yes Yes Yes Yes	332MHz 128MB/3GB* 64-bit ECC DIMM 32KB/32KB* 256KB* 2 Yes Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 13/3 91GB/2274GB No Yes Yes Yes	340MHz 128MB/8GB* 64-bit ECC DIMM 64KB/64KB* 4MB* 2 Yes Yes 8 PCI (4 32-bit + 4 64-bit) 33/50MHz 13/3 91GB/254.8GB No Yes Yes Yes	2, 4, 6 or 8 200MHz 256MB/4GI 72-bit JEDEC \$ 32KB/32KE 2MB* 4 Yes No 15 Micro Char N/A 4 91GB/273C
256MB/8GB* 64-bit ECC DIMM 64KB/32KB* 4MB* 2 Yes No (32-bit) + 2 PCI (64-bit) 33/50MHz 5 91GB/54.6GB No Yes Yes No Yes	128MB/1GB 64-bit ECC DIMM 32KB/32KB 1MB 4 No No No 2 PCI (32-bit) 33MHz 2/2 91GB/364GB No Yes Yes No	64MB/1GB* 64-bit ECC DIMM 32KB/32KB* 1MB* 8 Yes (option) Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 22 91GB/336.6GB Yes Yes No No	128MB/3GB* 64-bit ECC DIMM 32KB/32KB* 256KB* 2 Yes Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 18/4 91GB/336.6GB Yes Yes Yes Yes	128MB/3GB* 64-bit ECC DIMM 32KB/32KB* 256KB* 2 Yes Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 13/3 91GB/2274GB No Yes Yes Yes	128MB/8GB* 64-bit ECC DIMM 64KB/64KB* 4MB* 2 Yes Yes 8 PCI (4 32-bit + 4 64-bit) 33/50MHz 13/3 91GB/254.8GB No Yes Yes Yes Yes	256MB/4GI 72-bit JEDEC \$ 32KB/32KE 2MB* 4 Yes No 15 Micro Char N/A 4 91GB/273C
64-bit ECC DIMM 64KB/32KB ^b 4MB ^b 2 Yes No (32-bit) + 2 PCI (64-bit) 33/50MHz 5 91GB/546GB No Yes Yes Yes Ves Yes Yes Yes Yes Yes Yes Yes Yes Yes Y	64-bit ECC DIMM 32KB/32KB 1MB 4 No No No 2 PCI (32-bit) 33MHz 2/2 91GB/364GB No Yes Yes No	64-bit ECC DIMM 32KB/32KB* 1MB* 8 Yes (option) Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 22 91GB/336.6GB Yes Yes No No	64-bit ECC DIMM 32KB/32KB* 256KB* 2 Yes Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 18/4 91GB/336.6GB Yes Yes Yes Yes	64-bit ECC DIMM 32KB/32KB* 256KB* 2 Yes Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 13/3 91GB/2274GB No Yes Yes Yes	64-bit ECC DIMM 64KB/64KB ^b 4MB ^b 2 Yes Yes 8 PCI (4 32-bit + 4 64-bit) 33/50MHz 13/3 91GB/2548GB No Yes Yes Yes Yes	72-bit JEDEC \$ 32KB/32KE 2MB* 4 Yes No 15 Micro Char N/A 4 91GB/2730 No No No
64KB/32KB ^b 4MB ^b 2 Yes No (32-bit) + 2 PCI (64-bit) 33/50MHz 5 91GB/546GB No Yes	32KB/32KB 1MB 4 No No No 2 PCI (32-bit) 33MHz 2/2 91GB/364GB No Yes Yes No	32KB/32KB ^b 1MB ^b 8 Yes (option) Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 22 91GB/3366GB Yes Yes Yes No No	32KB/32KB ^b 256KB ^b 2 Yes Yes 7PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 18/4 91GB/3366GB Yes Yes Yes Yes	32KB/32KB* 256KB* 2 Yes Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 13/3 91GB/2274GB No Yes Yes Yes	64KB/64KB ^b 4MB ^b 2 Yes Yes 8 PCI (4 32-bit + 4 64-bit) 33/50MHz 13/3 91GB/2548GB No Yes Yes Yes	32KB/32KE 2MB* 4 Yes No 15 Micro Char N/A 4 91GB/273C No No No Yes
4MB ^b 2 Yes No (32-bit) + 2 PCI (64-bit) 33/50MHz 5 91GB/54.6GB No Yes	1MB 4 No No No 2 PCI (32-bit) 33MHz 2/2 91GB/364GB No Yes Yes No	1MB ^b 8 Yes (option) Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 22 91GB/3366GB Yes Yes Yes No No	256KB ^b 2 Yes Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 18/4 91GB/336.6GB Yes Yes Yes Yes	256KB ^b 2 Yes Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 13/3 91GB/2274GB No Yes Yes Yes	4MB ^b 2 Yes Yes 8 PCI (4 32-bit + 4 64-bit) 33/50MHz 13/3 91GB/254.8GB No Yes Yes Yes	2MB* 4 Yes No 15 Micro Char N/A 4 91 GB/2730 No No Yes
2 Yes No (32-bit) + 2 PCI (64-bit) 33/50MHz 5 91GB/54.6GB No Yes Yes Yes Yes Ves Yes Yes Yes Yes Yes Yes Yes Yes Yes Y	4 No No No 2 PCI (32-bit) 33MHz 2/2 91GB/364GB No Yes Yes No	8 Yes (option) Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 22 91GB/3366GB Yes Yes Yes No No	2 Yes Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 18/4 91GB/336.6GB Yes Yes Yes	2 Yes Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 13/3 91GB/2274GB No Yes Yes Yes	2 Yes Yes 8 PCI (4 32-bit + 4 64-bit) 33/50MHz 13/3 91GB/2548GB No Yes Yes Yes	4 Yes No 15 Micro Char N/A 4 91 GB/2730 No No Yes
No (32-bit) + 2 PCI (64-bit) 33/50MHz 5 91GB/54.6GB No Yes	No 2 PCI (32-bit) 33MHz 2/2 91GB/364GB No Yes Yes No	Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 22 91GB/336.6GB Yes Yes No No	Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 18/4 91GB/336.6GB Yes Yes Yes Yes	Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 13/3 91GB/2274GB No Yes Yes Yes	Yes 8 PCI (4 32-bit + 4 64-bit) 33/50MHz 13/3 91GB/254.8GB No Yes Yes Yes	Yes No 15 Micro Char N/A 4 91GB/2730 No No Yes
No (32-bit) + 2 PCI (64-bit) 33/50MHz 5 91GB/54.6GB No Yes	No 2 PCI (32-bit) 33MHz 2/2 91GB/364GB No Yes Yes No	Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 22 91GB/336.6GB Yes Yes No No	Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 18/4 91GB/336.6GB Yes Yes Yes Yes	Yes 7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 13/3 91GB/2274GB No Yes Yes Yes	Yes 8 PCI (4 32-bit + 4 64-bit) 33/50MHz 13/3 91GB/254.8GB No Yes Yes Yes	No 15 Micro Char N/A 4 91GB/2730 No No Yes
(32-bit) + 2 PCI (64-bit) 33/50MHz 5 91GB/546GB No Yes Yes Yes No Yes	2 PCI (32-bit) 33MHz 2/2 91GB/364GB No Yes Yes Yes No	7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 22 91GB/336.6GB Yes Yes No No	7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 18/4 91GB/336.6GB Yes Yes Yes Yes	7 PCI (5 32-bit + 2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 13/3 91GB/2274GB No Yes Yes Yes	8 PCI (4 32-bit + 4 64-bit) 33/50MHz 13/3 91GB/254.8GB No Yes Yes Yes	15 Micro Char N/A 4 91GB/2730 No No Yes
33/50MHz 5 91GB/546GB No Yes Yes Yes No Yes	33MHz 2/2 91GB/364GB No Yes Yes Yes No	2 64-bit) + 2 PCI/ISA (32-bit) 33/50MHz 22 91GB/336.6GB Yes Yes No No	2 PCI/ISA (32-bit) 33/50MHz 18/4 91GB/336.6GB Yes Yes Yes Yes	2 PCI/ISA (32-bit) 33/50MHz 13/3 9:1GB/2274GB No Yes Yes Yes	33/50MHz 13/3 91GB/254.8GB No Yes Yes	N/A 4 91GB/2730 No No Yes
5 91GB/54.6GB No Yes Yes Yes No Yes	2/2 91GB/364GB No Yes Yes Yes No	22 91GB/336.6GB Yes Yes No No	18/4 91GB/336.6GB Yes Yes Yes Yes Yes	13/3 91GB/2274GB No Yes Yes Yes	13/3 91GB/254.8GB No Yes Yes Yes	4 91GB/2730 No No Yes
91GB/54.6GB No Yes Yes Yes No Yes	91GB/364GB No Yes Yes Yes No	91GB/336.6GB Yes Yes Yes No No	91GB/336.6GB Yes Yes Yes Yes Yes	91GB/2274GB No Yes Yes Yes	91GB/254.8GB No Yes Yes Yes	91GB/2730 No No Yes
No Yes Yes Yes No Yes	No Yes Yes Yes No	Yes Yes Yes No No	Yes Yes Yes Yes	No Yes Yes Yes	No Yes Yes Yes	No No Yes
Yes Yes Yes No Yes	Yes Yes Yes No	Yes Yes No No	Yes Yes Yes	Yes Yes Yes	Yes Yes Yes	No Yes
Yes Yes No Yes	Yes Yes No	Yes No No	Yes Yes	Yes Yes	Yes Yes	No Yes
Yes No Yes	Yes No	No No	Yes	Yes	Yes	
No Yes	No	No				No
Yes			Yes			INU
Yes	ies	Yes	Yes	Yes Yes	Yes Yes	No
Yes	100 DECEMBER 1	якомверный гипогус ос	800 AZESZENE NOBELDEN	TO ANGLES AND DESCRIPTION OF	Federal discount	
Yes Yes Yes Yes Yes Yes Yes Yes Yes	Yes	Yes	Yes	Yes	Yes	Yes
Yes Yes Yes Yes Yes Yes Yes	Yes	Yes	Yes	Yes	Yes	Yes
Yes Yes Yes Yes Yes Yes	No Yes	Yes	Yes	Yes	Yes	Yes
Yes Yes Yes Yes	No	No	Yes Yes	Yes Yes	Yes Yes	Yes
Yes Yes Yes	Yes	Yes	Yes	Yes	Yes	No
Yes	Yes	Yes	Yes	Yes	Yes	Yes Yes
	Yes	Yes	Yes	Yes	Yes	Yes
Yes	Yes	Yes	Yes	Yes	Yes	Yes
V	Yes	Yes	Yes	Yes	Yes	Yes
Yes	No No	Yes	Yes	Yes	Yes	Yes
No No	No No	No No	No Yes	No Yes	No Yes	No
-	-	-	Yes	Yes	Yes	Yes
No	No	No	Yes	Yes	Yes	Yes No
Yes	No	Yes	Yes	Yes	Yes	No
T130P, 2000P, 3000P	GXT130P	GXT 130P	GXT 130Pf	GXT 130P	GXT 130P	-
(1, 2-way)		(1, 2-way)	(1, 2, 3 or 4-way)	(1, 2, 3, 4-way)	(1, 2, 3, 4-way)	(2, 4, 6, or 8-
2654 (2-way)	14.5	700	2148/6716 (4-way)	6716 (4-way)	11774 (4-way)	-
11.5 25.1	14.5 9.76	7.80 5.60	6.79/14.0 8.11/12.1	14.0 12.1	13.7	-
12.5	15.1	8.71	7.52/14.4	14.4	16.0	-
27.0	10.1	5.87	8.52/12.6	12.6	21.2	-
104, 205	No	69.9,132	61.0, 121, -, 241/124, 245, 365, 485	124, 245, 385, 485	144, 287, 430, 573	121, 244, 343
225, 434	No	50.1, 89.5	72.8, 143, -, 267/109, 206, 292, 364	109, 206, 292, 364	182, 354, 512, 645	90.3, 176, 248
The County of th	No	A SEA PROOF CAMES A RECENT	8142.40, 63 (4-way, 166MHz), 9853.13, 65 (4-way, 332MHz)	BLZ days of your clude makes of your clude makes	17133.73,79 (4-way)	9165.13; 99 (8
	No	Aumented 1152 - House Amenda a	Contract is an area of a second of a second of	Archienne-Cappings to		-
105.210		- 27.50	- 8.2, 14.9, 21.0, 271/10.0, 17.9, 25.2, 32.8	10.0, 17.9, 25.2, 32.8	-	-
10.5, 21.0 \$19,000	No 6.0	3.7, 5.2			16.6, 31.9, 44.2, 57.1	9.3, 17.0, 23.6









Graphics Accelerators



RS/6000 Workstation performance	140'(332M
GRAPHICS ACCELERATORS	GXT2000P
GPC/XPC Xmark93	35.6
GPC/PLB PLBwire93	169
GPC/PLB PLBsurf93	350
GPC/OPC ProCDRS-02	7.2
GPC/OPC DX-05	8.35
GPC/OPC DRV-06	4.68
SPEC/OPC Light-03	0.92
GPC/OPC AWadvs-02	12.2

Software

RS/6000 Software	140'.
OPERATING SYSTEM SUPPORT	
AIX° 4.2 (5735-C34)	X
AIX 4.3 (5755-C34)	X
LINUX	
HACMP (5765-D28)	X

RS/6000 Software	H50
OPERATING SYSTEM SUPPORT	
AIX 4.2	X
AIX 4.3	X
LINUX	
HACMP	X

OPERATING SYSTEM SUPPORT		
AIX 4.2	X	X
AIX 4.3	4.3.1+	4.3.1+
LINUX		-
НАСМР	X	X

¹ Multi-threaded graphics API which exploits SMP available ² Enabled ^{*} Supported

Visit the RS/60

For Physical Planning \

The IBM RS/6000 Models and AIX V4[†] offered in this catalog are...

Year 2000 ready[#]

For additional information on www.ibm.com/year2000

[†]Current users of AIX* V4 may require Program Temporary Fixes

"Year 2000 ready means the product, when used in accordance and/or receiving date data within and between the twentieth an

Information provided in this catalog and information contained Information and Readiness Disclosure Act of 1998, a U.S statuticon on IBM's Year 2000 Web site (www.rs6000.ibm.com/s they are provided.

Model R50	Model S70	Model S80
7015	Advanced 7017	7017
server	server	server
rack drawer	rack mounted	rack mounted
ual PowerPC 604e	PowerPC RS64 II	PowerPC RS64 III
2, 4, 6 or 8	4, 8 or 12	6, 12, 18 or 24
200MHz	262MHz	450MHz
256MB/4GB*	1GB/32GB*	2GB/64GB*
2-bit JEDEC SIMM	Card-based ECC SDRAM	Card-based ECC SDRAM
11	64KB/64KB ^b	128KB/128KB ^b
32KB/32KB ^b		
2MB ^b	8MB ^b	8MB*
4	20	16
Yes	Yes	Yes
No	Yes	Yes
5 Micro Channel®	53 PCI (33 32-bit + 20 64-bit)	53 PCI (33 32-bit + 20 64-bit)
N/A	33MHz	33MHz
42 Lioney ec	48/8	48/8
9:1GB/27:3GB	9.1 GB/873.6GB	9.1 GB/873.6 GB
NOHO-CIGSS	HIM SSALISOD & 10 SIDAGSE	
No	and many has No and an analysis	No
No	Yes	Yes
Yes	Yes	Yes
No	No No	No
No	Yes	Yes
T - Service	Yes	Yes
Yes	Yes	Yes
Yes	Yes	Yes
Yes	Yes	Yes
The second second second second	Yes	Yes
Yes	AGE HOSTO - HOLY - ASTO LE UNI GARAGE.	
No	Yes	Yes
Yes	Yes	Yes
No	Yes	Yes
Yes	Yes	Yes
Yes	Yes	Yes
No	No	400
No	Yes	Yes
Fo= rapderate work	GXT130P	GXT130P
(2, 4, 6, or 8-way)	(4, 8, or 12-way)	(6, 12, 18, 24-way)
-	20200 (12-way)	40, 161 (12-way)
- 100	_	
_		
11 - 0		
101 044 040 445	TARREST TARREST	
121, 244, 343, 445	THE YORK THE WALL SE	
90.3, 176, 248, 320	110 42410 122 (5 pada alimbar)	
9165.13; 99 (8-way)	110, 434.10, 122 (5 node cluster)	
- 1000		
-	- 1	
9.3, 17.0, 23.6, 30.6	46.0, 82.7, 113.8	123.3, 233.3, 326.7, 400.0
\$64,000	\$125,000	\$290,000







140'(332MHz)	150'	260'
GXT2000P	GXT2000P	GXT3000P (2-way)
35.6	42.6	35.6
169	257	714
350	466	898
7.2	11.2	24.5
8.35	11.0	14.7
4.68	6.19	6.44
0.92	1.12	0.97
12.2	15.4	13.2

140'	150'	260'	B50'	F40'	F50'
					A STATE OF THE STA
X	Χ	X	organ paragritorise ball	Χ	X
X	4.3.2+	4.3.2+	4.3.2+	X	X
-			X²		
X	X	X	COLUMN - MARKEUDALD	X	X

H50	H70	R50	S70 Advanced	S80	
X	-	X		and the second s	
Χ	4.3.2+	Χ	4.3.2+	4.3.3	
-					
Χ	X	X	X	Χ	

SP 332 MP Wide	SP 160 Thin	SP POWER3 SMP Thin	SP POWER3 SMP Wide	SP POWER3 SMP HIGH	T 70
X	X	ficeulst enhalt-up/W nec al	at 9M2 to me lukusad vaan	nomotesis en taes in 8 februari	is in the second
4.3.1+	4.3.1+	4.3.2+	4.3.2+	4.3.2+	4.3.2+
-		nour led stole 75 rectionan	THERE IS DUE TO STORE SHITS		
X	X	X	X	Χ	X

RS/6000 Web site at www.rs6000.ibm.com

al Planning Visit http://www.rs6000.ibm.com/resource/hardware_docs/

formation on Year 2000 readiness, refer to the Year 2000 implementation and planning guide at:

ire Program Temporary Fixes to be Year 2000 ready.

uct, when used in accordance with its associated documentation and with any applicable program temporary fixes, corrective service deliveries or similar requirements installed, is capable of correctly processing, providing and between the twentieth and twenty-first centuries, provided that all other products (for example, hardware, software and firmware) used with the product properly exchange accurate date data with it.

ag and information contained on IBM's past and present Year 2000 Internet Web site pages regarding products and services offered by IBM and its subsidiaries are "Year 2000 Readiness Disclosures" under the Year 2000 sure Act of 1998, a U.S statute enacted on October 19, 1998. IBM's Year 2000 Internet Web site pages have been and will continue to be our primary mechanism for communicating Year 2000 information. Please see the "legal" (www.rs6000.ibm.com/solutions/y2k) for further information regarding this statute and its applicability to IBM. IBM's obligations regarding its products and services are governed solely by the agreements under which





The RS/6000

RS/6000 e-business Solutions

From Web servers to commercial applications to Internet service providers, to security, IBM offers a full menu of RS/6000 Solution Series for e-business offerings to start you fast, with confidence.

RS/6000 Solution Series for e-business provides ease of entry into the various aspects of e-business, with world-class software integrated with the full line of RS/6000 hardware products, backed by IBM service and support.

How do you get started?

- **1.** Select the RS/6000 e-business software to meet your business needs
 - **IBM WebSphere**
 - Lotus Domino
 - **IBM Net.Commerce**
 - **IBM eNetwork FireWall**
 - **Check Point FireWall-1**
- **2.** Select the RS/6000 platform that meets your requirements
- **3.** Select any specific add-on products you may want

FROM PAGES 9-13

Solution Series for e-business

WEB APPLICATION SERVER SOLUTION

WebSphere

Build and deploy standards-based Web applications for strengthening customer relationships and publishing dynamic, interactive and personalized content



Highlights:

- **Exploits AIX industry-leading Internet** server capabilities
- Supports Enterprise JavaBeans with the reliability necessary for transactional applications
- Includes IBM's security enhancements to the Apache Web server

Advantages:

- Industry-leading Java** performance on an industrial-strength, e-business-ready **AIX operating environment**
- Tight linkage between server capabilities and IBM VisualAge* for Java development environment, to enable easy applicationcreation testing and deployment of e-business applications
- Scalability to meet the performance requirements of any business

Services Available:

43P Model 150

For Web Application Server Solution services from initial installation, configuration and setup through advanced application development, see:

http://www.software.ibm.com/webservers/vaconsul.html#1

For more information, contact:

RS/6000 at our Web site: www.rs6000.ibm.com/solutions/e-business/ and access the solutions section or contact one of our e-business specialists at 800 426-2255

Small Configuration Medium Configuration Large Configuration HA Configuration Supports hundreds of thousands **Supports thousands** Supports hundreds of thousands **Supports millions** of Web page views per day with no single point of failure For moderate workloads requiring legacy For co-location of Web applications and data Advanced clustering technology for virtually integration and application connectivity for moderate to heavy workloads infinite scalability and services

Model S80

Model F50

www.ibm.com/Shop call 800 426 2255 today



e-COLLABORATION SERVER SOLUTION

Lotus Domino

dow/wc

Lotus.

Share and distribute information within your organization for better productivity and competitiveness

Highlights:

- Provides secure and easy access to business applications and processes for employees and customers using industrystandard Internet protocols
- Provides reliable, integrated productivity support through e-mail, shared calendaring and collaboration tools and rich document database support
- Assists companies in the development and management of their Web presence and image, with functionality to support secure Web publishing to interactive customer support

Advantages:


- Allows deployment of companywide business solutions that support a variety of clients (Web browsers, Lotus Notes and others), delivered using Internet-based technology
- Provides integrated tools to support the development and management of interactive Web applications
- Start with simple configurations to support a small user community and grow uninterrupted to support hundreds of thousands of users with unmatched reliability

Services Available:

■ SmoothStart Services for Lotus Domino Server are available. See page 73 for more information.

For more information, contact:

RS/6000 at our Web site: www.rs6000.ibm.com/solutions/e-business/ and access the solutions section or contact one of our e-business specialists at 800 426-2255



visit

www.ibm.com/Shop call 800 426 2255 today

ELECTRONIC COMMERCE SOLUTION

IBM Net.Commerce

Do secure business on the Internet with your customers or suppliers

Highlights:

- Create a virtual storefront or online catalog and securely process sales transactions and accept electronic payment over the Web from customers around the world
- Provide product promotions, identify customer buying patterns and preferences, and customize incentives for each customer or product
- Complemented by a range of Partner products for customer service, catalog content creation, online payment authorization and settlement worldwide, ad management, personalization, data mining and others, which can be found at: http://www.software.ibm.com/commerce/net.commerce

Advantages:

- Helps increase your top-line sales and attract new customers while controlling overhead costs normally associated with bringing on additional salespeople and traditional brick-and-mortar stores
- Provides for integration with back-end business management systems like inventory for checking product availability prior to order confirmation and updating order management after processing an online order
- High-availability configurations help ensure that your virtual storefront will be online
 24 hours a day, 365 days a year, providing a mature, proven solution for protection from unplanned system outages

<u>e</u>

Launch your
Net. Commerce
Solutions.
IBM RS/6000
Start Now for
e-Commerce can help.
See page 3

For more information, contact:

RS/6000 at our Web site: **www.rs6000.ibm.com/solutions/e-business/** and access the solutions section or contact one of our e-business specialists at **800 426-2255.**

For mid-sized businesses needing to quickly set up an e-commerce site with Net.Commerce, which includes store creation wizard, three starter stores, Domino Go Webserver, CommercePOINT eTill and DB2*

Small Configuration



Medium Configuration

For more advanced businesses looking to build a highly available, second-generation Web site with advanced cataloging tools and back-end integration with SAP, EDI, MQSeries*, CICS*, IMS through Net.Commerce Pro



Large Configuration

For the most scalable, most responsive and most available virtual storefront in the industry when combined with Net.Commerce Pro and Partner product used by many of the industry's leading online retailers



Model F50

HA-H70

SP



SECURITY SOLUTIONS

Check Point FireWall-1

IBM eNetwork Firewall

Help protect your data and control access with firewall technology that provides a secure connection to the world of e-business



Highlights:

- Central management console with distributed security rules enforcement enables consistent policies across the enterprise
- Modular architecture offers seamless scalability from a single location to a global enterprise
- Wide range of complementary network security applications available to provide content screening, monitoring/reporting, intrusion detection, load balancing and much more

Advantages:

- Superior security through enhanced **IP Security and Virtual Private Network** support built into AIX 4.3
- **IBM-mature, industrial-strength AIX** blocks known hacker entry points and is ITSEC C2/E3-certified
- RS/6000-proven performance delivers outstanding TCP/IP throughput and scalability
- High-availability options help prevent firewall from being single point of failure for e-business network

Services Available:

■ Installation services are available through IBM Business Partners. See http://solsrc.rs6000.ibm.com/searchbp and select the firePOWER specialty for a list of qualified partners

For more information, contact:

RS/6000 at our Web site: www.rs6000.ibm.com/solutions/e-business/ and access the solutions section contact or one of our e-business specialists at 800 426-2255



Model 43P-150

Model 43P-260

HA50

SERVICE PROVIDER SOLUTIONS

Provide secure, reliable and high-performance Web content, e-commerce and e-mail hosting designed exclusively for Service Providers

Network Appliances:

- Firewall
 - Check Point FireWall-1
 - IBM e-Network Firewall
- Caching Proxy
 - IBM Web Traffic Express*
 - Squid (Public Domain)
- Load Balancing
 - IBM e-Network Dispatcher*
 - Resonate Dispatch

'Included in Websphere Performance Pack

e-mail Hosting Services:

- Software.com Intermail
- Netscape Messaging Server
- Lotus Domino
- POP3/IMAP4/Sendmail (Included in AIX)

Web Content Hosting Services:

- Apache (Public Domain)
- IBM WebSphere
- Netscape Enterprise Server
- Lotus Domino
- Chili!Soft ASP V3.0 Developer Edition (5 users)
- Microsoft Front Page Server Extensions

e-commerce Hosting Services:

- IBM Net.Commerce
- Mercantec SoftCart
- Intershop4

For more information, contact:

RS/6000 at our Web site: www.rs6000.ibm.com/solutions/e-business/ and access the solutions section or contact one of our e-business specialists at 800 426-2255

Single Configuration Multiple Configuration Multi-Tier Configuration Single Model B50 server dedicated to an application like Firewall, Dedicated Model B50 front-end Webservers, SMTP Servers or Multiple Model B50 dedicated servers running single application Caching Proxy, Webserver, or e-mail server like Firewall, Webserver or e-mail e-Commerce application servers. Network attached to back-end database server

Model B50

Model B50

Model B50 and H50/H70

visit www.ibm.com/Shop call 800 426 2255 today

Outstanding SMP performance for workstation and server applications

43P Model 260







The Model 260 Workstation/Server shown. Monitor, keyboard and mouse not included. See page 33 for information on P Series Monitors

- 256MB to 8GB of ECC SDRAM system memory
- 9.1-54.6GB Ultra SCSI System Disk
- Two disk drive bays/Three media bays
- 5 PCI slots (two 64-bit, three 32-bit)
- 10/100Mpbs Integrated Ethernet
- 1-2 way Symmetric Multiprocessing (SMP)
- 64-bit 200MHz POWER3 processors, with 4 MB L2 Cache per processor.

The IBM RS/6000 43P 7043 Model 260 has the power to be whatever you want it to be - a single-seat MCAD design and analysis workstation, an Internet server, or even a costeffective platform for developing and testing 64-bit SMP applications designed to run on larger RS/6000 systems. The compact, deskside Model 260 is an affordable 64-bit, 1- or 2-way SMP system with application support, powerful graphics options, and extended floating point capabilities that make it possible to perform both design and analysis on a single system. Plus, its SMP capabilities and robust set of DASD and communications features make the Model 260 an excellent choice for meeting a wide range of entry-level server requirements.

Start with a basic 1-way Model 260 with 200MHz POWER3 processor and 256MB of memory and modularly expand it into a fully configured 2-way SMP system with up to 8GB of system memory, 54.6GB of Ultra SCSI disk storage and five PCI slots (two 64-bit and three 32-bit). The Model 260 includes 4MB of L2 cache for each processor, a 9.1GB Ultra SCSI disk drive, 32X maximum speed CD-ROM drive, 1.44MB 3.5-inch diskette drive, and support for both 32-bit and 64-bit applications. You can economically mix and match storage devices with an integrated service processor, Ethernet, and both Ultra SCSI and Ultra-2 SCSI controllers integrated on the Model 260's planar. A variety of 2D and 3D graphics adapters, including the powerful new GXT2000P and GXT3000P 3D Graphics Accelerators, are also available for the Model 260.

The AIX V4.2.1 or AIX V4.3.2 operating system is supported on the Model 260.

Feature	Туре	Mod	Description	Lease [†]	Price
	7043	260	43P-260 200MHz POWER3 SMP	day more *A	\$19,000
CPU Options		cor anarialiste s	business specialists at 800 426 428 438 and and	ectione of our e-	strico
▶ 4342			2nd 200MHz POWER3		\$8,000
▶ 4107			64MB SDRAM (2-32MB DIMMS)		\$640
► 4110			256MB SDRAM (2-128MB DIMMS)		\$2,560
4119			512MB SDRAM		\$6,400
▶ 2908		Maratan ja gottalige	9.1GB Ultra SCSI	ds ha or calcalcad tevres:	\$1,300
2909	nagesa yapa calali serveis. Per	00-9	18.2GB Ultra SCSI	n-a to saviougies proof or	\$2,300
▶ 4098	VIEW SECTION (SECTION 2014)		Ram Card for Expansion Slot 2GB		\$1,038
Color Monitors for 43	P Model 260				
▶ 3629			17" P76 (viewable image size of 16.0") Pearl White		\$995
▶ 3630			21" P260 (viewable image size of 19.8") Pearl White		\$1,995
▶ 3627			17" P76 (viewable image size of 16.0") Stealth Black		\$995
▶ 3628			21" P260 (viewable image size of 19.8") Stealth Black		\$1,995

FCC Class B (Defined on page 4)

System Dimensions: 16.5"W x 18.1"D x 6.5"H

For Benchmarks, check out the 4-page Power Lineup chart inside pages 6 and 7. † Turn to page 76 for details on lease payment information

* PLEASE CALL FOR LATEST PRICES

▶ 24 Hour QuickShip Custom QuickShip

Higher performance than the Model 140, still at a low price

43P Model 150



The Model 150 Workstation/Server shown with the P72 Monitor (not included) displaying the RS/6000 CATIA Welcome Center. Keyboard and mouse not included

- 375MHz PowerPC 604e Processor
- 128MB 1GB ECC SDRAM memory
- 1MB of L2 cache
- 9.1GB 54.6GB Ultra SCSI disk drive
- Optional 10/100Mbps integrated Ethernet

The IBM RS/6000 43P 7043 Model 150 PCI-based desktop system is a cost effective entry-level server. It features an enhanced memory controller that enables the use of SDRAM memory and a faster 83MHz memory bus speed, five PCI slots and five bays for expansion, 32X (Max.) CD-ROM drive, 1.44MB 3.5-inch diskette drive and your choice of AIX V4.2.1 or AIX V4.3.2. The 150 with the GXT2000P graphics accelerator provides outstanding price/performance as a design workstation.

	Туре	Mod	Description	Lease [†]	Price
D	7043	150	43P-150 375MHz	*	\$9,995

Turn to page 76 for details on lease payment information FCC Class B (Defined on page 4)

See page 50 for information on P Series Monitors.

System Dimensions: 16.5"W x 18.1"D x 6.5"H

For Benchmarks, check out the 4-page Power Lineup chart inside pages 6 and 7.

* PLEASE CALL FOR LATEST PRICES

Options

Feature	Description	Price
▶ 4150	128MB SDRAM	\$896
▶ 4169	258MB SDRAM	\$1,792
▶ 2908	9.1GB Ultra SCSI	\$1,300
▶ 2909	18.2GB Ultra SCSI	\$2,300

▶ 24 Hour QuickShip

An affordable, high-performance PCI platform

43P Model 140



- 233 or 332MHz PowerPC 604e
- 64MB 768MB ECC memory
- 1MB Synchronous Level 2 cache
- 9.1GB 54.6GB SCSI-2 disk drive
- Five expansion slots (3 PCI, 2PSI/ISA shared)
- 20X (Max.) 600MB CD-ROM drive
- Integrated SCSI and Ethernet controllers.

The Model 140 excels as a powerful graphics workstation. It is upgradeable from 233MHz to 332MHz, and supports AIX V4.1.5, AIX V4.2.1 or AIX V4.3.

_	Туре	Mod	Description	Lease†	Price
D	7043	140	Model 43P-140 233MHz	*	\$5,250
>			Model 43P-140 332MHz	*	\$7,295

Turn to page 76 for details on lease payment information.

FCC Class B (Defined on page 4)

Current users of AIX V4 may require Program Temporary Fixes to be Year 2000 ready.

PLEASE CALL FOR LATEST PRICES

Options

Feature	Description	Price
4102	Upgrade to 128MB ECC DIMM	\$448
▶ 4114	64MB ECC Memory DIMMs	\$448
► 4115	128MB ECC Memory DIMMs	\$896
▶ 2908	9.1GB Ultra SCSI	\$1,300
▶ 2909	18.2GB Ultra SCSI	\$2,300

Systems Dimenstions: 16.5"W x 18.1"D x 6.5"H

For Benchmarks, check out the 4-page Power Lineup chart inside pages 6 and 7.

▶ 24 Hour QuickShip







Optimized for Internet and application service providers

Enterprise Server Model B50

For e-business solutions See page 13





- Ideal for dedicated "appliance" solutions such as Web hosting, firewall, caching, messaging or e-commerce
- Space-saving industry standard 2U 19" rackmount form factor ideal for large "server farm" environments
- Plug-in serviceability and toolless access to all major system components
- Comprehensive remote setup and system management features, like AIX Web System Management and Tivoli offerings
- High level of network connectivity, with built-in 10/100Mbps Ethernet, and support for high-speed protocols such as FDDI, ATM and ISDN
- Ultra-SCSI and SSA RAID storage external device options for improved data transfer performance and availability
- Supports award winning AIX Version 4.3, enabled for Linux and popular freeware applications.

The IBM® RS/6000 Enterprise Server Model B50 was

created specifically for the service provider industry. As a high performance UNIX solution platform, the RS/6000 product family is ideally suited for service provider applications including Web hosting, caching, messaging, firewalls, directory services and e-commerce.

The RS/6000 Model B50 has a mix of performance and features optimized for service provider needs, with:

- RISC-based PowerPC* 604e processor running at 375 MHz
- 128MB of main memory, expandable to 1GB
- 1MB Level 2 cache
- Performance enhanced AIX 4.3.3

The Model B50 server delivers a variety of high-performance, Web-serving features in a space saving, 2U (3.5") package designed specifically for industry standard 19" rack enclosures. This rack-mount packaging enables packaging as many as up to 20 servers, 60 discrete network connections and over 720GB of internal storage.

The reliability, availability and serviceability

(RAS) features required by today's business-critical computing environments are built into the Model B50. For example, Error Checking and Correcting (ECC) memory helps detect and correct single-bit errors on the fly. An easy-to-read LED operator status panel on the front of the system keeps you informed of its status at a glance. Concurrent diagnostics enable troubleshooting minor problems that may occur without forcing a system shutdown.

Getting on-line, staying on-line

The Model B50 is an excellent choice for applications that require high availability and rock-solid reliability. As an established, proven platform, the RS/6000 supports rapid deployment of popular offerings, business critical applications and network infrastructure.

The New 2104 Expandable Storage Plus provides a compact, 5.1" (3u) high, 21.8" deep, 19" wide, rack-mountable storage drawer ideal for Internet and application service providers who need mass storage and/or require the hotswap feature. This low-cost, 10-drive, storage enclosure features high-performance 80MB/s Ultra2 SCSI (LVD) technology. It scales easily from 9-364GB per drawer to terabytes per rack. And, it features hot-swappable 9.1GB, 18.2GB and 36.4GB disk drives. Attachment via supported IBM RS/6000 SCSI RAID adapters can enhance storage protection with RAID 0, 1 and 5 options.

Visit our Web site at: www.rs6000.ibm.com

Туре	Mod 1999-1990 ho	Description	Price
7046	B50	Model B50	\$3,995

Call for prices for Model B50 features.

FCC Class A defined on page 4 Dimensions 3.5"H x 19"W x 24"D (standard 2u rack mount)

Servers At-a-Glance

Servers

	Model F40	Model F50	Model B50
Packaging	Deskside	Deskside	Rack drawer
Operating System (Your choice at no additional charge.)	AIX V4.3	AIX V4.3	AIX V.4.3.3 or AIX V4.3.2
MP Configurations	1- or 2-way	1-, 2-, 3- or 4-way	Uni
Processor Type	PowerPC 604e, 233MHz	PowerPC 604e, 166MHz/332MHz	PowerPC 604e 375MHz
Memory	64MB-1GB	128MB-3GB	128MB - 1GB
Memory Slots	8	2	4
Standard SCSI Disk	9.1GB	9.1GB	9.1GB
Cache Memory per Processor	32KB/32KB L1, 1MB L2	32KB/32KB L1, 256KB L2	32KB/32KB L1, 1MB L2
I/O Bus	PCI	PCI	32b PCI
Number of I/O Buses	2	3	1 de sales de la sego ini les de
I/O Bandwidth (MB/sec.)	246	400	132
I/O Slots Available	9	9	2 (1 full length, 1 half length)
Disk Bays Available	18	18	2 avail. for 9.1GB or 18.2GB drives
Media Bays Available	4	4	diskette & 32X CD-ROM standard
"Hot-Pluggable" Disks	Yes	Yes	no
Optional Keyboard/Mouse Support	Yes	Yes	yes
SCSI-2 F/W Adapter	Yes	Yes	yes
Tray Loading CD-ROM Drive	Yes	Yes	yes standard
1.44MB Diskette Drive	Yes	Yes	yes standard
1 Parallel/3 Serial Ports	Yes	Yes	1 parallel, 2 serial
Lease ^{rt}	*	*	*
Price	\$9,900 [†]	\$13,900/17,900 [†]	\$3,995†

	Model H50	Model H70	Model R50	Model S70 Advanced	Model S80
Packaging	Rack drawer	Rack drawer	Rack drawer	Rack mounted	Rack mounted
Operating System (Your choice at no additional charge.)	AIX V4.3	AIX V.4.3.3 or V4.3.2	AIX V4.3	AIX V.4.3.3 or V4.3.2	AIX V4.3.3
MP Configurations	1-, 2-, 3- or 4-way	1-, 2-, 3- or 4-way	2-, 4-, 6- or 8-way	4-, 8- or 12-way	6-, 12-, 18- or 24-way
Processor Type	PowerPC 604e, 332MHz	PowerPC RS64-II, 340MHz	PowerPC 604e, 200MHz	PowerPC RS64 II	PowerPC RS64 III
Memory	128MB-3GB	128MB-8GB	256MB-4GB	1GB-32GB	2GB - 64GB
Memory Slots	2	2	4	20	16
Standard SCSI Disk	9.1GB	9.1GB	9.1GB	9.1GB	9.1GB
Cache Memory per Processor	32KB/32KB L1, 256KB L2	64KB/64KB L1, 4MB L2	32KB/32KB L1, 2MB L2	64KB/64KB L1 8MB L2	128KB/128KB L1, 8MB L2
I/O Bus	PCI	PCI	Micro Channel	PCI	PCI
Number of I/O Buses	3	4 Assessment of A	2	4-16	4-16
I/O Bandwidth (MB/s)	400	528	160	500	500MB/s per I/O drawer
I/O Slots Available	9	8	15	11 minimum, 53 max.	11 minimum, 53 max.
Disk Bays Available	13	13	4	11 minimum, 47 max.	11 minimum, 47 max.
Media Bays Available	3	3	4	1 minimum, 7 max.	1 minimum, 7 max.
"Hot-Pluggable" Disks	Yes	Yes	No	Yes	Yes
Optional Keyboard/Mouse Support	Yes	Yes	Yes	Yes	Yes
SCSI-2 F/W Adapter	Yes	Yes	Yes	UltraSCSI	UltraSCSI
Tray Loading CD-ROM Drive	Yes	Yes	Yes	Yes	Yes
1.44MB Diskette Drive	Yes	Yes	Yes	Yes	Yes
1 Parallel/3 Serial Ports	Yes	Yes	Yes	1 parallel, 2 serial ports	1 parallel, 2 serial ports
SSA RAID Adapter	Yes	Yes	Yes	Yes	Yes
Lease ^H	*	* Pacas NII) area d 115WU1	*	*	*
Price	\$22,000 [†]	\$26,900 [†]	\$64,000 [†]	\$125,000 [†]	\$290,000 [†]

[†] Includes AIX base license.

†† Turn to page 76 for details on lease payment information.

FCC Class A (Defined on page 4)


* PLEASE CALL FOR LATEST PRICES

Servers for workgroups


Workgroup Server Model F40

Fax Document 6309





- 7 PCI, 2 PCI/ISA slots
- 64MB ECC memory (expandable to 1GB)
- 1MB Level 2 cache per 233MHz processor
- Dual integrated SCSI-2 F/W controllers
- Up to 345.8GB internal disk storage
- SSA adapter available as an optional feature
- 9.1GB or 18.2GB disk drives
- Ultra SCSI. SCSI F/W or SCSI F/W RAID
- 20X (Max.) speed tray loading SCSI-2 CD-ROM drive
- 5 available hot-swap disk bays and 2 available media bays (plus 12 optional hot-swap disk bays)
- Optional service processor to help ensure high availability
- 1.44MB diskette drive
- Two serial ports, one parallel port
- AIX V4.3 is included in the base price.



426-4329

IBM's powerful Model F40 is one of our most expandable PCI workgroup servers, operating as a high-performance 1- or 2-way Symmetric Multiprocessing (SMP) system. Using IBM's AIX Connection software, a full range of clients - AIX, DOS, Windows** and MacOS - can attach to the F40.

An upgrade to the Model F50 with serial number protection is offered.

Туре	Mod	Description	Lease	Price
7025	F40	233MHz 604e	the selection of the control of the selection of the sele	\$9,900

[†] Turn to page 76 for details on lease payment information

FCC Class A (Defined on page 4)

* PLEASE CALL FOR LATEST PRICES

CPU Options

Feature	Description	Price
▶ 4306	2nd 166MHz PowerPC 604e (for 166MHz systems)	\$2,000
▶ 4341	2nd 233MHz PowerPC 604e (for 233MHz systems)	\$2,000

Memory Options

Feature	Description	Price
4129	Upgrade to 64MB ECC DIMM	\$224
► 4114	Additional 64MB ECC DIMM	\$448

Additional Internal Storage Options - see page 30

See page 50 for color monitor options. System Dimensions: 9.6"W x 27.3"D x 24.3"H For Benchmarks, check out the 4-page Power Lineup chart inside pages 6 and 7. Expand to SMP - Enhance your uniprocessor system with a second 233MHz PowerPC 604e. ▶ 24 Hour QuickShip

Top-rated Web Server

Workstation/Server Model F50

Fax Document 7614

- New! 10K rpm 9.1GB Ultra SCSI and SSA drives for improved performance
- One, two, three or four 166MHz or 332MHz PowerPc processors with X5 Cache
- 128MB synchronous DRAM memory (expandable to 3GB) with peak memory bandwidth of 1.3GB/s
- 256KB 8-way, set-associative Level 2 cache per processor (expandable to 4 processors)
- 9.1GB or 18.2GB disk drives for a maximum capacity of 345.8GB
- 7 PCI and 2 shared PCI/ISA slots.

The versatile Model F50 has a faster processor selection and is an excellent choice as either a high-end workgroup server or an entry-level enterprise server. It also boasts an aggregate I/O data rate of up to 400MB/second, using three I/O buses for nine slots. (Two 64-bit PCI slots connect to one bus, three 32-bit PCI slots connect to a second and the remaining four 32-bit slots [2 PCI, 2 PCI/ISA] connect to the third I/O bus.)

The F50 also features four media bays and 18 hot-swappable disk bays with three optional interconnect standards: SCSI-2 Fast/Wide, Ultra SCSI and SSA. An optional, integrated SSA RAID controller eliminates the need for an external SSA RAID

Upgrade to the Model H70 with serial number protection.



Model F50









-	Туре	Mod	Description 19/10/10/00	mod aulo. p.a. pnii Leaset au	Price
D	7025	F50	166MHz 604e	* Silver see	\$13,900 ¹
D	7025	F50	PowerPC 604e 332MHz 1-way Processor Card	*	\$17,900 ¹

Feature	Description	Price
CPU Options	The boundaries and the second of the second	
▶ 4307	PowerPC 604e 166MHz 1-way Processor Card with 256KB L2 Cache (F50)	\$3,000
▶ 4309	PowerPC 604e 166MHz 2-way Processor Card with 2x256KB L2 Cache (F50)	\$6,000
4356	PowerPC 604e 332MHz 1-way Processor Card	\$4,000 ¹
4357	PowerPC 604e 332MHz 2-way Processor Card Select	\$7,000 ¹
▶ 4358	PowerPC 604e 332MHz 1-way Processor Card	\$7,000
▶ 4359	PowerPC 604e 332MHz 2-way Processor Card	\$10,000
Memory Options	betternoodbydingteroppings trahennoo	
4106	256MB (2X128MB), DIMMS	\$1,280 ¹
▶ 4107	64MB (2X32MB), DIMMS	\$640

Additional Internal Storage Options - see page 30

[†] Turn to page 76 for details on lease payment information. FCC Class A (Defined on page 4) See page 50 for color monitor options Dimensions: 9.6"W x 27.3"D x 24.3"H For Benchmarks, check out the 4-page Power Lineup chart inside pages 6 and 7.

PLEASE CALL FOR LATEST PRICES

Reduced Price

Custom QuickShip

Superior SMP price/performance with rack-drawer expandability

RS/6000 Enterprise Server Model H50





The IBM RS/6000 Enterprise Server Model H50, a rackdrawer, PCI-based, 1-4 way Symmetric Multiprocessing (SMP) server is designed to deliver unprecedented price/ performance among systems in its class. It provides outstanding ease of use, sophisticated system and network management capabilities, and excellent reliability, availability and serviceability (RAS). The H50 is ideal for a variety of enterprise computing environments including:

- enterprise resource planning
- e-business applications
- business intelligence applications
- collaborative computing, e.g. Lotus Domino or other groupware applications

The H50 features IBM's enhanced X5 Cache system with the powerful 332MHz PowerPC 604e processors. It comes with 128MB and expands to 3GB of memory; 256KB of ECC Level 2 cache per processor in an 8-way set associative implementation; 9.1GB hard disk drive and a modular disk subsystem that allows fast, easy addition and replacement of drives while the system is running.

The H50 has a maximum hot-swappable disk storage capacity of 236.6GB and a flexible I/O subsystem with 9 I/O slots (5 32-bit PCI, 2 64-bit PCI and 2 shared PCI/ISA) and 16 disk/media bays. It is packaged in a black 9" x 16" 8-EIA rack drawer (recommended for use in the black Model S00 Rack) and is shipped with the internal adapters and devices configured and installed.

Designed for high availability, the Model H50 can be expanded from 1 to 4 processors as your performance requirements dictate. And you can upgrade to the Model H70 with serial number protection.

- New! 10K rpm 9.1GB Ultra SCSI and SSA drives for improved performance
- One, two, three or four 332MHz PowerPC processors with X5 Cache
- 256KB of 8-way set associative Level 2 cache per processor
- Redundant cooling fans and optional redundant power supply (both hot-swappable)
- 128MB to 3GB of SDRAM memory
- Configurable for use as an SSA RAID server
- 32X (Max.) CD-ROM
- AIX V4.3 is included in the base price.

Туре	Mod	Lease [†]	Price	
7026	H50	*	\$22,000	

[†] Turn to page 76 for details on lease payment information. For Benchmarks, check out the 4-page Power Lineup chart inside pages 6 and 7

FCC Class A (Defined on page 4)

* PLEASE CALL FOR LATEST PRICES

Feature	Description	Price
CPU Options		
4311	PowerPC 604e 332MHz 1-way Processor Card with 256MB L2 Cache	\$7,000
4320	PowerPC 604e 332MHz 2-way Processor Card with 2x256MB L2 Cache	\$10,000
4338	PowerPC 604e 332MHz Select 1-way to 2-way	\$3,000

Internal Disk Options - see page 30

High availability solutions

RS/6000 High Availability Cluster Server-HA50


The RS/6000 High Availability Cluster Server - HA50 is an affordable, packaged - priced solution that provides redundant hardware and software and high-availability features that are designed to protect against unplanned system failures. It includes:

- Two rack mounted, 1-way (scalable to 4-way) SMP H50 Servers
- One 7133 Serial Disk System with built-in redundancy, data paths and high-performance SSA disks
- Proven HACMP for AIX software
- AIX operating system

64-bit performance and availability

Enterprise Server Model H70





- New! 10K rpm 9.1GB UltraSCSI and SSA drives for improved performance
- 9.1GB and 18.2GB disk drives
- 8 I/O slots and up to 16 disk/media bays
- 64-bit and 32-bit applications run concurrently
- The I/O data bandwidth provides more than 500MB/sec peak performance
- Ultra SCSI disk support doubles data transfer rates over SCSI-2 up to 40MB/sec
- Internal RAID storage helps protect data without purchasing external disk subsystems.

The RS/6000 Enterprise Server Model H70 is an improved follow-on to the popular Enterprise Server Model H50.

With one to four 64-bit 340MHz processors and up to 8GB of SDRAM memory, it provides significant performance gains when coupled with 64-bit database and application programs or when running legacy 32-bit applications. Reliability features include error correcting memory and L2 cache; a built-in service processor that can monitor system operation and report a system failure remotely; optional redundant power supplies and hot-swappable disks.

The Reliability/Availability/Serviceability (RAS) of the Model H70 is further enhanced by ECC level 1 cache, reduced soft memory errors and boot-time reconfiguration that can automatically take a failed processor offline. The combination of hardware features and high availability software (HACMP) means the model H70 excels in achieving up-time requirements critical in today's business operations.

Feature	Product No.	Description	Lease	Price
7017	7026-H70	Model H70 - 340MHz processor	*	\$26,900
CPU Option	S a street a street			
4317		340MHz 1-way Processor Card with 4MB L2 Cache		\$10,000
4319	Description	340MHz 2-way Processor Card with 2 x 4MB L2 Cache		\$20,000
Memory Opt	tions			
▶ 4107	lons	64MB (2 x 32MB) DIMMS		\$960
▶ 4110	512MB Memb	256MB (2 x 128MB) DIMMS		\$3,840
▶ 4119	1994faR Men	512MB (2 x 256MB) DIMMS		\$6,400

Internal Disk Options - see page 30

[†] Turn to page 76 for details on lease payment information. For Benchmarks, check out the 4-page Power Lineup chart inside pages 6 and 7

FCC class A defined on page 4.

System Dimensions: 13.8"H x 17.5"W x 34.3"D

* PLEASE CALL FOR LATEST PRICES

▶ 24 Hour QuickShip

Maximize system uptime

HA-H70 Cluster Server

- **Built-in redundant software and hardware**
- **High Availability Cluster Multi-processing for** AIX (HACMP)
- Powerful one- to four-way symmetric multiprocessor (SMP)
- Designed for easy growth up to four H70 servers and six 7133 disk systems (with a total storage capacity of 1.74TB) may be attached to the cluster system.

HA-H70 is designed to maximize system uptime and keep your company's critical applications, data and systems operational and available 7 days a week, 24 hours a day and 365 days a year.


The HA-H70 solution provides the capability to recover from unplanned server hardware and application failures...the estimated downtime is less than six minutes per year (99.99% available). It also provides the means to take down an individual server (node) for planned maintenance and upgrades, without having to take down the entire HA-H70 Cluster, thus providing additional uptime.

Powerful SMP server

RS/6000 Enterprise Server Model R50

Fax Document 5664 (Model R50)





- Non-blocking data crossbar delivers sustained memory bandwidth of 1.8GB/s
- Exclusive onboard IBM SystemGuard* service processor monitors your system and provides automatic, unattended recovery from most errors
- AIX V4.3 is included in the base price.

RS/6000 Enterprise Server Model R50 offers a broad range of performance to meet your requirements. Featuring highspeed 200MHz PowerPC 604e processors, this enhanced SMP server delivers greater speed, flexibility and capability than previous 604-based models. For high output, high bandwidth and efficient cache management, SMP is a great solution.

Model R50 is rack mounted for easy expandability. It can be configured as a 2-, 4-, 6- or 8-way SMP system with one to four dual 200MHz PowerPC 604e processors.

Designed for high-throughput SMP from the ground up

Our RS/6000 SMP family schedules and synchronizes work across available processors, helping to provide efficient paths between each processor and memory. Each system has been engineered for demanding environments that require dependable, high-performance multiprocessor architecture.

Feature	Description	Lease [†]	Price
4162	1GB SMP DIMMs on 1GB card	*	\$11,334
▶ 4165	256MB DIMMs on 1GB card	*	\$7,680
▶ 4166	256MB DIMM Kit	British An 1*1 cn	\$5,140

[†] Turn to page 76 for details on lease payment information.

FCC Class A defined on page 4. System Dimensions: R50: 17.52"W x 36.42"D x 10.5"H

For Benchmarks, check out the 4-page Power Lineup chart inside pages 6 and 7. Current users of AIX V4 may require Program Temporary Fixes to be Year 2000 ready.

PLEASE CALL FOR LATEST PRICES

▶ 24 Hour QuickShip

High availability for critical applications

HA-S70 Advanced Cluster Server

Two IBM RS/6000 Enterprise Server S70 Advanced; each server includes:

- One 4-way SMP, 262MHz, RS64 II processor each with 8MB L2 Cache
- 2GB of memory
- **Dual Ultra SCSI controllers and boot disk drives**
- Dual PCI SSA disk adapters
- **Three PCI Lan adapters**
- N+1 AC power

Two IBM 7133 Model D40 Serial Disk System; each 7133 includes:

- Eight 9.1GB or 18.2GB hot-swappable SSA disk
- Redundant data paths and power supplies
- One IBM S70 Advanced I/O rack with redundant power distribution unit.

HA-S70 Advanced enhances your ability to conduct business around the clock-day in, day out-around the world...knowing you have an ideal recovery system in the event of an unplanned failure. HA-S70 Advanced is designed to maximize system uptime. For outages caused by unplanned failures, the HA-S70 Advanced system is estimated to be available 99.999% of the time or be unavailable less than 6 minutes annually. Moreover, with the HA-S70 Advanced, IBM has made high availability much more robust and affordable.

HA-S70 Advanced Protection

HA-S70 Advanced is built on a reliable foundation with built-in redundancy... two powerful four- to twelve-way symmetric multiprocessor (SMP) RS/6000 Enterprise Server S70 Advanced, dual 7133 Serial Storage Architecture (SSA) disks, proven HACMP (High Availability Cluster Multi-Processing for AIX*) and AIX software. For added availability, the disk systems and I/O drawers are mounted in a rack with redundant power.

IBM's award-winning HACMP and AIX system software are integrated into the HA-S70 Advanced solution. HACMP provides high-availability application services and allows HA-S70 Advanced hardware and software resources to be fully utilized by monitoring and detecting system hardware and software failures, including processor, network, adapter, power, application and user-defined events.

HA-S70 Advanced financing options

HA-S70 Advanced financing options include pre-tested, industry-leading applications, high-availability services and attractive financing rates for credit qualified customers.

High availability and greater expandability for mission-critical applications

RS/6000 Enterprise Server S70 Advanced



64-bit 262MHz RS64 II microprocessor,
packaged 4 processors per card with 8MB of L2
ECC cache per processor

- 4-way to 12-way SMP scalability
- 1GB to 32GB of ECC SDRAM system memory
- Supports both 32-bit and 64-bit applications and **PCI** cards
- Supports SCSI, Ultra SCSI and SSA storage, media, and communications options
- RAID support for SSA
- Internal I/O system scalable to 56 PCI slots and 873.6GB internal disks
- Up to 48 hot-pluggable disk bays with an additional external capacity of 45TB.

The IBM RS/6000 Enterprise Server S70 Advanced is the SMP server solution of choice. Offering a higher level of performance, reliability, availability and serviceability, it has been designed for mission-critical environments. The service processor, redundant cooling and power and the ability to cluster multiple systems using High Availability Cluster Multi-Processing (HACMP) for AIX software, allows greater horizontal system growth.

The S70 Advanced is a Central Electronics Complex (CEC) and an I/O rack. The entry-level CEC configuration is a 4-way scalable SMP system that utilizes the 64-bit 262MHz RS64 II processor with 8MB of L2 cache per processor, respectively. The first drawer in the I/O rack contains the service processor, high-performance disk drive, 32X maximum speed CD-ROM, 1.44MB 3.5-inch disk drive and two PCI Ultra SCSI disk adapters. Upgrades are also available.

Туре	Mod	Description	Lease [†]	Price
7017	S7A	Model S70	*	\$125,000

† Turn to page 76 for details on lease payment information * **PLEASE CALL FOR LATEST PRICES**

CPU Option

Feature	Description	Price
► 5312	PowerPC RS64 II 4-way Processor Card	\$55,000
Memory Op	tions	
▶ 4171	512MB Memory Group (4 x 128MB)	\$9,728
► 4173	1024MB Memory Group (4 x 256MB)	\$19,456
4175	2048MB Memory Group (4 x 512MB)	\$34,816
► 4177	4096MB Memory Group (4 x 1024MB)	\$57,344
4179	8192MB Memory Group (4 x 2048MB)	\$98,304
nternal Dis	k Options	
➤ 2913	9.1GB Ultra SCSI Hot Swap	\$1,400
3104	18.2GB Ultra SCSI Hot Swap	\$2,400
Additional	nternal Storage Options	
▶ 6159	12GB/24GB 4mm Internal Tape Drive	\$3,200
▶ 6156	20GB/40GB 8mm Internal Tape Drive	\$6,250

FCC Class A (Defined on page 4) CEC Dimensions: 22.3"W x 40.98"D x 62.0"H I/O Dimensions: 25.5"W x 40.1"D x 62.0"H

For Benchmarks, check out the 4-page Power Lineup chart inside pages 6 and 7.

▶ 24 Hour QuickShip

64-Bit computing

RS/6000 Enterprise Server Upgrades

If you are an IBM J30/40/50 or R30/40/50 installation, the Model S70 Advanced is an ideal solution for increased processing power and application compatibility. And now IBM makes going to the Model S70 Advanced easier than ever. Model conversion kits enable J30/40/50 or R30/40/50 users to cost-effectively move to the Model S70 Advanced while maintaining their existing serial number.

The following required features must be ordered and installed on the Model S70 Advanced:

- Base 4-way processor
- Base or selected memory
- 9.1GB Ultra SCSI-enabled hot-swappable disk
- I/O Rack and base 8296 drawer (for J30/40/50 users) or 8296 drawer only (for R30/40/50 users)
- Two PCI Ultra SCSI adapters

In addition, you retain all memory, all Micro Channel adapter cards and all processor cards except for the base 2-way card. These features are now available for reuse in any other J30/40/50 or R30/40/50 systems you may have installed.



Move into the next generation of mission-critical, commercial computing

Enterprise Server Model S80





The Model \$80 provides the power, capacity, reliability and expandability you need with:

- 64-bit system with 6-, 12-, 18- or 24-way scalability - packaged on 4 processor cards (6 RS64 III processors per card)
- **Expandable from 2GB to 64GB of ECC SDRAM**
- Support for UltraSCSI, SSA and FCAL interfaces
- 32-bit and 64-bit applications supported
- AIX for Servers (1 2 Users) license included
- **Excellent reliability, availability and** serviceability (RAS).

Performance by design

The S80 is the newest member of IBM's popular S-series of 64-bit enterprise servers. It builds on the successful design of the S70 and S70 Advanced by doubling the number of processors to 24, and doubling memory to 64GB. And the S80 is the first RS/6000 to feature the RS64 III microprocessors, based on IBM's state-of-the-art "copper chip" technology. The result is faster, more reliable processors.

Strategic computing depends on throughput

Throughput depends on balanced system design and here, again, the S80 delivers with increased internal memory bandwidth and external I/O bandwidth that help eliminate potential bottlenecks. And new performance enhancements to AIX 4.3.3 take full advantage of this leading-edge design.

More power for business applications

In pre-release testing, a 12-way S80 delivered a SPECweb96¹ benchmark (which measures Web-serving performance) that was 66 percent better than the previous record. And in the VolanoMark² test (which measures Java performance) a sixway S80 shattered the previous best mark established by an 8-way Hewlett-Packard server.

Online, 24 x 365

To help ensure strategic applications remain available 24x365, the S80 features ECC main and cache memory that can detect and correct many errors. Should downtime occur, its fault and error correction functions - such as machine check handling, reboot recovery, PCI fault isolation and service processor error collection - help speed system recovery.

A strategic weapon

With its powerful combination of performance, scalable growth options, investment protection, reliability and flexibility, the S80 offers a comprehensive solution for mission-critical computing environments - for today and tomorrow.

Requirements:	Call for hardware and software requirements.	SIMP
---------------	--	------

Product No.	Mod	Feature	Description	Lease [†]	Price
7017	S80	demondina	Model S80 with one 6-way processor, 2GB memory	**************************************	\$290,000
7017	S80	5308	RS64 III Processor, 6-Way SMP, 450MHz, 8MB L2 Cache	edundani cooling and p	\$200,000
architeolura. y		4190	1024MB Memory (4 x 256MB Cards)	Applitagiolas/Astronaya siqu	\$19,456
	Halb shakor	4191	2048MB Memory (4 x 512MB Cards)	多來自印度的自己的反應	\$34,816
	HUMBLE	4192	4096MB Memory (4 x 1024MB Cards)	application/lawygamates	\$57,344
Pesture A		4193	8192MB Memory (4 x 2048MB Cards)	en-end.com/wate.rescur	\$98,304
4102		4194	16384MB Memory (4 x 4096MB Cards)	seed datachers suetern t	\$147,456
P 4100 X		2913	9.1GB UltraSCSI 16-bit Hot-Swap Disk Drive	don. The energine on Linus	\$1,400
BADNING CONTROL	DOMESTICAL	3008	9.1GB 10,000 rpm UltraSCSI 16-bit Hot-Swap Disk Drive	ir system men undere n	\$1,680
Tom Miles Are	SE BREAKES	3104	18.1GB UltraSCSI 16-bit Hot-Swap Disk Drive	in bivie of L2 octorie per	\$2,400

Turn to page 76 for details on lease payment information.

FCC Class A defined on page 4. System Dimensions: CEC Enclosure 62"H x 22.3"W x 40.98"D

For more information see www.spec.org, August '99

For more information see www.volano.com/benchmarks.html

The model S80 shatters benchmark records for Web-serving and Java!

Model S80 Benchmarks

Fast servers that are reliable and can handle large numbers of users are critical to companies transitioning their businesses and their customer relationships to the Internet.

SPECweb96 - A 12-way S80, running a pre-release version of AIX 4.3.3, the IBM UNIX operating system, delivered a SPECweb96 benchmark result of 40,161 http ops./sec., 66 percent better than the former champ, the HP 9000 N-Class server from Hewlett-Packard.

SPECweb96 measures the maximum number of Hypertext Transfer Protocol (HTTP) operations per second.

Imagine the power of this system when it is configured with its maximum of 24 processors!

VolanoMark - In this Java server performance measure, a 6-way S80 executed 22,906 messages/sec., 92% better than Hewlett-Packard's best result, 11,920 messages/sec. by an N Class server configured with 8 processors. VolanoMark is a 100 percent pure Java server benchmark that measures the

speed of the Java platform and accurately predicts realworld Java performance and scalability.

While hardware improvements were important in setting these new records, AIX enhancements were just as significant. AIX 4.3.3, released in September, offers several Java, Web-performance, and scalability enhancements. It is also the first release of AIX to be influenced by Project Monterey. Project Monterey is an initiative led by IBM with SCO, Sequent, and Intel, to deliver a single UNIX product line that spans RS/6000 systems, IA-32, and upcoming IA-64 based systems.

VolanoMark testing also used IBM's Java Virtual Machine 1.1.8 and Just in Time Compiler 3.1, both of which have significant performance advantages over their predecessors.

For more information on:

SPEC - see www.spec.org

VolanoMark benchmark - see www.volano.com/

benchmarks.html

IBM RS/6000 Results Magazine

RS/6000 Results is a quarterly IBM
publication that is distributed across the United
States and Canada. Providing the latest news
about product releases, promotions, and
coming events, RS/6000 Results contains
customer case studies and insightful feature
articles on technology and directions,
application strategies, and implementation
issues, all designed to help you gain a
competitive edge with an RS/6000 solution.
In a word - results!

http://www.rs6000.ibm.com/resource/results
Visit this site to see the current issue, subscribe,
or view past issues.

Current issue - Server Consolidation



Server consolidation cuts administrative costs

RS/6000 SP



- Building-block architecture comprised of "nodes," each a complete RS/6000 system with its own processor(s), memory, PCI expansion slots, disk devices and AIX operating system
- Ability to serially run any of more than 10,000AIX applications on separate nodes
- Ability to use nodes in parallel bringing hundreds or thousands of processors together to create a massively parallel system that is perfect for large-scale computing requirements
- An optional SP Switch that provides high-speed communications for inter-node data transfers and system backups
- Flexible configuration can mix node types as desired and house them in short or tall frames
- Growth to 512 nodes per system harnessing the power of thousands of processors, all managed and controlled from a single graphical operations console.

If your server-related administrative costs are skyrocketing, it's time to do what over 2,000 other leading-edge companies have already done: invest in an RS/6000 SP system - the industry's leading platform for UNIX** server consolidation. The SP* platform helps cut costs while allowing operational and applications flexibility. It handles Web-serving, transaction processing, financial analysis, simulation, decision support and more. Plus the SP has an unmatched ability to cost-effectively grow with your business.

World class scalability With the ability to start with a single node and grow to a total of 512, the RS/6000 SP system gives you excellent scalability. You determine how much power you need to add at any given time, since the SP system can be grown in one-node increments. You can even mix-and-match different processor generations in the same SP configuration, an important feature that lets you increase the performance of growing application nodes while leaving others at their current performance levels until more power is needed.

Superior availability The SP system was built with high availability in mind. It features "hot-pluggable" nodes, optional I/O and internal disk redundancy and multiple redundant, hot-pluggable power supplies. IBM's popular and industry-leading HACMP high-availability software is also supported on the RS/6000 SP system, up to 32 nodes, enabling nodes to provide backup and recovery for one another in the event of a node failure or other error.

Improved manageability The RS/6000 SP system allows for growth with limited increased administration. The status of all hardware, software, jobs and users can be monitored by your system administrator from a single graphical operations console – an RS/6000 control workstation running PSSP (Parallel Systems Support Programs) software. The administrator can also perform multiple management tasks from this console – everything from distributing software to hundreds of nodes and centrally managing error logs and password files, to monitoring and controlling SP hardware at remote sites.

Increased flexibility If you are looking for a truly multipurpose platform with excellent flexibility, the RS/6000 SP system is it. The SP system lets you support a wide variety of single or multi-tiered applications concurrently. There's no need to invest in multiple hardware platforms and administrative skill sets for different applications. You can develop, test and run applications for multiple AIX versions on the same hardware platform. You can even partition the system into pools of nodes. And because the SP system allows for nearly linear scaling of disk capacity along with processors and memory, upgrades are easier to manage and you can provide applications access to terabytes of data.

SP nodes pack more power

RS/6000 Nodes: High, Thin and Wide

IBM is pleased to announce the new 64-bit, POWER3-based SMP High node. With up to eight 222MHz POWER3 processors, support for up to 16GB of memory and a 14GB/second (peak) New memory bandwidth, this node is built for performance. And, with 5 internal PCI slots and up to 6 optional SP IO Expansion Units (each allowing an additional 8 PCI slots and 4 disk bays), the POWER3 High node can support up to 53 PCI attachments.

The 1- or 2-way POWER3 Thin and Wide nodes

deliver great floating-point performance - ideal for technical applications like seismic processing, engineering analysis, scientific research, chemical modeling and electronic design automation - balanced with strong integer capabilities in a small package. They support up to 4GB of memory, a range of PCI adapters, and provide up to 36.4GB of mirrored disk.


The 332MHz PowerPC 604e SMP Thin and Wide nodes provide increased price/performance leadership, improved packaging and enhanced RAS over previous SMP

configurations. Their excellent integer performance makes them the ideal solution for mission-critical applications such as data mining and warehousing, OLTP, collaborative computing and groupware solutions.

SP "attached servers" – S80 and S7A

RS/6000 SP Attached Servers: Models S80 and **\$70 Advanced**

Now you can attach up to 16 of the RS/6000 Model S80 and S70 Advanced (S7A) servers to an SP system and have them function like internal SP nodes. This provides very large capacity, high-performance database server capabilities for advanced applications such as ERP and data marts. The attached server can be attached directly to the RS/6000 SP switch fabric and is managed like any other SP node using the PSSP systems management software.



Visit our Web site at: The Server Consolidation Savings Estimator can be found at: www.rs6000.ibm.com/estimator



Scale your RS/6000 SP to new heights

RS/6000 SP

	POWER3 High	POWER3 Thin	POWER3 Wide	Thin-332	Wide-332
Processor	222MHz POWER3 (2-, 4-, 6-, 8-way)	200MHz POWER3 (1-, 2-way)	200MHz POWER3 (1-, 2-way)	332MHz PPC 604e (2-, 4-way)	332MHz PPC 604e (2-, 4-way)
L1 Cache	64KB data ¹ 32KB instruction ¹	64KB data ¹ 32KB instruction ¹	64KB data ¹ 32KB instruction ¹	32KB data ¹ 32KB instruction ¹	32KB data ¹ 32KB instruction ¹
L2 Cache	4MB ¹	4MB ¹	4MB ¹	256KB ¹	256KB ¹
RAM	1-16GB	256MB-4GB	256MB-4GB	256MB-3GB	256MB-3GB
Memory Bus Width	576-bit	128-bit	128-bit	128-bit	128-bit
Basic Internal Storage	None required ³	none required ³	none required ³	none required ³	none required ³
Max. Internal Storage	473.2GB ^{4,5}	36.4GB ⁴	72.8GB ⁴	36.4GB	72.8GB
Disk Bays	2-265	2	4	2	4
PCI Expansion Slots (available)	5-53 ⁵	2	10	2	10
Nodes/Frame - Tall	Four	16	8	16	8
Nodes/Frame - Short	N/A	8	4	8	4
I/O Bus Speeds	264 MB/Second	132MB/second	132MB/second	132MB/second	132 and 264MB/second ²
Adapters	Integrated Ultra SCSI and Ethernet (10/100 Mb/Second)	Integrated Ultra SCSI and Ethernet (10/100 MB/Second)	Integrated Ultra SCSI and Ethernet (10/100 MB/Second)	Integrated SCSI-2 F/W and Ethernet	Integrated SCSI-2 F/W and Ethernet

Pricing for RS/6000 SP systems ranges from approximately \$150,000 for a single-node system to several million dollars for truly large-scale systems configured with up to 512 nodes.

1 Per processor 2 Triple bus 3 Boot from external storage required if no internal storage 4 Disks must be installed in like pairs to support mirroring 5 with SP Expansion I/O Uni ⁴ Disks must be installed in like pairs to support mirroring



Increase productivity with more memory

RS/6000 Server and Workstation memory









Deskside SMP Servers

Feature	Description	Model F40	Model F50	Model J50	Price
▶ 4093	OMB Card ^a		•	-	\$1,038
► 4107	64MB (2x32MB DIMMs)	_	•	-	\$640
► 4110	256MB (2x128MB DIMMs)	-	•	-	\$2,560
► 4113	32MB DIMM ^b	•	_	-	\$224
► 4114	64MB DIMM ^b	•	_	-	\$448
► 4115	128MB DIMM ^b	•	_	-	\$896
4165	1GB Card ^c (with 1 256MB DIMM)	_	_	•	\$7,680
▶ 4166	256MB DIMM (for use with 4165)	-	_	•	\$5,140
4167	1GB Card (with 4 256MB DIMMs)	-	_	•	\$24,380

Rack-Mounted Servers

Feature	Description	Model B50	Model H50	Model H70	Model R50	Price
▶ 4093	OMB Card ^a	_	•	•	-	\$1,038
► 4107	64MB (2x32MB DIMMs)	_	•	•	_	\$640
► 4110	256MB (2x128MB DIMMs)	- (4)	•	•	-	\$2,560
► 4119	512MB (2x256MB DIMMs)			•	_	\$6,400
4150	125MB DIMM	•	_	_	_	*
4169	256MB DIMM	•	_	-	-	*
► 4165	1GB Card ^c (with 1 256MB DIMM)	_	_	-	•	\$7,680
▶ 4166	256MB DIMM (for use with 4165)		_	_	•	\$5,140
4167	1GB Card (with 4 256MB DIMMs)	-	_	-	•	\$24,380

S Family Servers

Feature	Description	Model \$70	Model S70 Advanced	Model \$80	Price
► 4171	512MB	•	•	-	\$9,728
► 4173	1GB	•	•	-	\$19,456
► 4175	2GB	•	•	-	\$34,816
► 4177	4GB	•	•	_	\$57,344
► 4179	8GB	•	•	_	\$98,304
4180	8GB	_	— · · · · · · · · · · · · · · · · · · ·	•	\$84,480
4191	2GB	_		•	\$34,816
4192	4GB	<u> </u>	-	•	\$57,344
4193	8GB	- 1000000		•	\$98,304
4194	16GB	<u> - </u>	_	•	\$147,456

^{*} PLEASE CALL FOR LATEST PRICES

^a 16 DIMM positions ^b DIMMs must be installed in pairs ^c Supports 256MB, 512MB or 1GB

^a 16 DIMM positions ^c Supports 256MB, 512MB or 1GB

^{▶ 24} Hour QuickShip

Boost performance with more memory









Workstations

Feature	Description	Models 120/132	Models 140/240	Model 150	Model 260	Models 25T ^a /41W/42W/T ^a	Model 3CT	Price
▶ 4083	32MB SIMM	•	_	_	-		_	\$1,280
▶ 4011	16MB SIMM	_	_	_	_	•	-	\$640
► 4012	32MB SIMM	-	-	_	_	•	-	\$1,280
► 4113	32MB DIMM	_	•	_	_	_	_	\$224
► 4114	64MB DIMM	_	•	_	_	_	_	\$448
► 4115	128MB DIMM	-	•	_	_	<u> </u>	_	\$896
▶ 4069	64MB Card	_	_	_	_	_	•	\$1,920
▶ 4090	128MB Card	-	-	_	_	_	•	\$3,200
▶ 4095	256MB Card	-	-	_	_		•	\$6,400
► 4149	64MB DIMM	_	_	•	_	_	-	\$320
► 4150	128MB DIMM	-	_	•	_		-	\$896
► 4169	256MB DIMM	-	-	•	_	<u> </u>	_	\$1,792
▶ 4098	OMB Card			_	•	-	-	\$1,038
► 4107	64MB DIMM [†]	-	-	_	•		-	\$640
► 4110	256MB DIMM ^{††}	-	-	_	•	_	_	\$2,560
4119	512MB ⁺⁺⁺	_	-	_	•	_	-	\$6,400

 $^{^{\}rm a}$ Memory must be purchased in groups of four identical SIMMs. † (2 x 32MB) $^{\rm tt}$ (2 x 128MB) $^{\rm ttt}$ (2 x 256MB)

Servers

Feature	Description	Models E30/F30	Models C10 ^a /20 ^a	Model 39H	Model 397	Models 59Hb/590	Model 591 ^b /595 ^b	Price
▶ 4011	16MB SIMM	_	•	_	_	_	-	\$640
▶ 4012	32MB SIMM		•	_	_	-	-	\$1,280
► 4132	32MB DIMM	•	-	_	-	_	=	\$480
▶ 4164	64MB DIMM	•	_	_	_	_	-	\$960
4168	128MB DIMM	•	_	-	-	-	-	\$1,920
▶ 4069	64MB Card	-	-	•	-	•	_	\$1,920
▶ 4090	128MB Card	1 - 1 - 1	-	•	-	•		\$3,200
▶ 4095	256MB Card	_	_	•	_	•	_	\$6,400
4077	64MB Card	-	-	_	-	-	•	\$1,920
▶ 4078	128MB Card	-	-	_	-	-	•	\$1,920
▶ 4079	256MB Card	-	-	-	-	-	•	\$3,840
▶ 4087	64MB Card	-	-	-	•	-	-	\$1,920
▶ 4088	128MB Card	-	-	-	•	-	_	\$1,920
▶ 4089	256MB Card	_	_	_	•	-	-	\$3,840

⁽DIMM - Dual Inline Memory Module as opposed to Single Inline Memory Module - SIMM) ^a Memory must be purchased in groups of 4 identical SIMMs. ^b Memory must be purchased in matched pairs.

Expand your storage options

RS/6000 Disk Drives





Feature	Description	Model B50	Model H50	Model H70	Model R50	Price
▶ 2908	9.1GB UltraSCSI ^{††}	-	•	•	•	\$1,300
2909	18.2GB UltraSCSI [™]	-	•	•	•	\$2,300
▶ 2913	9.1GB UltraSCSI [†]	-	•	•	-	\$1,400
3104	18.2GB UltraSCSI [†]	-	•	•	-	\$2,400
3112	9.1GB UltraSCSI	•	-	-	-	*
3113	18.2GB UltraSCSI	•	_	-	-	*
3008	9.1GB UltraSCSI [†] , 10,000 rpm	-	•	•	-	\$1,680
▶ 3071	4.5GB SSA [†]	_	•	•	-	\$1,600
3074	9.1GB SSA [†]	-	•	•	-	\$1,600
3009	9.1GB SSA [†] , 10,000 rpm	_	•	•	_	*

S Family Servers

Feature	Description	Model \$70	S70 Advanced	Model \$80	Price
▶ 2913	9.1GB UltraSCSI [†]	•	•	•	\$1,400
3104	18.2GB UltraSCSI [†]	•	•	•	\$2,400
3008	9.1GB UltraSCSI [†] , 10,000rpm	•	•	•	\$1,680

[†] Supported as SCSI2F/W in Model S70, UltraSCSI in S70 Advanced and S80; Hot-Swappable Drive

SMP Servers

Feature	Description	Model F40	Model F50	Model J50	Price
▶ 2913	9.1GB UltraSCSI [†]	•	•	-	\$1,400
3104	18.2GB UltraSCSI [†]	•	•	-	\$2,400
3008	9.1GB UltraSCSI [†] , 10,000 rpm	•	•	_	\$1,680
▶ 3071	4.5GB SSA [†]	•	•	_	\$1,600
3074	9.1GB SSA [†]	•	•	_	\$1,600
3078	9.1GB SSA [†] , 10,000 rpm	•	•	_	\$1,920
3020	9.1GB UltraSCSI ^{††}		_	•	\$1,750

Workstation and Workgroup Servers

Feature	Description	Model 140	Model 150	Model 240	Model 260	Models 3BT/3CT	Model 397	Price
▶ 3028	4.5GB UltraSCSI 16-bit Enhanced	_	_	-	•	-	-	\$1,400
▶ 3029	9.1GB UltraSCSI 16-bit Enhanced	_	-	-	•	-	_	\$1,400
2906	9.1GB UltraSCSI 16-bit Enhanced 10,000 rpm	_		_	•	_	_	\$1,680
3027	9.1GB UltraSCSI, 10,000 rpm	_	-	_	•	_	_	\$1,560
▶ 2908	9.1GB UltraSCSI	•	•	•	•	•	•	\$1,300
2909	18.2GB UltraSCSI	•	•	_	•	-		\$2,300

Servers

Feature	Description	Model E30	Model F30	Models 390/39H	Model 591	Model 595	Price
▶ 3071	4.5GB SSA [†]	-	•	_	_	-	\$1,600
3074	9.1GB SSA [†]	-	•	_	_	_	\$1,600
3078	9.1GB SSA [†] , 10,000 rpm	-	•	_	_	_	\$1,920
▶ 2908	9.1GB UltraSCSI	•	_	•	•	•	\$1,300
▶ 2913	9.1GB UltraSCSI [†]	-	•	-	_	_	\$1,400

[†] Hot-Swappable Drive

[†] Hot-Swappable Drive † Supported on SCSI-2 F/W in R50 * PLEASE CALL FOR LATEST PRICES

[†] Hot-Swappable Drive †† Supported as SCSI-2 F/W

New single chip architecture for a price/performance breakthrough

POWER GXT2000P Graphics Accelerator



- Exceptional 3D graphics performance and functionality at a competitive price
- Single-chip implementation supports primary 3D graphic functions including setup, rasterization, bus management and digital to analog conversion
- UNIX 3D graphics price/performance leader when coupled with the RS/6000 43P Model 150 workstation and AIX V4.3.2
- OpenGL™ and graPhIGS™ 3D Application **Programming interfaces API features (such as 3D** texture mapping and trilinear detail filtering) supported in hardware for the most demanding scientific and technical visualization applications
- Supports advanced 3D features such as:
- Hidden line and surface removal, line antialiasing
- Advanced texture mapping, including luminance filtering
- Gouraud shading, depth cueing/logging, transparency
- YUV color space conversion, point and bilinear video scaling
- Meets the performance and functional requirements of the most demanding 3D graphics application areas, such as mechanical computeraided design (MCAD) and mechanical computeraided engineering (MCAE).

IBM's POWER GXT2000P Graphics Accelerator brings a new level of productivity to day-to-day design and engineering. It is designed to be the graphics accelerator for the primary design workstation of an engineering enterprise; providing the power of 2D and 3D visualization with winning price/ performance and functionality.

The GXT2000P is a single PCI adapter card that requires only a half-sized PCI slot. It provides display resolutions up to 1920 x 1200 (maximum) at up to 76Hz, and includes support for monitors that comply with the ISO 9241 Part 3. It was designed specifically to support the functional requirements of the OpenGL and graPHIGS APIs, and offers many features demanded by the most widely used software applications for visualization and design including:

- 32MB Unified Frame Buffer
- Four 256-entry hardware color tables
- Separate gamma correction tables
- Face culling support
- OpenGL polygon offset support and mode support

The rich capabilities of the GXT2000P are driven by the highly innovative electronic design of a single chip solution, which reduces cost as it increases performance.

The GXT2000P has been tested to show highly competitive performance in GPC benchmarks as well as application-level graphics rating, providing up to two-and-a-half times IBM's previous entry 3D graphics workstations, positioning IBM as the price/performance leader in UNIX computer graphics

It has been tuned to support the most desirable MCAD applications, such as CATIA, ProENGINEER and I-DEAS Master Series, which continues IBM's strong support of automotive and aerospace manufacturing.

With the GXT2000P installed, the 43P Model 150 Workstation is an exceptional price/performance MCAD design seat. The GXT2000P can also be installed in the 43P Model 260 and most 43P Model 140 systems. Up to four GXT2000P 3D graphics accelerators may be installed on the 43P Models 140, 150 or 260.

Software Requirements:	AIX Version 4.3.2, AIX 4.2.1 OpenGL, PHIGS and XIib are included with AIX V4.3.2. OpenGL, PHIGS are purchased separately with AIX 4.2.1.

Feature	Description	Slots/Bus	Price
2823	GXT2000P	1/PCI	\$2,995

FCC Class B (Defined on page 4)

For your most demanding 3D visualization and modeling tasks

POWER GXT3000P Graphics Accelerator



- Single 64-bit PCI accelerator that attaches to the RS/6000 Model 260 via a 64-bit slot or Model 150 via a 32-bit slot. For the Model 150, the **GXT3000P** will use 2 slots of space
- Supports display resolutions up to 1280 x 1024 at 85Hz refresh rate, providing seamless display of the most complex 3D models
- 8-bit and 24-bit double-buffered color
- 24-bit Z buffer
- Allows the display of up to 16.7 million simultaneous colors
- Hardware acceleration for such advanced 3D graphics as hidden-line and surface removal, antialiasing, Gouraud shading, depth cueing, stenciling and transparency
- Face culling support
- Supports hardware 3D texture mapping, with **16MB texture memory**
- 8-bit overlay buffer, window ID buffer, stencil buffer and double buffered alpha
- Hardware-accelerated lighting, video scaling, and stereo-in-a-window capabilities. Requires AIX V4.3.2 or AIX V4.2.1.



For 43P Series Models 150 and 260

Use the POWER GXT3000P with POWER3- and PowerPCbased workstations like the RS/6000 7043 Models 150 and 260 for your most demanding 3D visualization and design tasks - aerospace/automotive MCAD and engineering, petroleum exploration and production, scientific visualization, and other graphics-intensive applications in a wide range of technical industries.

The 64-bit, PCI-based POWER GXT3000P is IBM's topperforming graphics accelerator. It delivers up to three times greater GPC and graphics performance than previous IBM workstation adapters - placing it among the industry's graphics performance leaders. Native support is provided for both PHIGS and OpenGL application programming interfaces to facilitate adaptation of the most popular 3D applications to the AIX workstation environment.

Up to two GXT3000P graphics accelerators can be installed in a 7043 Model 260.

Graphics accelerators that are right for your application

- Typical Applications/Use - RS/6000 Model	- CASE - Customer Service - Process Control	- EDA - Drafting - Fin. Modeling - GIS	- MCAD/MCAE - Geo. Science - Visualization
43P Model 140	GXT120P	GXT250P	GXT2000P GXT3000P
43P Model 150	GXT120P	GXT250P	GXT2000P GXT3000P
43P Model 260	GXT120P	GXT250P	GXT2000P GXT3000P

Feature	Description	Price
2825	GXT3000P 1- or 2-PCI	\$6,500

FCC Class B (Defined on page 4)

Exceptional 2D graphics performance

POWER GXT130P



- Delivers exceptional 2D graphics performance for UNIX systems at a low price
- Provides graphic functions as a performance monitor for ebusiness server solutions
- Supports traditional X Windows graphics, database management and maintenance, process control status and activity for securities trading.

The POWER GXT130P is a versatile, low-priced 2D graphics accelerator for RS/6000 workstations and servers.

This powerful accelerator is ideal for process control environments because as many as four may be installed in a single RS/6000 system. Each accelerator controls a monitor displaying graphics and text for dozens of process points. For decision support systems, the GXT130P provides opportunities for rapid, simultaneous display of large amounts of critical information at high resolution on one or more multiple screens.

Software	AIX 4.2.1 or AX 4.3.2 (Xlib is included with AIX V4.2.1 or 4.3.2

Visit our Web site at: www.rs6000.ibm.com

Feature	Description	Price
2830	POWER GXT130P	\$340

3D control at your fingertips

6094-051 3D Spaceball 3D Input Device



- Four new buttons (adding up to twelve total)
- New Lighted Program Function Keys (LPFK)
- New PowerSensor technology allows improved response and motion control
- Ergonomically improved with new smaller "ball"
- New SpaceWare 9.0 AIX driver with additional functions.

Interactive control of the Model 051 is easy and natural. You simply apply fingertip control to push, pull and twist the ball, manipulating the image on screen in 3-D as though it were grasped in your hand. This allows the user to zoom, pan and rotate so a computer-generated model can be viewed from any angle, allowing improved productivity with smooth dynamic six degrees of freedom through the new sensing technology. The removable palm rest can be switched to optimize right and left hand use.

The Model 051 is enhanced by a new SpaceWare 9.0 AIX driver with additional finctions that allow users to:

- create and modify user-defined buttons
- make groups of functions for multiple-user configurations
- modify individual sensitivity settings for panning, zooming and rotating

AIX Version 4.2.1, or 4.3.2 or later modification level is required. The SpaceWare Installation/Driver CD-ROM is shipped with the unit. Shipped with everything required for full connectivity and operation.

Software Requirements: AIX Version 4.2.1 or V4.3.2 or later modification level.

Туре	Mod	Description	Price
6094	051	Spaceball Model 051	\$849

FCC Class B (Defined on page 4)

Store your growing data in these 18.2GB drives

7204 External Disk Drive



- Models 118/418 support both Ultra SCSI (40Mbps) and SCSI F/W (20Mbps)
- Models 409 and 419 support both SCSI-3 Fast-20 Wide attachment (40Mbps) and LVD Fast-40 Wide attachment (80Mbps)
- Multiple 7204 devices allowed for each system
- Magneto-resistive (MR) head technology.

IBM's newest members of the 7204 family, Models 409 and 419, offer reliable and affordable storage at media data transfer rates up to 32MB per second. The Models 118 and 418 offer a maximum data transfer rate of 18.2GB/s

A formatted capacity of 9.1GB and 18.2GB of data is provided in a LVD/SE Multi-mode drive. The specific Models and their capacities are depicted in the table below.

If your applications do not demand the performance of the above Models, then the Models 139 and 339 with a maximum data transfer rate of 13.7MB/s may be the best choice.

The 7204 Family comes in both single port and dual port SCSI connector configurations.

Туре	Mod	Description	Lease†	Price
7204	118	(SCSI-2 F/W, Single Ended) 18.2GB	*	\$4,750**
7204	139	(SCSI-2 F/W, Single Ended) 9.1GB	*	\$2,750**
7204	339	(SCSI-2 F/W, Differential) 9.1GB	*	\$2,950
7204	418	(SCSI-2, Ultra Differential) 18.2GB	*	\$4,950#
7204	409	(SCSI-3 Fast-20 Wide, LVD Fast-40 Wide) 9.1GB	*	\$2,550
7204	419	(SCSI-3 Fast-20 Wide, LVD Fast-40 Wide) 18.2GB	*	\$3,800

 † Turn to page 76 for details on lease payment information.

* Reduced Price

FCC Class B (Defined on page 4)

* PLEASE CALL FOR LATEST PRICES

Optical storage at a low cost-per-MB

3995 Enhanced C-Series Optical Library Dataserver

Fax Document 3418/7302





- Improved granularity with 5 models delivering from 104GB to 1341GB per model
- Helping to protect customer investment by supporting previous generations of IBM 5.25-inch optical cartridges
- Storage solution of choice for electronic storage of information currently stored on paper or microfiche.

IBM's 3995 Enhanced C-Series Optical Library Dataserver is the solution of choice for extended online storage in data-intensive applications and for infrequently accessed database files. Double the capacity over previous generation IBM optical drives – up to 5.2GB (8X) (unformatted) storage per optical cartridge. All five models can read and write 5.2GB (8X) and 2.6GB (4X) and read 1.3GB (2X), 650MB (1X), Permanent WORM, CCW WORM and MO rewritable media. The 3995 optical cartridge media is available in convenient 10-pack or 52-pack bundles.

Optical Library Management functions to support these libraries need to be provided by your chosen application (such as ADSM for AIX) and/or software available from Independent Software Solution Providers that have certified support for these models.

Туре	Mod	Storage Capacity (unformatted)	Internal Optical Drives	Lease [†]	Price**
3995	C60	104GB	1 or 2	*	\$8,995
3995	C62	270GB	2	*	\$22,500
3995	C64	540GB	2 or 4	*	\$31,300
3995	C66	811GB	4 or 6	*	\$49,000
3995	C68	1341GB	4 or 6	*	\$68,500

[†] Turn to page 76 for details on lease payment information.

¹¹ Does not include cost of optical media or the cost of optional additional drive(s).

FCC Class A (Defined on page 4)

* PLEASE CALL FOR LATEST PRICES

Outgrown SCSI? Step up to 3.5TB of high performance SSA

7133 Serial Disk System

Fax Document 8229/4399



7133-D40

- Sustained data rate up to 90MB/s and 160MB/s/ loop bandwidth per SSA 160 adapter
- Excellent for low-cost, RAID-5 storage on PCI or Micro Channel (MCA) systems
- Attaches to supported models of HP, DEC and Sun Servers via the IBM 2108-S20 SAN Data Gateway for Serial Disk.

The high-capacity 7133 Serial Disk System can accept up to 16 "hot-swappable" disk drives. The advanced models D40 and T40 can be configured with 4.5GB, 9.1GB, 18.2GB or 36.4GB disk drives. The 7133 D40 and T40 models can provide a total capacity of up to 582.4GB per drawer or tower and up to 3.5TB in a fully loaded 6-drawer rack. With SSA dual data paths to every disk, redundant power and cooling, host bypass features, and the ability to connect to multiple UNIX, Novell Netware and Windows NT** servers, the 7133 is ideally suited for multi-host attachments of RS/6000s and other open systems servers.

D40 (rack):	17.5"W x 29"D x 6.7"H
T40 (deskside):	8.3"W x 33.9"D x 24"H

1	Туре	Mod	Description	Price
▶	7133	D40	Rack-Mount Drawer Maximum Storage Up to 582.4GB	*
-	7133	T40	Deskside Tower Maximum Storage Up to 582.4GB	*

^{*} PLEASE CALL FOR LATEST PRICES

Cluster up to eight RS/6000s or SP nodes

SSA Adapters

SSA RAID adapters let you cluster up to eight RS/6000 or SP nodes (two in RAID mode) for access to large databases residing on your SSA-based 7131 and 7133 storage solution. The Advanced SerialRAID adapters 6225 supports 160 MB/s throughput as well as non-RAID, RAID 5, and RAID 0 and provides support for "under the covers" SSA implementations. The SSA RAID EL adapter #6219 provides microchannel attachment to 7133 storage.

	Feature	Description	Price
•	6219	SSA RAID EL (MCA), 2-way RAID 5- OR 8-way NON-RAID, 1-way only with SSA Fast Write Cache Module, Supports loop speed of 80 MB/s	\$3,750
•	6222	4MB Non-Volatile SSA Fast Write Cache Module for use with 6215 and 6219	\$3,700
•	6225	Advanced Serial RAID adapter PCI, 2-way RAID 5- or 8-way NON-RAID, 1-way only RAID 0, 1-way only with SSA Fast Write Cache Module, Supports loop speed of 160 MB/s	\$3,000
•	6235	32MB Non-volatile SSA Fast Write Cache Module for use with #6225, 1-way only	\$575

▶ 24 Hour QuickShip

High-performance storage at a low cost-per-GB

7131 Multi-Storage Tower

Fax Document 4832/3793

■ Model 405 (SSA) features the SSA interface with sustained data rate up to 35MB/s and 80MB/s/loop bandwidth



■ Model 105 (SCSI) features the SCSI-2 interface with sustained data rate up to 12.5MB/s

Employing IBM's high-performance 9.1GB disk drives, the advanced deskside Multi-Storage Tower offers storage capacity up to 45.5GB (Model 405) or 63.7GB (Model 105). Both models offer five bays of "hot-swappable" disk drive modules, configurable with 4.5GB or 9.1GB drives. Model 405 features IBM's Serial Storage Architecture (SSA) for higher data rates, improved availability and significant performance advantages over its SCSI-based alternative.

Туре	Mod	Description	Lease	Pricett
7131	105	SCSI Model Maximum Storage Up to 63.7GB	uper *oni	h (1.
7131	405	SSA Model Maximum Storage Up to 45.5GB	*	*

† Turn to page 76 for details on lease payment information.

⁺⁺ Depending on drive capacity. FCC Class A (Defined on page 4) Dimensions: 7.75"W x 19"D x 16"H

* PLEASE CALL FOR LATEST PRICES

^{▶ 24} Hour QuickShip

Unprecedented scalability – great performance

Enterprise Storage Server (ESS)

Fax Document 9400







- Superior storage sharing for UNIX, Windows NT, AS/400 and S/390 servers
- Two powerful four-way RISC SMP processors, large cache and serial disk attachment provide high performance
- State-of-the-art copy services including FlashCopy, Peer-to-Peer Remote Copy and **Extended Remote Copy provide for rapid backup** and disaster recovery
- Redundant hardware and RAID 5 disk arrays provide high availability for mission critical business applications.

The IBM Enterprise Storage Server (ESS) is ideal for organizations with growing e-business operations that are being handled by multiple heterogeneous servers. It provides unprecedented scalability (up to 11TB) while maintaining excellent performance.

The ESS offers a variety of host attachment options such as UltraSCSI, ESCON, FICON and Fibre Channel. This enables the Enterprise Storage System to be optimized for the price/ performance requirements of each computing environment.

Visit our Web site at: www.ibm.com/storage/ess

Centralize and share server storage across your data center

IBM Versatile Storage Server (VSS)

Fax Document 9315

- Scalable to over 4TB of serial disk storage capacity
- Dual SMP clusters with up to 6GB of read/write cache assure high performance for all attached servers



Remote management of VSS using Web-based storage management software over company-secured network/ intranet connections.



426-4329



IBM Versatile Storage Server (VSS)

Visit our Web site at: www.ibm.com/storage/vss

Reach optimum system performance and protection

IBM Fibre Channel RAID Storage Server

Fax Document 9660

- High performance with bandwidth of 200 MB/s with two **Fibre Channel ports**
- **Supports multiple RAID** levels (0, 1, 5 and 0+1)
- Automatic I/O path failover capabilities
- Dynamic RAID array migration, RAID array capacity expansion and segment size change
- Scalability designed to accommodate business growth, starting from 36GB to over 1TB.





2102-F10 IBM Fibre Channel RAID Storage Server and 2102-D00 IBM Expandable Storage Unit

This is an ideal solution for customers planning to implement Fibre Channel SANs or requiring high availability and easily managed storage solutions for their distributed systems.

Visit our Web site at: www.ibm.com/storage/fcss

Distributed data protection for network computing environments

IBM Network Storage Manager

Fax Document 5881







- Network Storage
- 332MHz PowerPC processor in a 2- or 4-way **SMP** configuration
- SSA Serial Disk Storage subsystem with 72GB to 864GB capacity
- Choice of industry-standard DLT tape library or **IBM Magstar* tape library**
- Preloaded NSM Software Package V3.1 that includes functions provided in Tivoli Storage Manager (formerly ADSM); as well as a Web browser function for administrators
- Support for clients running on more than 30 server types and ADSM-supported workstations
- Support for new 3466 models C00, C10, C20 and
- Optional features include: Disaster Recovery Manager (DRM), Hierarchical Storage Manager (HSM), Open Systems and Server-to-Server Communication.


Your business rides on your network, and the mission-critical business data that flows across that network must be protected at all times against both manmade and natural disasters. The IBM Network Storage Manager (NSM) is a complete, integrated storage solution that provides comprehensive distributed data protection and disaster recovery capabilities for your network computing environment. A member of the Seascape family of products, the easy-to-install-and-manage IBM Network Storage Manager (NSM) is a complete, integrated storage solution that provides comprehensive distributed-data protection and disaster recovery capabilities for your network computing environment.

Visit our Web site at: www.ibm.com/storage

Double the UltraSCSI data rate with Ultra2 SCSI

Ultra2 SCSI LVD Adapters

- Up to 80MB/s data transfer rate
- **Protects investment in existing disks**





IBM is now offering Ultra2 SCSI Low Voltage Differential (LVD) adapters in both RAID (FC2494) and non-RAID (FC6205) versions. Both support data rates of up to 80MB/s when used in conjunction with an Ultra2 SCSI LVD capable subsystem, such as IBM Expandable Storage Plus Models 2104-DL1 or 2104-TL1. They also support UltraSCSI or SCSI2 F/W implementation, thus protecting your investment in existing devices. In such a case the data transfer rate will be determined by the speed of the device, up to 40MB/s.

Feature 2494 supports RAID levels 0, 1 and 5 for either external or internal applications. When used in conjunction with available UltraSCSI hot-swappable disks in the RS/6000 models F50, H50 and H70, it provides an "under-the-covers" RAID solution that allows "hot-swap" in the event of disk

Feature	Description	Price
6205	Ultra2 SCSI PCI LVD 2-channel	\$790
2494	Ultra2 SCSI PCI 3-channel RAID (0,1,5) with 32MB Fast Write cache	\$3,500

Run at Ultra speed!

UltraSCSI Adapters

- Up to 40MB/s data transfer rate
- Cost-effective, 1-channel alternative for environments not Ultra2 SCSI capable
- Single-ended or Differential
- Industry Standard.

IBM offers 9.1GB and 18.2GB internal disks that run at Ultra speeds in many RS/6000 systems. Both adapters will support SCSI2 F/W implementation, thus protecting your investment in existing devices. In such a case the data transfer rate will be determined by the speed of the device, up to 20MB/s.

Feature	Description	Price
6206	UltraSCSI PCI Single Ended 1-channel	\$395
6207	UltraSCSI PCI Differential 1-channel	\$650

Ultra-fast, reliable access to data

3570 Magstar MP Tape Subsystem

Fax Document 5869





- NEW Extended Length Cartridge
- Magstar MP 3570 Model C enhanced to support 7GB native cartridge capacity (40% improvement)
- Serpentine longitudinal recording technique maximizes tape cartridge capacity (up to 21GB with 3:1 compression)
- Model C drives deliver data rates over three times faster than Model B drives (Model C: 7MB/s vs. Model B: 2.2MB/s).

The 3570 Magstar MP (Multi-Purpose) Magnetic Tape Subsystem expands the capability of tape to optimize both write- and read-intensive operations. You can access up to 420GB of compressed storage with near online performance. Model C drives can back up larger amounts in less time and existing B-Format data can be read and updated by Model C drives - up to a 50% improvement in performance.

The 3570 can be used with the RS/6000, AS/400, Netfinity and other popular SCSI-attach systems.

B01/B02:	19"W x 3.11"D x 9.7"H
C01/C02:	483mmW x 790mmD x 247mmH
B11/B12:	17.5"W x 19.5"D x 10.5"H
C11/C12:	444mmW x 748mmD x 266mm (6 EIA units)H

Product No.	Feature	Description	Lease [†]	Price
3570-B00		3570 MP Drive, Stand-alone	*	\$8,500
3570-B01	la nut ta	Magstar MP 1-Drive Library, Stand-alone	(A) * (A)	\$14,900
3570-B02	diw.stet	Magstar MP 2-Drive Library, Stand-alone	voe * no	\$23,400
3570-B11	REPORT OF IS	Magstar MP 1-Drive Library, Rack Mount	Ioon WA	\$14,900
3570-B12	en refere	Magstar MP 2-Drive Library, Rack Mount	*	\$23,400
3570-C00	SE BOOK AND	Magstar MP Drive Unit	*	\$14,999
3570-C01	illig exce	Magstar MP 1-Drive Library, Stand-alone	*	\$19,900
3570-C02		Magstar MP 2 Drive Library, Stand-alone	*	\$29,900
3570-C11		Magstar MP 1-Drive Library, Rack Mount	*	\$19,900
3570-C12	eran era	Magstar MP 2 Drive Library, Rack Mount	*	\$29,900
perionis	2007	Magstar MP Extended Length Cartridge	edylror	

[†] Turn to page 76 for details on lease payment information.

Media, interposers and cables available separately – call to order!

ECC Class A (defined on page 4)

Fast and reliable automated tape handling and storage

3575 Magstar MP Tape Library Dataserver

Fax Document 7631





Model 3575

- NEW Extended Length Cartridge
- Combined drive throughput of up to 300GB/hour (Model C drives) with maximum compression with 6 Model C drives
- Mid-point load for faster access to data
- Library cartridge capacities of 60, 120, 180, 240 and 324
- Native data capacities of 420GB, 840GB, 1.26TB, 1.68TB and 2.26TB
- Compressed data capacities of 1.26TB, 2.52TB, 3.78TB, 5.04TB and 6.8TB.

Here's a midrange and network tape storage solution for your RS/6000 system that is fully scalable to meet your growing needs. It provides an ideal near-online storage and retrieval system, as well as a high-capacity, high-performance, traditional, data-backup storage solution.

The 3575 has the speed needed to increase productivity in network storage management, image processing and data warehousing, and digital library applications. It also provides an ideal storage solution for less-frequently used, storage-intensive and historical applications. In addition, the patented, new, multipath architecture of the 3575 allows both homogeneous and heterogeneous hosts to share library resources.

Product No.	Feature	Description	Lease†	Price
3575-L06	modiff	Magstar MP Library, 60 cartridge	*	\$19,500
3575-L12	219.49.1610	Magstar MP Library, 120 cartridge	A *100	\$36,000
3575-L18	s Storage	Magstar MP Library, 180 cartridge	18181*-01	\$46,800
3575-L24	orage soli	Magstar MP Library, 240 cartridge	*	\$49,500
3575-L32	ta protect	Magstar MP Library, 324 cartridge	*	\$62,000
This QOB	2007	Magstar MP Extended Length Cartridge	KERKESHEDA	

[†] Turn to page 76 for details on lease payment information

^{*} PLEASE CALL FOR LATEST PRICES

FCC Class A (defined on page 4) Dimensions: 40"W x 34"D x 40"H

^{*} PLEASE CALL FOR LATEST PRICES

Put 374TB of data at your fingertips

Magstar 3494 Tape Library

Fax Document 2207





- Perform up to 610 cartridge mounts/dismounts per hour with DAA option
- Can mix 3490E and Magstar 3590 tape drives
- Modular growth
- Disaster recovery and unattended backup
- High-end reliability at a mid-range price.

Now you can use the modular, automated IBM Magstar 3494 Tape Library Dataserver to provide hierarchical storage management of up to 374 terabytes of data (over 6,000 cartridges) while reducing time and operational costs. The Magstar 3494 Model HA1 with a second library manager and accessor meets your high-availability needs. With feature 5230, up to 30 cartridges can be added or removed from the library without interrupting library operations. And a tape control unit expansion feature doubles the number of tape control units that can be attached to 16 - allowing you to add more Magstar 3590 tape drives in your Magstar 3494 library.

Туре	Mod	Feature	Description	Lease†	Price
3494	L10	Aun ndni	Tape Library Dataserver ¹	*	\$86,900
3494	L12	APIO1911	Tape Library Dataserver ¹	*	\$86,900
3494	L14		Tape Library Dataserver ¹	*	\$86,900
3494	D10		Drive Unit	9501-*300	\$35,000
3494	D12	306 - DL	Drive Unit	*	\$35,000
3494	D14	3713	Drive Unit	*	\$35,000
3494	S10	US 1581 1588	Storage Frame	* 1100	\$30,000
3494	HA1	for R8/80	High-availability Model	*	\$86,900
3494	B18 ^{††}	er 8mm b	Virtual Tape Server	vith a* eth	\$180,000
. egiv	10	5210	10 I/O Stations	bold *	\$3,630
A REPORT OF	30	5230	30 I/O Stations	(UU) *	\$8,710
		5228	Tape Control Support	*	\$2,000
nieureon	BT ROTERS	5215	Dual Gripper	*	\$10,000

[†] Turn to page 76 for details on lease payment information. †† Base 3494-B18 price

IBM's high-performance, largecapacity tape subsystem

Magstar 3590 Tape Subsystem

Fax Document 9664

- Up to 120GB backed up per hour*
- Up to 60GB* capacity per standard cartridge.

The IBM Magstar 3590 delivers a high level of reliability, performance, capacity and cost-effectiveness. When attached to RS/6000 servers with Ultra SCSI adapter (FC 6207) it can provide a data rate up to 40MB/s, compacted. Magstar 3590 cartridges have a capacity of up to 20GB. Up to 60GB per cartridge can be stored using LZ1 compaction. With it's Automatic Cartridge Facility (ACF) the rack models can provide random access up to 300GB with the 3590-B11 and 600GB with the 3590-E11 of compacted data stored in a removable ten-cartridge magazine. *User results may vary.

Туре	Mod	Description	Lease [†]	Price
3590	B1A	Designed for use in 3494	boak *	\$29,500
3590	B11	Rack-mount, includes ACF	*	\$32,500
3590	E1A	Designed for use in 3494	*	\$43,500
3590	E11	Rack-mount, includes ACF	value* shown assu	\$46,500
		Model BXX to Model EXX Upgrade	Selv I*3880 On dell	\$15,500

[†] Turn to page 76 for details on lease payment information

FCC Class A (Defined on page 4)

Dimensions: B1A: 8.8"W x 29.8"D x 10.5"H B11: 9.1"W x 39"D x 20.6"H

* PLEASE CALL FOR LATEST PRICES

Compact, yet full-featured tape

3490E Magnetic Tape Subsystem

- 18- and 36-track reading and writing for RS/6000
- Simplified tape threading and improved mechanical and data reliability
- Random access to up to 24GB of compacted data using the 10-cartridge ACF.

The 3490E F models write bidirectionally, doubling the capacity of a base IBM Cartridge System Tape and virtually eliminating rewind time. Using the Improved Data Recording Capability (IDRC) and a SCSI interface, effective data throughput can be as high as 6.8MB/sec. Connection can be made to a wide variety of RS/6000 PCI and non-PCI SCSI-2 and Ultra SCSI adapters.

Туре	Mod	Description	Lease	Price
3490	F00	Tabletop Single Drive	*	\$18,500
3490	F01	Tabletop Single Drive 10 Cartridge RAL	300× 15	\$22,500
3490	F11	Rack-mounted Single Drive 10 Cartridge RAL	*	\$22,500
3490	F1A	Library Model	*	\$18,500

[†] Turn to page 76 for details on lease payment information

FCC Class A (Defined on page 4) Dimensions: 17"W x 24"D x 7"H

PLEASE CALL FOR LATEST PRICES

FCC Class A (Defined on page 4)

Dimensions: 30"W x 60"D x 71"H PLEASE CALL FOR LATEST PRICES

High-capacity, high-performance

7205 Digital Linear Tape Drive



- High Capacity: 35GB to 70GB^{††} data storage capacity
- High Throughput: 5MB/sec. to 10MB/sec.^{††} data transfer rate.

IBM's newest stand-alone tape drive employs proven DLT7000[†] tape technology and provides the benefits of shorter backup windows, less operator intervention, affordable and reliable data integrity and high-function saveand-restore tape management. It has flexible read/write compatibility with previous DLT media formats and features proven longitudinal serial serpentine recording format for high reliability.

Туре	Mod	Leasettt	Price
7205	311	*	\$11,850

DLT7000 is a trademark of Quantum Corp.

T Capacity values shown assume average compression ratios. Compression ratios can vary widely based on data characteristics.

*** Turn to page 76 for details on lease payment information.

FCC Class B (Defined on page 4) PLEASE CALL FOR LATEST PRICES

Speed and reliability on a desktop

7208 External 8mm Tape Drive



- 20GB to 40GB† data storage capacity
- Up to 6MB/sec. data transfer rate.

Our 7208 Model 341 External Tape Drive is a compact, tabletop drive with the capacity, advanced performance and high reliability you demand in a data storage solution.

Enhanced reliability is provided through a streamlined, rugged design with fewer moving parts, improved capstanless tape path, dynamic head cleaner, simplified and gentle tape loading and highly-integrated electronics and diagnostics.

The onboard data compression of the new 8mm Mammoth drive increases its data storage capacity up to 40GB† on new 170-meter 20GB AME tape.

Туре	Mod	Lease ^{††}	Price
7208	341	*	\$6,500

† Capacity values shown assume average compression ratios. Compression ratios can vary widely based on data characteristics.

† Turn to page 76 for details on lease payment information.

FCC Class B (Defined on page 4) Dimensions: 11"W x 11.3"D x 3.125"H

PLEASE CALL FOR LATEST PRICES

Supports up to 13GB native

7207 1/4" Cartridge Tape Drive



For reliable and affordable entry-level external tape storage, IBM's 7207 family of products leads the way. This leadingedge tape storage subsystem offers up to 13GB native per tape cartridge and up to 26GB per cartridge with 2:1 compression. With an enhanced data transfer rate of up to 1.5MB/sec. native (up to 3MB/sec. with 2:1 compression), the 7207 is an excellent solution for customers who are migrating from older 1/4-inch and 4mm tape formats.

Туре	Mod	Description	Lease [†]	Price
7207	122	4GB native	*	\$1,850
7207	315	13GB native	AND WOOM TELE	\$4,940

[†] Turn to page 76 for details on lease payment information. FCC Class B (Defined on page 4)

Dimensions: 9 8"W x 10 8"D x 2 2"H PLEASE CALL FOR LATEST PRICES

Terrific low-cost solution

7206 External 4mm Tape Drive



7206

This powerful stand-alone DAT cartridge tape drive is the ideal low-cost solution for your workstation storage needs. It features an advanced data grade "media recognition" system along with host-independent diagnostics.

	Storage Capacity	Data Transfer Rate
7206-005	4GB to 8GB [†] data	400KB/sec. to 800KB/sec. New DDS-3 technology
7206-110	12GB to 24GB	1.1MB/sec. to 2.2MB/sec.

Туре	Mod	Lease ^{††}	Price
7206	005	5230 * Sp.(40) Spikers	\$2,995
7206	110	2 Instan 3 and T * 9005	\$3,245

† Capacity values shown assume average compression ratios. Compression ratios can vary widely based on data characteristic

 $^{\rm tt}$ Turn to page 76 for details on lease payment information. FCC Class B (Defined on page 4)

Now available for HP, Sun and DEC systems. Call for details. Dimensions: 11"W x 11.3"D x 3.125"H

Autoloading save-and-restore

7332 4mm DDS-3 Tape Autoloader

Fax Document 1996



426-4329



7332

■ Low cost, 4mm tape cartridge auto loader

■ 1.1MB/sec data transfer rate - up to 2.2MB/sec with data compression.

Operating in streaming mode, this external, multiplecartridge, tape autoloader is read/write compatible with older IBM 7206 models as well as other open systems 4mm tape devices. Designed with advanced digital audio tape (DAT) technology. 4-cartridge magazine yields 48GB data storage capacity - up to 96GB capacity (compressed data).

Туре	Mod	Description	Lease [†]	Price
7332	110	(4-cartridge magazine)	ides hoth PC a	\$5,745

FCC Class B (Defined on page 4) Also available for HP and Sun systems. Call for details. Dimensions: 11"W x 11.5"D x 4.8"H

* PLEASE CALL FOR LATEST PRICES

Expand your storage needs effectively

7337 (DLT) Digital Linear Tape Library





■ Model 305 - DLT Stand-alone Desktop Library

■ Model 306 - DLT 19" Rack-mountable Library.

Models 305 and 306 are efficient offerings of DLT Tape technology for RS/6000 systems. DLT offers additional capacity over 8mm tape to 35GB/70GB with an effective data rate of up to 10MB/sec.

Туре	Mod	Description	Lease	Price
7337	305	DLT Stand-alone Desktop Library	* 55	\$23,995
7337	306	DLT Rack-mountable Library	HOUL DO * Lang	\$23,995

Turn to page 76 for details on lease payment information

FCC Class B (Defined on page 4)

PLEASE CALL FOR LATEST PRICES

High-capacity tape library

7331 8mm Tape Library

Fax Document 3045





- Holds up to 20 cartridges (20GB each) for a total storage capacity of up to 400GB (up to 800GB of compressed data)
- Up to 6MB/sec per drive with data compression
- Includes 1 or 2 20GB tape drives (dual drive is field-installable)
- Automatic drive cleaning.

This high-performance tape library is perfect for customers with ever-growing online storage needs that include save/ restore, program distribution, migration, data interchange, automatic migration of data between disk storage and tape mass storage for data archive.

The IBM 7331 Tape Library has a dual-host function which will allow two RS/6000 processors to be attached and operated as two independent libraries. This tape library has 1 or 2 tape drives and 2 removable magazines with slots for twenty 8mm cartridges plus two bonus slots: one for cleaning cartridges and one for user-defined purposes. Using an implementation of IBM's improved data recording capabillity (DRC), up to 40GB of data can be stored on a single cartridge with a data transfer rate of up to 6MB/sec. This is equal to as much as 43GB per hour with compression on a split, dual-host, two-drive model.

Туре	Mod	Description	Lease [†]	Price
7331	305	20/40GB 8mm	protein *	\$13,995

Turn to page 76 for details on lease payment information. FCC Class B (Defined on page 4) Also available for HP and Sun systems. Call for details Dimensions: 8.8"W x 26.6"D x 24.5"H

PLEASE CALL FOR LATEST PRICES

Five versatile network printing solutions

Workgroup Printers



■ Full connectivity - parallel, network and IBM host. IBM Infoprint 40

High quality output with print speeds up to 40 pages per minute (ppm) is achieved with this robust workgroup printer. It features 600 dpi quality (with REFINE mode that rivals 1200 dpi quality), a duty cycle up to 200,000 pages monthly, RePro copier-like function, optional 2,000 sheet finisher with stapling and offset jogging, and duplex option for two-sided printing.

Complete family of midrange, heavy-duty printers

6400 Line Matrix Printers

- Attachment via ethernet ASCII, coax or twinax interfaces, parallel or serial network
- Supports wide range of systems from IBM mainframe/parallel servers to PCs
- Emulation with IBM Proprinter', Epson and an expanded range of Printronix" printers.



IBM's family of continuous form, line matrix 6400 printers covers the full spectrum of print requirements for today's busy office environments, offering high-quality printing from 500 lines per minute (lpm) to a high-volume 1,500 lpm.

The 6400 family supports IPDS*, SCS and ASCII for IBM and non-IBM environments. All 6400 models can handle one- to six-part forms and offer a number of flexible form handling characteristics.

IBM Infoprint 32

A heavy-duty, 32 page per minute (ppm) workgroup printer that features: optional duplex, 600 dpi printing, RePro transmit-once copier-like capability, duty cycle up to 150,000 pages monthly and optional 2,500-sheet input and 2,000-sheet finisher with stapling and offset jogging.

IBM Infoprint 20

Award-winning office and workgroup printer delivers up to 20 ppm speed, 600 dpi quality (with 1200 dpi emulation), Adobe PostScript 3 support, 75,000-page maximum monthly duty cycle and full-bleed 11x17 and A3/ledger printing.

IBM Network Printer 17

Versatile 17 ppm printer with standard duplex printing features 600 dpi quality with TrueRes edge smoothing and up to 5 input trays with 1,350-sheet total capacity, with offset jogging and secure mailbox options.

IBM Network Printer 12

A compact, entry-level printer for small workgroups that prints up to 12 ppm at 600 dpi with TrueRes edge smoothing and provides both PC and Macintosh** support.

Ideal for all of your form-printing requirements

4247 Multi-Form Printer



The 4247 handles multiple forms.

The versatile 4247 is ideal for high-speed office printing, heavy-duty printing for small systems, or workstation printing for larger systems and networks. With the 4247, you can load up to six different types of forms at once, allowing you to consolidate applications that previously required multiple printers. Rated speed is 700 characters per second.

Dimensions: 26.75"W 15.75"D 12.25"H

Warranty: Three months

FCC Class A (Defined on page 4)

visit w

www.ibm.com/Shop

call 800 426 2255 today

Improved performance and network connectivity

3130 Advanced Function Printer

- Up to 3 concurrently active interfaces
- Low cost of operation
- Either 240 or 300 dpi resolution
- Superior IPDS performance.



Advanced, cut-sheet machines that print up to 30 impressions per minute and 200,000 impressions per month, the 3130 models 03S and 02D feature optional network attachments for improved connectivity in AIX, IBM LAN Server and Novell NetWare** environments. They are available with support for PCL5e and PostScript Level 2 as well as drivers for AIX, OS/2* and Microsoft Windows.

Dimensions: O3S: 26"W x 26"D x 54"H

O2D: 26"W x 26"D x 54"H Warranty: Three months

FCC Class A (Defined on page 4)

The new standard in distributed, cut-sheet printing

IBM Infoprint 60/3160 Advanced Function Printer

- Speeds up to 60 ipm
- Duty Cycle up to 750,000 pages per month
- Infoprint 60 now offers optional PCL5e support
- Supports Adobe **PostScript Level 2 and PCL** (through IBM server technology).



High-volume, high-speed printing in a small footprint

Speed, flexibility and affordability make these cut-sheet printers perfect for the most demanding data center or departmental needs. The IBM 3160 and the Infoprint 60 pack power and endurance into one of the smallest footprints in their class (just over 7 sq. ft.).

Optional finisher for the Infoprint 60 also available (not compatible with PCL5e option).

Dimensions: 41.75"W x 27.4"D x 51.2"H

Warranty: Three months

FCC Class A (Defined on page 4)

IBM printers to meet your every need

Printer Comparison Table

Printer	Speed	Description	Lease [†]	Price	Fax Doc
LASER	Estate 2.2.2. Assignment	steed contrastivity for the majorous	топил ецениот с	ametava	
Network Printer 12	Up to 12 PPM	Cut sheet	*	\$1,036	-
Network Printer 17	Up to 17 PPM	Cut sheet, duplex standard	*	\$1,387	-
Infoprint 20	Up to 20 PPM	Cut sheet	*	\$1,999	70000
Infoprint 32	Up to 32 PPM	Cut sheet	* 20	\$3,229	-
Infoprint 40	Up to 40 PPM	Cut sheet	*	\$3,799	-
3130-02D	Up to 30 ipm	Cut sheet, duplex	*	\$20,995	3139
3130-03S	Up to 30 ipm	Cut sheet, simplex	*	\$17,995	3139
3160-001	Up to 60 ipm	Cut sheet, duplex	Addust *	\$49,995	3916
Infoprint 60 (3160-002)	Up to 60 ipm	Cut sheet, duplex	*	\$69,995	3916
LINE MATRIX	smale connection of up to ito in	5-122 devices to	ded: X 21£5	MARKING	
6400-050	Up to 500 lpm	Enclosed cabinet	*	\$6,195	2108
6400-P50	Up to 500 lpm	Pedestal model	s one S igapit E	\$5,195	2108
6400-010	Up to 1,000 lpm	Enclosed cabinet	2m912 * 1319 (\$7,995	2108
6400-P10	Up to 1,000 lpm	Pedestal model	naitemana volm	\$7,395	2108
6400-015	Up to 1,500 lpm	Enclosed cabinet	*	\$11,595	2108
DOT MATRIX	Vind XXX labely) \$30,000 miles and the control of t	Toyqu	C WIE	
4247-A00	700 cps	ASCII, continuous forms, cut sheet	*	\$2,895	4753
4247-001	700 cps	ASCII, Coax or Twinax, continuous forms, cut sheet	*	\$3,595	4753
4230-413	600 cps	IPDS, Twinax/ASCII, continuous forms, cut sheet	*	\$3,995	2899
4230-4S3	600 cps	SCS, Twinax/ASCII, continuous forms, cut sheet	*	\$3,395	2899
4230-513	600 cps	IPDS, Coax/ASCII, continuous forms, cut sheet	*	\$3,995	2899
4230-5S3	600 cps	SCS, Coax/ASCII, continuous forms, cut sheet	*	\$3,395	2899
4232-302	600 cps	ASCII, continuous forms, cut sheet	*	\$2,595	2245

Turn to page 76 for details on lease payment information.

FCC Class A (Defined on page 4)

* PLEASE CALL FOR LATEST PRICES

With IBM, you will make the perfect connection every time

Local Area Network Adapters





Feature	Description	Price
thernet Ada		AF0-
2993	Ethernet BNC MC Adapter	\$595
	Designed for connection to 10Mbps networks with improved price/performance over previous Ethernet adapter (#2980).	
	Optimized 32-bit busmaster interface and software device driver for high throughput, low latency and reception Makes full use of the 40MB/sec. data streaming capability of the Micro Channel bus Compatible with IEEE 802.3, 10Base2 networks	etes enelle eggae
2992	Ethernet/FDX 10Mbps TP/AUI MC Adapter	\$595
	Provides full duplex Ethernet connectivity for RS/6000 systems.	
	 Supports 10BaseT networks directly or any 802.3 medium via external transceiver connected to AUI port Makes full use of the 40MB/sec. data streaming capability of the Micro Channel bus Optimized 32-bit busmaster interface, low latency and low device driver overhead to free up more CPU power 	investa Talana Talana
2994	IBM 10/100Mbps Ethernet MC Adapter	\$795
	This fast Ethernet solution offers MCA-based RS/6000 users an easy migration from 10Mbps to 100Mbps. Uses Category 5 UTP wiring.	
atures 600 or quality), opier ike fi	Single-port connection to 10/100BaseTX LANs using UTP Category 5 cable Supports full duplex Auto Speed detection – adapter automatically senses the line speed: 10Mbps or 100Mbps	
2985	Ethernet BNC/RJ-45 PCI Adapter	\$195
	Provides 10Mbps Ethernet connectivity for PCI RS/6000 systems.	
	- Supports 10BaseT or 10Base2 networks directly - Provides full duplex Ethernet on 10BaseT port	
2987	Ethernet AUI/RJ-45 PCI Adapter	\$195
	Provides 10Mbps Ethernet connectivity for PCI RS/6000 systems.	
70.00	- Supports 10BaseT networks directly or any 802.3 medium via external transceiver connected to AUI port	
2968	10/100Mbps Ethernet PCI Adapter	\$275
	This fast Ethernet solution offers PCI-based RS/6000 users an easy migration path from 10Mbps to 100Mbps LANs without requiring a change of adapter.	
	Supports full duplex using Category 5 UTP cable Auto Speed detection Adapter is designed to sense the line speed: 10Mbps or 100Mbps	
2969	Gigabit Ethernet - SX PCI Adapter	\$2,125
	Provides one Gigabit Ethernet connection for selected RS/6000 PCI systems	
	- Full duplex operation - Multimode fiber - NIM support	

Feature	Description	Price
FDDI Adapt		40.055
➤ 2724	FDDI-Fiber Single-Ring Adapter (MC)	\$3,955
	LAN communications adapter using optical cabling designed for FDDI protocols with a line speed up to 100Mbps.	
	- Compatible with ANSI X3T9.5 and ISO 9314, requires one Micro Channel slot	
	Fax Doc 2283	n R e
► 2723	FDDI-Fiber Dual-Ring Upgrade Kit (MC)	\$1,995
	An upgrade for FC #2724 for use with dual attach stations – requires additional Micro Channel slot.	
2741	SysKonnect SK-NET FDDI-LP SAS PCI Fiber [†]	\$1,590
► 2742	SysKonnect SK-NET FDDI-LP DAS PCI Fiber [†]	\$2,230
2743	SysKonnect SK-NET FDDI-UP SAS PCI UTP [†]	\$955
	[†] Lets PCI-based RS/6000 users connect to fiber or UTP FDDI rings as either SAS (Single Attach Station) or DAS (Dual Attach Station), directly or through FDDI concentrators.	
	High speed, low latency and low CPU and bus utilization AMD SUPERNET3 single-chip FDDI design Conforms to FDDI-ANSI X3T12 specification and FDDI Standard Series	
Token Ring		
➤ 2972	Auto Token-Ring LANStreamer MC 32 Adapter	\$850
	Additional functionality over FC #2970 includes:	
	Adapter Auto senses line speed between 4Mbps and 16Mbps Data streaming support Supports full duplex	
➤ 2920	Auto Token-Ring LANStreamer' PCI Adapter	\$795
	Provides 4/16Mbps Token-Ring connectivity for PCI RS/6000 systems.	
	Adapter is designed to sense the line speed between 4Mbps and 16Mbps Data streaming support 7025-F40 and 7043-140 only	
4959	IBM Token-Ring PCI Adapter	\$795
	PCI adapter for RS/6000	
	 Single slot, short, 32-bit PCI adapter Supports 4 or 16 Mbps data rates, either half-duplex or full-duplex 	
	ransceivers (AMARIAN DIE	010-00%
4223	Ethernet 10Base2 Transceiver	\$195
	Provides a connection to thin Ethernet coaxial cable, 10Base2 (Model 2XX only).	
kerlaw II. ko xeb	 Compatible with Ethernet/IEEE 802.3 transceiver specifications and 10Mbps Ethernet CSMA/CD operation 	

FCC Class A (Defined on page 4) FCC Class B (Defined on page 4) - (except features 2741, 2742 and 2743)

▶ 24 Hour QuickShip

Communications Adapters and Cables

Asynchronous Adapters and Cables

Feature	Description	Price
➤ 2930	8-Port Async Adapter - EIA-232 (MC)	\$832
	Allows for attachment of up to eight EIA-232D Async serial devices.	
	- Supports eight ports, utilizing one I/O card slot (eight connectors for device attachment are provided in Multiport Cable #2995) - Data rates up to 38.4Kbps per port - Supports cabling up to 61 meters (200 ft.) FC #2950 for MIL-STD 188 also available, call for details	
▶ 8128	128-Port Async Controller (MC)	\$1,295
nevirb s	Provides support for attaching a maximum of 128 EIA-232D asynchronous serial devices using a single Micro Channel slot.	ψ1,230
	- Contains two async channels - each allows a daisy-chain cable connection of up to four Remote Async Nodes (FC #8130) - Support for direct or synchronous modem	
	- Attachment of up to eight Remote Async Nodes - 512KB memory	
	Fax Doc 2282	
2943	8-Port Async EIA 232/422A PCI BUS	\$1,395
	- Supports eight ports, utilizing one I/O card slot - Data rates up to 230Kbps per port - EIA 232A supports up to 61 meters (200 ft.) - RS 422A cabling up to 1,200 meters (4,000 ft.) - Includes 8-Port breakout cable	
≥ 2944	128-Port Async Controller - PCI BUS	\$1,295
	- Contains two synchronous channels - each allows a daisy-chain cable connection up to four Remote Async Nodes - Data rates up to 230Kbps - Supports cabling up to 61 meters using EIA RAN (FC # 8136), up to 1200 meters using 422 RAN (FC # 8137)	
ANS		
▶ 8137	Enhanced Remote Async Node RAN 16-Port EIA-232	\$1,595
	Provides remote connection of up to 16 EIA-232 devices to a 128-Port Async Controller adapter. FC #8128 (MC), #2933 (ISA), #2944 (PCI).	
	- 16 async ports each with a data interchange rate up to 230Kbps - Cable lengths up to 200 feet	
	- Compatible with EIA-232D Full set of modem control signals	
▶ 8138	Enhanced Remote Async Node RAN 16-Port RS-422	\$1,795
	Provides remote connection of up to 16 RS-422 devices to a 128-Port Async Controller adapter. FC #8128 (MC), #2933 (ISA), #2944 (PCI).	
	- 16 async ports each with a data interchange rate up to 230Kbps - Cable lengths up to 4,000 feet - Supports the following interface signals: +TxD, +RxD, -TxD, -RxD	

MC = Micro Channel
FCC Class A (Defined on page 4)

Feature	Description	Price
synchronou	us Communications Cables	512.000
8131	128-Port Async Controller Cable	\$60
	Length (M) = 4.57	
8132	128-Port Async Controller Cable	\$40
	Length (M) = .23 For use with FC #2944 and #8128 provides an 8-wire Controller-to-RAN, or RAN-to-RAN connection	
8133	RJ-45 to DB25 0.61 Converter Cables	\$120
	For use with FC #8137 - provides 25-pin D-shell connector for device attached to RAN (four cables provided per order).	
8135	64-Port to 128-Port Pin-out Converter	\$45
	Attaches async devices wired for 64-port concentrators to 128-port remote async nodes EIA-232 (quantity: four to a package).	
2995	Multiport Interface Cable	\$384
	Length (M) = 3	
	For use with FC #2930, #2940, #2950	
ide Area No	etwork Adapters	1405
2700	4-Port Multiprotocol Communications	\$2,600
	Controller (MC)	
	Attaches system to synchronous networks at data rates up to 64Kbps per port (user-provided software required).	
	 Prepares all in/outbound data, relieves system processor of various communications tasks, supports SDLC and BSC protocols 	
	 Supports EIA-232D on Ports 0, 1, 2 and 3; EIA-422A on Ports 0 and 2; V.35 on Ports 0 and 1; and X.21 on Port 0 Multiport interface box and cables for X.21, EIA-232 and V.35 are available 	
2708	Eicon ISDN DIVA PCI Adapter	\$995
	Allows ISDN Basic Rate connection to RS/6000 integrating with AIX PPP-Subsystem allowing TCP/IP protocol to connect over ISDN.	
	- 2 B Channels - 64KB each channel	
	- 1 D Channel	
	 Support for 2 64KB connections Multilink PPP capability combining both 64KB channels together providing a single 128KB data path Common ISDN API Version 2.0 (CAPI 2.0) compliant 	
	- Global ISDN Support - Europe - ETSI - USA - National ISDN 1 and ATT 5ESS- Australia - ATEL - Japan	
2962	2-Port Multiprotocol PCI Adapter	\$1,595
	Allows SDLC and X.25 connections to synchronous data networks at speeds up to 64Kbps per port. The following physical interfaces are supported: X.21, V.24, V.35 or V.36.	
	- Full duplex, synchronous - Cables supported - Supports SDLC and X.25	
ommunicat	ion Cables	
2951	2-Port V.24/EIA-232 Cable	\$175
2952	2-Port V.35 Cable	\$320
2953	2-Port V.36/EIA-449 Cable	\$255
2954	2-Port X.21 Cable	\$175



Get connected with IBM

Wide Area Network Adapters



FCC Class A (Defined on page 4)

▶ 24 Hour QuickShip

High-speed, high-throughput

ARTIC Communications Adapters

- Helps relieve the host from compute-intensive tasks associated with WAN applications and protocols, providing 4-6 times higher performance than Portmaster adapters
- New 8-port models support 8-port EIA-232, 6 port V.36 and 8 port X.21
- All ports support WAN link speeds up to 2.048Mbps full duplex
- All models include ARTIC real-time kernel and AIX V3.2.5 Operating system development driver.

ARTIC is a family of high-speed, high-throughput coprocessor adapters designed to operate in 32-bit Micro Channel bus-compatible systems. Call for cabling options.

Description	Price
mmunications Adapters	
ARTIC Portmaster* (1.0MB) (MC)	\$1,595
ARTIC Portmaster EIB (8 port, RS232) (MC)	\$697
ARTIC Portmaster EIB (8 port, RS422) (MC)	\$673
ARTIC Portmaster EIB (6 port, V.35) (MC)	\$1,227
ARTIC Portmaster EIB (6 port, X.21) (MC)	\$1,000
	ARTIC Portmaster* (1.0MB) (MC) ARTIC Portmaster EIB (8 port, RS232) (MC) ARTIC Portmaster EIB (8 port, RS422) (MC) ARTIC Portmaster EIB (6 port, NS422) (MC) ARTIC Portmaster EIB (6 port, V.35) (MC)

Connectivity is more than just hardware!

Whether you are setting up a network or expanding your e-business, IBM Global Services can provide the expert assistance you need. For more information see pages 72 - 74.

Communications Adapters

Channel Adapters

Feature	Description	Price
2751	System/390 ESCON Control Unit Adapter (PCI)	\$9,500
	Attaches RS/6000 via fiber optic link to System/390* and ESCON-capable System/370* hosts, as well as ESCON attached tape peripheral devices.	front only front de files for the
	Attachment is supported on both 10MB/s and 17MB/s ESCON Channels RS/6000 device driver Interface (provided) supports user written channel programs	473
2754	S/390 ESCON Channel Emulator Adapter (MC)	\$10,000
	Allows attachment of selected ESCON-capable I/O units (tape units and tape libraries) to RS/6000.	
	- Extends I/O attachment capabilities offered by the S/370 Channel Emulator/A Adapter (FC #2759) to ESCON customers - Fax Doc 3053	Solida Solida Solida
2755	Block Multiplexer Channel Adapter (MC)	\$4,400
	Provides high-speed parallel channel communications to a S/370 or S/390 at data rates up to 4.5Mbps (requires FC #2757 and #2758).	
	- Supported on AIX Version 4.1.4	
2756	System/390 ESCON Control Unit Adapter (MC)	\$10,000
	Attaches RS/6000 via fiber optic link to System/390 and ESCON-capable System/370 hosts (requires two Micro Channel slots).	
	Attachment is supported on both 10MB/s and 17MB/s ESCON Channels RS/6000 device driver Interface (provided) supports user written channel programs	
2757	Block Multiplexer Channel Adapter Cable	\$700
2758	Block Multiplexer Channel Cable Assembly	\$900
	Requires S/370 channel bus/tag cable.	
2759	S/370 Channel Emulator/A Adapter (MC)	\$3,500
	Allows attachment of selected Pennant* Printers and ADSTAR tape subsystems to an RS/6000 via an S/370 parallel channel (block multiplexer) connection.	
	Includes adapter, cable, wrap plugs, terminators and diagnostic diskette Requires separately purchased software Print Services	
	Facility* (#5765-505) or Parallel Channel TP Attach (#5799-QDA) - Fax Doc 2288	4-12-5 2-13-6
DDMD Gaice		444 444
2732	IBM Short wave Serial HIPPI PCI Adapter for RS/6000	\$12,000
2732		\$12,000

Feature	Description	Price
2733	IBM Long wave Serial HIPPI PCI Adapter for RS/6000	\$12,000
	Single slot, full size, 32-bit PCI adapter supporting TCP/IP over a serial HIPPI link. Data is sent and received over optical fiber at 1.2Gbps using the HIPPI standard 20/24 bit encoding scheme with long wave optical transducers. The effective maximum data rate of the HIPPI interface is 800Mbps.	
	- Attachment to a Serial HIPPI Network	
RBOWAY	S ATM Adapters	
2989	TURBOWAYS* 155 ATM Adapter (155Mbps) (MC)	\$2,695
	High-performance intelligent adapters providing direct access to high-bandwidth asynchronous transfer mode (ATM) LANs.	
	Offers RS/6000 users cost-efficient access to ATM networks supporting voice, data and video Operation at 155Mbps (TURBOWAYS 155) full-duplex to provide dedicated bandwidth between RS/6000 and other ATM devices	
	i960 RISC processor and specialized ATM chips offload tasks from host processor Up to 2 adapters can be installed in single RS/6000 Micro Channel Up to 1,024 virtual connections	
	- PVC/SVC support ATM Forum UNI 3.0, UNI 3.1 - ATM adaptation layer (AAL) 5 support - Supported on AIX 3.2.5 and AIX 4.1.4 or later - Supports IP over ATM, RFC 1577 - Supports LAN Emulation 1.0	
2998	TURBOWAYS 25 ATM PCI Adapter	\$375
	25Mbps ATM adapter providing access through an IBM 25Mbps ATM Concentrator (#8282) to an ATM LANs.	
	- Up to 6 adapters can be installed in a system - Up to 32 virtual connections - PVC/SVC support ATM Forum UNI 3.0, UNI 3.1 - Uses Cat-5 UTP wiring - Supports IP over ATM, RFC 1577 - Supports LAN Emulation 1.0	
2988	TURBOWAYS 155 ATM PCI MMF Adapter	\$1,595
	155Mbps ATM adapter providing access to an ATM switch.	
	- Up to 4 adapters can be installed in a system - Up to 1024 virtual connections - PVC/SVC support - ATM Forum UNI 3.0, UNI 3.1	
	- Vess 62.5 micron multimode fiber - Supports IP over ATM, RFC 1577 - Supports LAN Emulation 1.0	
2963	TURBOWAYS 155 ATM PCI UTP Adapter	\$1,495
XA) guma XA guma	Same as #2988, however attaches to Category-5 unshielded twisted pair (UTP Cat-5) wiring.	
scellaneou		
2936	Async Cable - EIA-232/V.24 Length (M) = 3	\$73
2945	Terminal Cable - EIA-422A Length (M) = 20	\$130



FCC Class A (Defined on page 4)
MC = Micro Channel
▶ 24 Hour QuickShip

QuickShip - The technology



No-Charge 2-day delivery of your order

In a hurry to get your new RS/6000 solution in place? This is a job for QuickShip! You get no-charge 2-day delivery of over 259 different RS/6000 products, anywhere in the continental U.S. (Alaska and Hawaii, \$5 charge). **Just place**

your order by 1 p.m. Eastern Time, and we'll ship your order the same day, delivering them to your door within 48 hours!

Want it faster? How about tomorrow?

If you wish, we can deliver your QuickShip order to you overnight, for a nominal charge:

CONTINENTAL U.S.

\$5 - up to 5 lbs.

\$10 - >5 to 20 lbs.

\$15 - >20 to 60 lbs.

\$35 ->60 to 100 lbs.

\$55 - >60 to 100 lbs.

ALASKA AND HAWAII

\$10 - up to 5 lbs.

\$15 - >5 to 20 lbs.

\$25 ->20 to 60 lbs.

\$45 ->60 to 100 lbs.

Feature Number/Description

MART CAMP (OVOCAR DIMANA)

Call for price - over 100 lbs. Call for price - over 100 lbs.

To Use QuickShip, you need:

- Commercial account relationship with IBM
- Current, valid IBM customer number
- Current, signed IBM Customer Agreement (ICA)
- Favorable payment history with IBM
- Location and shipment in the U.S.

Page

 Payment by purchase order, check, money order or credit card

¹ QuickShip orders require a valid IBM customer number to ensure shipment within 24 hours. Orders placed without a valid customer number will be shipped within 48 hours.

RS/6000 QUICKSHIP PRODUCTS

Feat	Page	
	MONITORS	
3629	Pearl White 17" P76 color monitor	50
3621	Pearl White 19" P92 color monitor	50
3630	Pearl White 21" P260 color monitor	50
3627	Stealth Black 17" P76 color monitor	50
3625	Stealth Black 19" P92 color monitor	50
3628	Stealth Black 21" P260 color monitor	50
	MODEL F40	
3071	4.5GB SSA Hot-Swap Drive	30
4306	2nd 166 MHz PowerPC 604e	18
4341	2nd 233MHz PowerPC 604e	18
4114	Additional 64MB ECC DIMM	18
4113	32MB DIMM	28
4115	128MB DIMM	28
6159	12GB/24GB 4mm Internal Tape Drive	18
2913	9.1GB UltraSCSI	30
	MODEL F50	
4307	PowerPC 604e 166MHz 1-way	19
4309	PowerPC 604e 166MHz 2-way	19
4358	PowerPC 604e 332MHz 1-way	19
4359	PowerPC 604e 332MHz 2-way	19
3074	9.1GB SSA Hot-Swap drive	30
3071	4.5GB SSA Hot-Swap drive	30
4093	OMB Card	28
	MODELS F50, H50	
3071	4.5GB SSA Hot-Swap Drive	30

4107	64MB (2X32MB DIMMs)	19, 28
4093	OMB card	28
	MODEL H70	AND THE PARTY OF T
4093	OMB Card	28
4107	64MB (2X32MB DIMMs)	21, 28
4110	256MB (2X128MB DIMMs)	. 21, 28
4119	512MB (2X256MB DIMMs)	21, 28
	MODELS J50, R50	
4165	256MB (1GB) Card	22, 28
4166	256MB DIMM kit	22, 28
VIA:	MODEL CZO ADVANCED	
2040	MODEL S70 ADVANCED	00
2913	9.1GB F/W Ultra SCSI	23
4171	512MB Memory Group (4X128MB)	23
4173	1024MB Memory Group (4X256MB)	23
4175	2048MB Memory Group (4X512MB)	23
4177	4096MB Memory Group (4X1024MB)	23
4179	8192MB Memory Group (4X2048MB), for Model S70A	23
5312	PowerPC RS64 II 4-way Processor Card with 8MB L2 Cache, for Model S70A	23
6159	12GB/24GB 4mm Internal Tape Drive	23
6156	20GB/40GB 8mm Internal Drive, for Model S70A	23
harden.	MODELS 120, 133	
4083	32MB SIMM	29

Feat	ture Number/Description	Page	
	MODELS 25T/41W/42W/T		
4011	16MB SIMM	29	
4012	32MB SIMM	29	
	MODELS 140/240		
2908	9.1GB UltraSCSI	15	
2909	18.2GB UltraSCSI	15	
4113	32MB DIMM	29	
4114	64MB DIMM	15, 29	
4115	128MB DIMM	15, 29	
Co E	g Rugio 24 pp. 6 ambazo en 25 a 16 a Rugio de solicitore en 20 a		
	MODEL 3CT		
	64MB Card	29	
	126MB Card	29	
4095	256MB Card	29	
199	High tains avew horiz tilli	\$6744 F	
	MODEL 397		
4087	64MB Card	29	
4088	128MB Card	29	
4089	256MB Card	29	
	MODEL OCC		
0000	MODEL 260	00	
3028	4.5GB Ultra SCSI 16-bit Hot Swap	30	
3029 4342		30	

you need when you need it.

Custom QuickShip

Custom QuickShip, too.

Now you can get custom-configured RS/6000 systems and storage subsystems delivered right to your door in just 7 calendar days (excluding holidays). Custom QuickShip quickly configures and ships customized RS/6000 products according to your exact specifications. There are no configuration or shipping charges with Custom QuickShip, so call today for configuration, pricing and ordering information. Flexible IBM Global Financing is also available. We deliver your RS/6000 products the way you need them!

Products available for Custom QuickShip include:

Item No.	Product	Page
7043	43P Model 260	14
7043	43P Model 150	15
7043	43P Model 140	15
7025	Model F40	17
7025	Model F50	18
7133	Serial Disk System	35
3570	Magstar Tape Subsystem	38
3590	Magstar Tape Drive, Models B1A, B11	39

More about QuickShip:

- Saturday delivery is also available! Call 800 IBM-CALL for details
- Since 1995, over 55,000 orders have been placed via QuickShip in North America
- All QuickShip products come with a 30-day moneyback guarantee
- Flexible financing offers are available from IBM Global Financing

For more info about QuickShip, including product listings, call: 800 426-2255 or Visit QuickShip on the Internet at: www.ibm.com/Shop/quickship

RS/6000 QUICKSHIP PRODUCTS

Feat	ure Number/Description	Page
	MODELS C10/20	
4011	16MB SIMM	29
4012	32MB SIMM	29
	MODELS E30/F30	
4132	32MB DIMM	29
4164	64MB DIMM	29
	MODELS 39H, 59H, 590	
4069	64MB Card	29
4090	126MB Card	29
4095	256MB Card	29
	MODEL 591/595	
4078	128MB Card	29
4079	256MB Card	29
	MODEL 397	
4087	64MB Card	29
4088	128MB Card	29
4089	256MB Card	29
	STORAGE	
6219	SSA RAID EL (MCA), 2-way RAID 5- OR 8-way NON-RAID, 1-way only with SSA Fast Write Cache Module	35
6222	4MB Non-Volatile SSA Fast Write Cache Module for use with 6215 and 6219	35

reatt	rage	
6225*	Advanced Serial RAID adapter PCI, 2-way RAID 5- or 8-way NON-RAID, 1-way only RAID 0, 1-way only with SSA Fast Write Cache Module,	
	Supports loop speed of 160MB/s	35
7133-D	40 Rack-Mount Drawer up to 291.2GB	35
7133-T	40 Deskside Tower up to 291.2GB	35

	PERIPHERALS				
2994	IBM 10/100Mbps Ethernet MC Adapter	44			
2968	10/100Mbps Ethernet PCI Adapter	44			
2985	Ethernet BNC/RJ-45 PCI Adapter	44			
2987	Ethernet AUI/RJ-45 PCI Adapter	44			
2920	Auto Token-Ring LANStreamer PCI Adapter	44			
2741	SysKonnect SK-NET FDDI-LP	44			
2742	SysKonnect SK-NET FDDI-UP DAS PCI Fiber	44			
2743	SysKonnect SK-NET FDDI-UP SAS PCI UTP	44			
2724	FDDI-Fiber Single-Ring Adapter (MC)	44			
2723	FDDI-Fiber Dual-Ring Upgrade Kit (MC)	44			
2972	Auto Token-Ring LANStreamer MC 32 Adapter	44			
2993	Ethernet BNC MC Adapter	44			
2992	Ethernet/FDX 10Mbps TP/AUI MC Adapter	44			
2930	8-Port Async Adapter - EIA 232 (MC)	45			
2944	128-Port Async Controller - PCI BUS	45			
8128	128-Port Async Controller (MC)	45			

Feat	ure Number/Description	Page
8137	Enhanced Remote Async Node 16-Port EIA-232	45
8138	Enhanced Remote Async Node 16-Port RS-422	45
8131	128-Port Async Controller Cable, Ig. 4.57	45
8132	128-Port Async Controller Cable, lg. 0.23	45
8135	64-Port to 128-Port Pin-out Converter	45
2700	4-Port Multiprotocol Communications Controller (MC)	45
2708	Eicon ISDN DIVA PCI Adapter	45
2943	8-Port Async Controller (MC)	45
2962	2-Port Multiprotocol PCI Adapter	45
2951	2-Port V.24/EIA-232	45
2952	2-Port V.35	45
2953	2-Port V.36/EIA-449	45
2954	2-Port X.21	45
2947	ARTIC 960 Hx 4-Port Selectable PCI Adapter	46
2755	Block Multiplexer Channel Adapter (MC)	47
2756	System/390 ESCON Control Unit Adapter (MC)	47
4224	Ethernet 10BaseT Transceiver	47
2989	TURBOWAYS 155 ATM Adapter (155Mbps) (MC)	47
2998	TURBOWAYS 25 ATM PCI Adapter	47
2988	TURBOWAYS 155 ATM PCI MMF Adapter	47
2963	TURBOWAYS 155 ATM PCI UTP Adapter	47
2936	Async Cable Đ EIA-232/V.24	47
2945	Terminal Cable - EIA-422A	47

it www.ibm.com/Shop call 800 426 2255 today

The new standard in ASCII displays

IBM InfoWindow* II 3153 ASCII/ANSI Display Station

Fax Document 5704









- Supports 24, 25, 28, 42, 43 and 50 rows in 80 or 132 columns
- Top-bottom split screen capability lets users view two applications simultaneously
- Eleven popular emulations, including IBM 3151, WYSE, 50/60 and DEC VT320/VT220/VT100.

The perfect displays for jobs that don't require the computing power - and expense - of a PC.

These terminals come with main and auxiliary communication ports and can be ordered with RS232 or RS422 main port

A versatile 14" (11" viewable image size) display station with your choice of green, amber or white monochrome.

Visit our Web site at: www.pc.ibm.com/support use 'QuickPath' option with Machine Type = 3153

IBM InfoWindow II 3153 ASCII/ANSI Display Station

	Product No.	Description	Price
▶	3153BG3FC9231	14" green (RS232 Main Port) 102-key ASCII Keyboard	\$577
>	3153BA3FC9231	14" amber (RS232 Main Port) 102-key ASCII Keyboard	\$577
>	3153BG3FC9131	14" green (RS232 Main Port) 102-key PC Keyboard	\$577
>	3153BA3FC9131	14" amber (RS232 Main Port) 102-key PC Keyboard	\$577
>	3153CG3FC9231	14" green (RS422 Main Port) 102-key ASCII Keyboard	\$577
>	3153CG3FC9131	14" green (RS422 Main Port) 102-key PC Keyboard	\$577

FCC Class A (Defined on page 4)

▶ 24 Hour QuickShip

The best just got better...IBM's high-performance monitors go perfectly flat

P Series Monitors P76/P260





- New Help Menu makes it even easier for users to find information and make necessary adjustments
- With enhanced horizontal scan rates and higher addressabilities
- Possibility of glare greatly reduced.

Now you will experience even more spectacular images from IBM's new P Series monitors with the introduction of new models incorporating leading-edge FD Trinitron aperture grille tubes. With the virtually flat screen surface of FD Trinitron, straight lines appear straighter and images appear "truer to life" due to the elimination of distortion associated with screen curvature. RS/6000 professionals can now get the superior performance they require on the new P76 and

The IBM P92 monitor is still available with the time-proven Trinitron aperture grille display technology.

	P76	P260
CRT Size/Type	17-inch/FD Trin	21-inch/FD Trin
Viewable Image Size	16.0"	19.8"
Stripe Pitch (on center)	0.24mm	0.24mm
Horizontal Scan Rate	30-96kHz	30-121kHz
Top Flicker-Free VESA Mode	1600 x 1200 at 75Hz	1600 x 1200 @ 85Hz
Maximum Addressability	1600 x 1200 @ 75Hz	1920 x 1440 @ 75Hz
Colors available	Pearl White/ Stealth Black	Pearl White/ Stealth Black
Feature Code	3629/3627	3630/3628
Price	\$995	\$1,995




Software for the New Millennium

IBM is committed to providing Year 2000-ready IBM products (i.e., products that, when used in accordance with their associated documentation, correctly process, provide and/or receive date data within and between the 20th and 21st centuries).

The readiness, of course, is contingent upon all other products properly exchanging accurate date data with these IBM Year 2000-ready products.



At IBM, Year 2000-readiness begins with the operating system. And in the RS/6000° world, that means AIX°.



How do you do that? You could start by reading AIX,
UNIX® Operating System, and
the Year 2000 Issue Workbook – the
must-read resource for every AIX and
UNIX installation, available at:

http://www.software.ibm.com/year2000/papers/aixy2k.html

But to identify exactly which service updates you need right now to make your particular version of AIX Year 2000-ready, you can use one of two methods:

Download a special tool from:

ftp://ftp.software.ibm.com/aix/tools/y2k/

This tool runs on AIX V3.2.5, V4.2 and V4.3 systems, and determines if all necessary fixes have been applied that would put the host system at the latest known state of Year 2000-readiness. It identifies those fixes that have not been applied. Note that this tool is a binary executable that does not require root permissions, but may require you to manually set the file's "execute" mode bits, before you can run it.

Issue Islpp -I to output product ID information on AIX software installed using the Installp command. Then obtain the most up-to-date list of fixes for each product from AIX support personnel to identify those not yet installed. Issue Insfix -Ik FIX_ID to verify that the FIX_ID has been applied to your system.

To obtain needed service updates, just call Support Services at 800 237-5511 and the updates will be shipped to you at no charge, on the media of your choice, in 3 to 5 days. Or you can download the needed APARs directly from:

http://service.software.ibm.com/support/rs6000 (in the U.S.) or

http://aix.boulder.ibm.com/aix.ww/countries (outside the U.S.).

Complete information on all IBM products and services in relation to the Year 2000 issue can be obtained at:

http://www.ibm.com/IBM/year2000/

Another comprehensive resource guide, *The Year 2000 and 2-Digit Dates: A Guide for Planning and Implementation*, is also available from your IBM representative or from:

http://www.software.ibm.com/year2000/resource.html

Cornerstone for Project Monterey¹ – the future of UNIX

AIX V4

Fax Document 1668







- Robust scalability with concurrent operation of 32-bit and 64-bit applications
- Binary compatability with most existing AIX applications
- UNIX98 branded and Year 2000 ready, EuroReady and Tivoli Ready
- C2 and E3/F-C2 Security
- Bonus Pack of additional software offerings
- *Web-based systems manager and TaskGuides
- Fast Connect for Windows and OS/2 feature for high-speed PC file and Print
- Includes Java™ Technology.

AIX V4.3 runs across the entire range of RS/6000° systems, from workstations to supercomputers, providing the reliability, availability, performance and security required for e-business. It integrates key Internet technologies and includes enhancements to the operating system that provide increased capacity and the ability to handle unexpected peaks in demand.

The robust AIX V4 lets you create and manage large files and file systems, making it ideal for data warehouses and data marts. It includes the optional RS/6000 Welcome Center, your online introduction to the world of AIX. And with the Fast Connect feature you can easily bring the reliability and scalability of UNIX file and print servers to your Windows and OS/2 clients.

Max. Users Charge ^{††}	Applicable Models	
40	CXX, EXX, F30, F40, 140, 240, 150, 260, B50	
80	F3L, F50, HXX, GXX, JXX, RXX, 3XX, 5XX, S70, S70 Advanced Server, S80	
160	All 9076 Models	

^{††} A maximum user charge is assigned by model. No additional charge for users beyond this maximum; does not apply to networked users.

Product No.	Feature	Description	ОТС
5765-C34		AIX V4 (2 users)†*	500 E
		Cost per each additional user ^{††}	\$125
	4101	Fast Connect for Windows	\$1,495
	4102	Fast Connect for OS/2	\$1,795

V4 release upgrades for AIX are \$450 with each additional user at \$45.

- ¹ Included as part of the RS/6000 base system price. Select either, V4.2 or V4.3.

 ¹¹ A maximum user charge is assigned by model. No additional charge for users beyond this maximum; does not apply to networked users.
- * AIX Bonus Pack Contents are subject to change and may vary by country due to import/export requirements.

Appropriate media charges apply and shipments of AIX, AIX Fast Connect and Bonus Pack are initiated through SPO 5692-AIX.

¹Project Monterey, a major UNIX operating system initiative led by IBM. For more information refer to **www.ibm.com/servers/monterey**.

Bonus Pack software offerings

AIX Bonus Pack

AIX Bonus Pack - your fast path to the 'net

Our enhanced AIX Bonus Pack, included with AIX Version 4.3 at no additional charge when media is selected, is loaded with more Internet tools than ever! See:

www.ibm.com/servers/aix/products/aixos/bonus/

- Netscape® Communicator™ 4.51
- Novell Network Services 4.1 for AIX, V2.2.1 Eval, SW
- Syntax TotalNET Advanced Server V5.3, Eval. SW
- IBM Ultimedia Services V 2.2.1.5 for AIX
- DB2 ° Universal Database ™ V6.1 for AIX, Eval. SW
- Oracle8i Server Trial Software
- Geodesic Systems [™] Great Circle [™] 3.1.2 Try and Buy
- The Kernel Group ZeroFault ™Dynamic
- Chili!Soft ASP™ V3.0 Developer's Ed.
- IBM AIX Fast Connect V2.1.1, Eval. SW
- Graphon GO-Joe™ V2.2.0.0
- SCO Tarantella® V1.4.0.0 Eval. SW
- IBM Web Sphere™ Application Server V2.0.1 Std. Ed.
- IBM HTTP Server V1.3.3
- Encryption & security support for AIX V4.3.3
- IBM VisualAge for Java Entry Ed. V2.0.0.3
- Tivoli® Management Agent V3.2

^{*} AIX Workload Manager included

A single, enterprise-wide administration point

Software Subscription for AIX



Provides price protection and the convenience of a single, enterprise-wide administration point



- Available to all U.S. RS/6000 customers without any minimum order requirements
- Annual billing with automatic renewal.

RS/6000 customers in the U.S. can now use the Web to sign up for notification of new AIX releases. Once notified, they can order delivery of the new releases over the Web. Combined annual billing with automatic contract renewal, Software Subscription for AIX simplifies software maintenance administration and expense management.

Software Subscription replaces the existing two-year Upgrade Protection program. The new subscription entitles the agreed-to quantity of products for the enterprise, allowing expenses to be administered as a group. New products can be added at the annual rate as they are acquired so the single point of administration can be maintained.

Notification of Upgrade availability and ordering:

You can register to be notified by e-mail when products have chargeable upgrades. To register visit: http://


www.rs6000.ibm.com/support then choose Tech support OnLine, Subscriptions.


Product No.

Price is determined by the products and product options selected. Please call for specific

A new feature of base AIX 4.3.3!

AIX Workload Management





- Control options include minimum and maximum percentage limits, shares or a combination of both
- Helps ensure that critical applications are not impacted by less important jobs in the system during peak demands
- Aids in server consolidation.

AIX Workload Manager (WLM), a feature of base AIX 4.3.3, provides a policy-based method for managing RS/6000 system workloads and resources.

WLM delivers automated resource administration for multiple applications running on a single server. This capability helps to ensure that critical customer applications are not impacted by the resource requirements of less critical jobs in the system. This feature will allow organizations to take advantage of server consolidation, and reap the cost and management benefits associated with centralized systems

The policy-based architecture of Workload Manager allows systems administrators to spend less time on routine, workload management tasks by automatically applying individually tailored resource allocation profiles.

Workload Manager's robust array of functions is just one important example of the quick benefits and payback from upgrading to AIX 4.3.3!



Certified C2 level security for your RS/6000

Certified C2 for AIX V4.3.1

- Operational subset of AIX Version 4.3.1, C2 certified under TCSEC TTAP criteria and offered as PRPQ
- Provides a mechanism for Discretionary Access Control (DAC) on a TCP/IP port
- Provides pre-configuration to eliminate system services that are not included in TCB
- Provides US seal of certification requiring strong implementation of user authentication, user authorization and process auditing
- **43P/F50/S70** configuration certified; operational on all RS/6000 hardware models including SPs
- Normal Service and Support available without a certified RAMP process
- PTFs required for EuroReady
- This PRPQ has a prerequisite that the customer must have a valid AIX V4 license separate from the PRPQ.

A system that has been rated C2 enforces a discretionary access control policy to help protect information. It allows users to share information under their daily control only with other specified users.

AIX Version 4.3 releases have C2 security built into the product, however, this PRPQ is an operational subset of AIX V4.3.1, which has been evaluated for the conformance to government standards according to United States Trusted Computer Security Evaluation Criteria (TCSEC) for C2 level of functionality. This is the first 64-bit UNIX system to be certified under the new TCSEC TTAP Criteria.

PRPQ is available on CDROM, including full documentation on HTMI

Product No.	Description	Price
5799-GFG	Certified C2 for AIX V4.3.1	\$995.00

Powerful B1-designed security functions for your mission-critical data

Bull B1/EST-X V2.0.2 for AIX V4.3.2

- Supplements AIX® 4.3.2 and is designed to provide B1-level features as defined by the **Department of Defense 5200.28.STD**
- Mandatory Access Control (MAC) enforced by the system
- Privileges that are managed via administrative commands
- Multilevel directories that control access to designated levels
- Password management, allowing the system administrator to select encryption procedures
- Additional Audit Events, providing systems administrators more control over unauthorized
- B1 system boot is fully integrated into the system boot process
- Runs on all RS/6000® configurations supported by AIX V4.3.2 except for SP
- Groupe Bull product offered and serviced by
- Supports 32-bit application environments.

Now you can give your financial, government and other mission-critical applications the protection required to provide for the integrity of your all-important corporate data. The new B1/EST-X V2.0.2 is designed to supplement the AIX V4.3.2 base to provide a B1 level of security functionality as defined in the Department of Defense 5200.28.STD†.

With access management, you can limit the number of times users log onto the system. Terminal inactivity checking automatically disconnects workstations at user-specified times. And with multilevel directories files can be hidden from users who do not have the appropriate access clearance.

Product No. Description		ОТС
5799-GFH 4001 Bull B1/EST-X security Group D		\$8,500
5799-GFH 4002	Bull B1/EST-X security Group E	\$11,275
5799-GFH 4003 Bull B1/EST-X security Group F		\$19,275
5799-GFH 4004 Bull B1/EST-X security Group G		\$28,200

Note: Requires installation on a newly installed copy of AIX V4.3.2


† This product is not B1 certified

Full-featured and multithreaded APIs

APIs for Complex 3D Graphics

Fax Document 1949





Softgraphics is an advanced graphics feature of AIX V4

PHIGS for AIX V4.3 OpenGL and GL 3.2 for AIX V4.3

AIX V4.3 enhancements now include PHIGS and OpenGL[†] runtime and development environments in the base operating system. The PEX API is no longer supported. Both PHIGS and OpenGL APIs for the PowerPC 604e platforms are SMP multithreaded enabled. In addition to the previous models and adapters supported on AIX V4.2, the RS/6000 Model F50 with the GXT800P, the GXT3000P on Models 150 and 260, and the newly announced GXT2000P in models 140, 150 and 260 are also supported.

PEX and PHIGS for AIX V4.2.1 OpenGL and GL 3.2 for AIX V4.2.1

These powerful software tools are supported on most IBM 2D and 3D graphics adapters either through software or hardware acceleration. Our PHIGS products offer the graPHIGS API and PHIGS language bindings based on the ISO/ANSI PHIGS standard. They feature independent lighting and shading controls, advanced primitives, extended rendering attributes and more.

The OpenGL and GL 3.2 for AIX provide real-time 3D rendering capabilities with OpenGL 1.1 compatibility. A rendering library, utility toolkit, X11 Window System integration suite, networking protocol and OpenGL widgets are included. GL 3.2 supports a full-featured 3D rendering interface as well as windowing interfaces.

Graphics support for PowerPC 604e platforms

Version 4.2.1 enhancements (both products) include full 3D graphics acceleration for the PowerPC 604e-based 43P Series Models 140, 150, 260 and Model F40 Server and the Notebook 860.

- Supports entry 3D PCI adapters POWER GXT250P/255P
- Supports Model F50 with GXT800P
- Supports midrange 3D PCI adapters POWER GXT550P, GXT800P, GXT2000P and GXT3000P
- Supports integrated (internal) 3D GXT1000 feature on F40
- OpenGL requires a GXT550P, GXT800P, GXT2000P or the GXT3000P.

	Software Prerequisite:	AIX V4.21
--	------------------------	-----------

Product No.	Description	ОТС
5765-660	PEX and PHIGS for AIX V4.2.1	\$695
5765-659	OpenGL and GL 3.2 for AIX V4.2.1	\$695
5765-C34	OpenGL and PHIGS for AIX V4.3 ^{tt}	N/C

[†] OpenGL is a registered trademark of Silicon Graphics Inc.

3D graphics with 2D hardware

Softgraphics

- Supports all RS/6000s. Scales with CPU so graphics performance increases without modification when moving to a faster system
- Supports multiple 3D APIs on a single workstation to help reduce purchase and training costs
- Ideal for applications development and distribution 3D applications can be developed on low-cost 2D platforms, then distributed to both 2D and 3D systems in the field!

IBM's breakthrough Softgraphics 3D capability is available for OpenGL, PHIGS and PEX for AIX Version 4.2 and Version 4.1.5. It is available for OpenGL and PHIGS for AIX V4.3. As the cornerstone of IBM's 3D API strategy, Softgraphics provides a full software implementation of OpenGL 1.1, PEXIIb 5.1 and graPHIGS 3D APIs so you can perform full-function 3D graphics while utilizing many of IBM's low-cost 2D graphics adapters!

¹¹ OpenGL and PHIGs included with AIX V4.3 at no additional charge

Enabling e-business for competitive advantage

IBM Suites for AIX

		IBM Enterprise Suite
	IBM Business	TXSeries
	Integration Suite	MQSeries
IBM Suite	MQSeries	DB2 Connect
WebSphere Appl Server	WebSphere Appl Server	WebSphere Appl Server
Communications Server	Communications Server	Communications Server
Systems Management	Systems Management	Systems Management
DB2 UDB	DB2 UDB	DB2 UDB
ADSM	ADSM	ADSM
Domino	Domino	Domino
Install Wrapper	Install Wrapper	Install Wrapper

IBM Suites for e-business for Windows NT, IBM AIX and Sun Solaris.

ADSM is optional for Suites for AIX and Solaris.

- IBM Suites for AIX makes it easy for companies to build, deploy and manage e-business applications
- Key components of award winning software such as Domino Server, DB2 Universal Database, WebSphere Application Server, MQSeries and TXSeries are integrated into IBM Suites for AIX°
- Flexible licensing allows you to install components across multiple servers, decreasing overall costs and allowing you to use all of the components
- Upgrading is simplified, whether from a single IBM product or from one suite level to the next
- Easy installation with a choice of express and custom options.

IBM Suites for e-business combines all the essential e-business application servers – Lotus Domino, WebSphere, DB2 Universal Database and MQSeries – into an integrated package that includes software for host integration and local systems management, plus an integrated installation tool.

What's in Suites for e-business?

E-mail and collaboration

The Domino Server is an integrated messaging and Web application software platform for growing companies that need to improve customer responsiveness and streamline business processes. As the only solution built on an open, unified architecture, Domino delivers secure communication, collaboration and business applications.

Transactional Web application Servers

These servers enable your company to conduct a wide range of business, from simple Web publishing to enterprise-scale, round-the-clock, online transaction processing.

TXSeries allows developers to build secure, reliable transaction systems

Data Management

DB2 Universal Database is one of the truly scalable, multimedia databases ready for e-business. This award-winning database offers 34-203% more power and 39-109% more throughput than competitive offerings.

Connectivity Services

MQSeries is a messaging and information backbone that enables organizations to transact complex business processes across 35 operating systems, more than any other messaging software on the market.

IBM eNetwork Communications Server smoothly integrates your host systems with the rest of your network and e-business applications.

Systems Management

EnlightenDSM™, a full-featured suite of workgroup systems administration and event monitoring capabilities that offer cross-platform functionality for UNIX and Microsoft Windows clients.

Visit our Web site at: www.ibm.com/software/xplatformsuites

Product No.	Feature	Description 280 VOID	Price
5697-E91	1001	IBM Suite for AIX Version 1.5 ^{1 2}	\$2,499
5697-E91	1002	IBM Suite for AIX Version 1.5 Client	\$225
5697-E97	0001	IBM Business Integration Suite for AIX Version 1.5 ^{1 2}	\$6,499
5697-E97	0002	IBM Business Integration Suite for AIX Version 1.5 Client	\$225
5697-E90	2001	IBM Enterprise Suite for AIX Version 1.5 ^{1 3}	\$18,249
5697-E90	2002	IBM Enterprise Suite for AIX Version 1.5 Client	\$375

¹ Requires registered user


² Authorized to run on RS/6000 Models 43P, F40 and F50 with up to 4 processors.

Authorized to run on any RS/6000 machine up to 4 processors

Powering the world's e-business solutions

DB2 Universal Database





- Provides unparalleled power and performance
- Offers wide-ranging accessibility and high availability
- Supports large data objects including text, audio, video, images and spatial
- Enables you to deploy e-business applications rapidly and cost effectively
- Works with IBM business intelligence solutions to help you exploit valuable business data
- Features tools that make data management easy.

As the foundation for e-business, DB2° Universal Database™ is the industry's first multimedia, Web-ready relational database management system, strong enough to meet the demands of large corporations and flexible enough to serve medium-sized and small businesses. DB2 Universal Database combines power for business intelligence (data warehousing and data mining) with industry-leading performance and reliability to drive the most demanding industry solutions. Industry-leading application vendors like SAP, PeopleSoft and Siebel Systems support DB2 in a wide variety of applications from ERP to Supply Chain Management to Customer Relationship Management. According to Dataguest Inc., a unit of Gartner Group, Inc., IBM° is the market share leader in the world-wide database industry with more than one million DB2 server licenses and 40 million users.

Cluster Proven

High performance parallel relational databases are provided whether you plan to implement AIX desktops, SMP, MPP, or clusters of SMPs with DB2 Universal Database Enterprise Edition and Enterprise Extended Edition. DB2 exploits AIX High Availability Cluster Multiprocessing (HACMP) feature offering customers wide-ranging accessibility and high availability. In addition, the optimizer in DB2 selects the lowest-cost path for execution making almost any query run faster, so you can generate results sooner and reach business conclusions way ahead of the competition.

Easy to Use

To make data management easy, the DB2 Control Center, is designed to manage all of the DB2 servers in your enterprise. Running as a Web browser or as native Java application, the Control Center offers an intuitive interface for accessing and manipulating any database object, a job scheduler, a performance monitors, and index SmartGuide along other management tools. DB2 is also integrated with Tivoli to provide Tivoli customers with the means to automatically discover, inventory and monitor DB2 resources enterprise wide.

Also available:

DB2 Connect provides your applications transparent access to data stored on any DRDA compliant database.

DB2 Universal Developer's Edition gives you a comprehensive suite of tools that help you build DB2 Universal Database applications.

DB2 Data Links Manager provides security and recoverability for external data by allowing files external to DB2 to be referenced and controlled by DB2.

DB2 Query Patroller provides query and resource management and tracking for decision-support systems.

DB2 Universal Database Enterprise Edition is part of the AIX Bonus Pack and is also a key component of the IBM Suites for AIX.

Hardware Prerequisites:	RS/6000 with CD-ROM
Software Prerequisites:	AIX Version 4.2 or later

For prerequisites on the full family of DB2 products, call 800-426-2265. All products are supplied on CD-ROM.

Product No.	Description	Platform	Foot-notes	ОТС
41L1685	DB2 UDB Enterprise Edition V6.1	OS/2, Windows NT, AIX, Sun, HP-UX, Linux	1	\$12,550
41L1714	DB2 UDB Enterprise - Extended Edition for AIX V6.1	AIX	1	\$20,050
41L3059	DB2 Connect Unlimited Edition V6.1	OS/2, Windows NT, AIX, Sun, HP-UX, Linux		\$5,050
41L1730	DB2 Connect Enterprise Edition V6.1	OS/2, Windows NT, AIX, Sun, HP-UX, Linux		\$2,500
41L1094	DB2 Universal Developer's Edition V6.1	OS/2, Windows, Windows NT, AIX, Sun, HP-UX, Linux	2	\$999
41L1704	DB2 Data Links Manager V6.1 for AIX	AIX		\$8,050
41L1699	DB2 Query Patroller V6.1	AIX, SUN		\$5,050

¹ Additional charges apply for servers having a greater number of processors.

² Universal Developer's Edition is licensed for installation and use by individual user only for the purpose of evaluating, demonstrating, testing and developing application programs.

A high performance, scalable, cluster file system for the RS/6000 SP

General Parallel File System, V1.2

- Follows with UNIX file standards, with minor exceptions
- Increases I/O performance and scales with the
- Optimizes RS/6000 SP Switch and disk utilization with support of multiple file block sizes
- Runs most AIX applications unmodified
- Provides greater data availability with logging, replication and component failover support
- Spans multiple SP nodes and disks and allows access to SP files from any GPFS node in the system
- Simplifies multinode file system administration.

If you've been looking for a truly scalable cluster file system for your SP system - one that follows most UNIX file standards and delivers superior performance across multiple file system nodes, with outstanding recoverability - here it is. IBM's General Parallel File System V1.2 (GPFS) can deliver greater file performance than existing NFS, DFS and PIOFS file systems on the SP. Plus, it provides the all-important scalability needed as you grow your SP system with additional processors and disks, while maintaining the application interfaces used in standard UNIX file systems.

GPFS can also survive most system and I/O failures. On an appropriately configured system it is capable of automatically recovering from node, disk and disk adapter failures and allows for continued operations in the event of failed disk connections.

Hardware Prerequisites:	RS/6000 SP with a minimum of 3 nodes running GPFS
Software Prerequisites:	AIX V4.3.2 or later modification levels. Parallel System Support Programs for AIX V3.1 or later (5765-D51). The IBM Virtual Shared Disk image of PSSP must be installed prior to the installation of Recoverable Virtual Shared Disk.

Feature	Product No.	Description	отс
4000	5765-B95	BOTC Program Pkg. – GPFS	\$10,000
4001		1-User Pack – GPFS	\$2,500
4002		5-User Pack - GPFS	\$10,000
4003		10-User Pack – GPFS	\$17,500
4004		50-User Pack – GPFS	\$40,000
1001		V1.2 Program Package (Incl 1 User)	\$10,000
1002		V1.2, 1-User Pack	\$2,500
1003		V1.2, 5-User Pack	\$10,000
1004		V1.2, 10-User Pack	\$17,500
1005		V1.2, 50-User Pack	\$40,000
1006		UPG V1.1 to V1.2 Program Package (Incl. 1 User)	N/C
1007		UPG V1.1 to V1.2, 1-User Pack	N/C

System management for RS/6000 SP & SP-attached S80 & S70 Advanced

Parallel Systems Support Programs for AIX V3.1

- Permits SP nodes and externally attached servers to be managed from a single point of control
- Exploits industry-leading cluster technology and provides numerous ease-of-use enhancements
- Support for all SP nodes, including 332 MHz and **POWER3 SMP nodes**
- Runs on AIX V4.3.2 and later
- Support for the attachment of \$80 and \$70 Advanced as SP-attached servers
- Supports PCI I/O adapters and SP Switch MX adapter
- Coexists with previous PSSP V2 releases and multiple AIX levels for easier migration.

PSSP is a collection of administrative and operational software applications - built on AIX system management tools and commands - that enable system administrators and operators to more easily manage SP system installation, configuration, device management, security, error logging and resource accounting.

With IBM's Parallel System Support Programs for AIX (PSSP), you can attach S80 and S70 Advanced RS/6000 Enterprise Servers to dramatically increase the SP's database capabilities. The PSSP V3.1 repackages previous PSSP features such as PTPE and HACWS into the base product. RVSD, previously a separate product, has been merged within VSD function in PSSP. V3.1 continues to enhance SP usability and diagnostic capabilities.

Hardware Prerequisites:	RS/6000 SP, including one control workstation.
Software Prerequisites for PSSP V3.1:	RS/6000 SP system control workstation AIX 4.3.2 or later.

Feature	Product No.	Description	OTC
2000	5765-529	UPG Nodes 4 V1.2-V2.2	\$750
2001	5765-529	UPG Nodes 16 V1.2-V2.2	\$11,250
2002	5765-529	UPG Nodes 32 V1.2-V2.2	\$22,500
2003	5765-529	UPG Nodes 64 V1.2-V2.2	\$33,750
2004		UPG Nodes 128 V1.2-V2.2	\$45,000
3000	5765-529	UPG Nodes 4 V2.1-V2.2	\$500
3001		UPG Nodes 16 V2.1-V2.2	\$7,500
3002	5765-529	UPG Nodes 32 V2.1-V2.2	\$15,000
3003	5765-529	UPG Nodes 64 V2.1-V2.2	\$22,500
3004	5765-529	UPG Nodes 128 V2.1-V2.2	\$30,000
4001	5765-D51	PSSP V3.1 (Incl. in Hardware)	N/C
4002	5765-D51	PSSP for Ext. Att. Server	\$15,000
4003	5765-D51	UPG from 5765-529 (V.2.2) - Per Node	\$2,250

Monitor, analyze and fine-tune your workstation performance

Performance Toolbox for AIX V2.2

- Monitors AIX systems for optimal local or client/ server performance
- Tunes parameters to balance the utilization of your fixed system resources
- Diagnoses and debugs performance problems
- For AIX Version 4.2 or AIX Version 4.3.

With a wide range of customizable performance management tools available in Performance Toolbox, it's easier to optimize the utilization of your workstation resources.

The enhanced Motif-based V2.2 includes support for either a stand-alone system (entry-level Local version) or multiple networked systems (Network version), orderable as separate features. Moving from Local to Network operation is a smooth transition.

Performance Aide, the client (agent) component, is shipped as an integrated feature of Performance Toolbox. It can perform local data filtering and alert processing as well as provide data to an SNMP agent.

Hardware and Software Requirements:	Call 800 426-2255 for specific requirements.	
-------------------------------------	--	--

Feature	Product No.	Description	отс
4001	5765-654	Performance Toolbox – Network	\$4,545
4002		Performance Toolbox – Local	\$850
4003		Performance Aide ¹ Qty. 1	\$450
4004		Performance Aide ¹ Qty. 5	\$2,000
4005		Performance Aide ¹ Qty. 10	\$3,500
4007		Performance Aide ¹ Qty. 50	\$14,500

¹ Client agent

Award-winning TP monitors for your transaction applications

TXSeries V4.2 for AIX

- Connect to a wide range of client machine environments
- Integrate TXSeries with other applications and middleware by deploying MQSeries applications
- Web-enable your TXSeries-based applications
- Connect to Lotus Notes applications
- Create complete e-business applications using the Domino Go Webserver.

IBM TXSeries V4.2 brings together and extends the functionality of the Transaction Server, CICS and Encina products. TXSeries provides a cohesive infrastructure to develop, manage and deploy high-performance, distributed transactional client/server applications. It supports multiple programming models, optional Web enablement and connectivity to a range of host-based and distributed systems.

The two TP monitors, Encina and CICS, are award-winning technology solutions. Encina received Network Computing Magazine's 1997 Well-Connected Award as a model of the next generation TP monitor; the CICS Transaction Monitor received Honorable Mention.

Whether your primary interest is leveraging previous investments in CICS programs or to develop new, highperformance enterprise-level applications using the latest development tools, TXSeries offers incomparable security, host connectivity, scalability and robustness.

Hardware Prerequisites:	Any RS/6000 hardware capable of running AIX V4.2 with the required memory and disk space for a given configuration. Call for more information on requirements.
Software Prerequisites:	AIX Operating System (32-bit) V4.2.1 or V4.3

Product No.	Description		отс
04L3036	TXSeries for AIX V4.2 Program Package	From	\$3,275
04L3032	TXSeries for AIX V4.2 (DES) Program Package	From	\$3,275

A scalable, digital printing management solution

IBM Infoprint Manager V3.1



- Secure, scalable enterprise printing support
- Reliability for mission-critical applications like SAP/R3
- Facility to include printing in Tivoli system management solution
- Ability to manage and print to printers, fax machines and more
- Support for wide range of printers (up to 1,000+ pages per minute)
- Server-based Adobe PostScript RIP with Level 3 **PostScript support**
- Support for IPDS, AFPDS, PostScript, PCL, PDF, GIF, JPEG, TIFF and other file types
- Set of Windows and Macintosh applications to receive print files in commonly used formats and assemble, archive or submit jobs for just-in-time printing.

IBM Infoprint Manager V3.1 is a comprehensive software solution that you can use to manage your entire digital printing facility. Infoprint Manager delivers productionvolume, single-copy integrity with PostScript quality - while simplifying the print process and helping to cut operating costs.

Infoprint manager combines award-winning print management technology with enhanced file management and spooling capabilities to address a wide variety of printing needs. Whether you must manage digital printing across your enterprise, workgroup, or commercial printing facility, it can provide a complete, easy-to-use print management solution. Its reliable queue and job management, comprehensive PSF* print and job control facilities, and server-based Adobe PostScript RIP ensure that your documents are printed completely and accurately the first time.

Infoprint Manager also gives commercial printers the tools they need to grow their businesses and manage all of their digital print shop facilities and processes, from file submission to final print.

Hardware Prerequisites:	Any RS/6000 Power2* 666MHz or PowerPC 133MHz or better machine. 64MB memory, 2GB Disk Storage and CD-ROM. Call for more information.
Software Prerequisites:	AIX V4.2.1 or 4.3 with specific APARs. Call for more information.

Feature	Product No.	Description	отс
0001	5648-B34	Infoprint Manager V3.1	\$15,000
0002		Page Formatting Aid	\$2,500
0003		SAP Integration	\$5,000
0004		Kanji Package	\$5,000
0005		InfoPrint Library	\$30,000
0006		Adobe PostScript	\$30,000
0007		Scanner Client	\$250
0008-0017		46-100 IPM Attachment (10 Max.)	\$2,000
0018-0023		<46 IPM Attachment (in increments of 20 printers)	\$4,000
0028-0031		>101 IPM Attachment (4 Max.)	\$12,000
0036-0039		Fax Support, 2-5 lines (17 Max.)	\$6,000
0071		InfoprintPlus for Tivoli	\$5,000

Manage R/3 systems, applications and networks from NetView platform

Application Manager for SAP R/3

- Integrated, centralized control and management of R/3 systems, applications and client/server network from a single NetView*
- Integrated repository of key management information across entire client/server environment.

IBM's new Application Manager for SAP R/3* component is designed to help customers manage the complex, highly integrated R/3 client/server environment from SAP. When combined with NetView, this open environment enables centralized management of the network and R/3 applications using a Management Information Database (MIB) and SNMP.

Hardware Prerequisites:	RS/6000 workstations or servers running AIX V4.1 or later; keyboard, mouse and color display. May require a TCP/IP network communication adapter; NetView (3.1) for AIX or later. Call for agent requirements. Available on CD-ROM and tape media.	
Software Prerequisites:	AIX 3.2.5.1: IBM AIX V4.1 or later (5756-030); IBM Visual System Management (V5M); IBM AIXwindows* V1.2.3 (5605-257) or later with Xwindows System* V11.5 or later and Motif 1.2 or later, AIX 4.1.3: (5765-393).	


Feature	Product No.	Description	отс
0001	5799-FQY	Base	\$12,000
0002		SNMP/Agent	\$12,000

Designed to improve productivity on IBM, HP & Sun

Distributed SMIT for AIX 2.2

Fax Document 4841





- Lets you execute system commands on RS/6000, Sun or HP platforms through a common user interface
- Provides ongoing security with single sign-on, administrator authentication, Message Authentication Code, Commercial Data Masking Facility and audit log of significant events
- Motif interface available
- Sun Solaris 2.3 Client.

Bring AIX power to your distributed environment and manage clusters of resources with increased flexibility. With DSMIT you can remotely execute AIX commands simultaneously or sequentially across multiple systems without logging on.

DSMIT's easy-to-use, menu-driven services include installation, configuration, device management, problem determination and more. Interactive menus/dialogs automatically build, execute and log commands without your learning command-level syntax.

Hardware Prerequisites:	Display and keyboard, Ethernet or Token-Ring adapter required: RS/6000 minimum; 16MB RAM, 500KB of fixed-disk storage for server, additional 1MB of fixed-disk storage for client. DSMIT client for AIX: Same as above with 50KB fixed-disk storage. Sun DSMIT client for SunOS: Sun SPARC** systems, 300KB of fixed-disk storage. HP DSMIT client for HP-UX: HP Series 700** system, 300KB of fixed-disk storage.
Software Prerequisites:	DSMIT for AIX: AIX V4.2 or later, compatible releases; TCP/IP, NFS** may be installed and configured to distribute the DSMIT database. DSMIT client for AIX: AIX V4.1 or later, compatible releases. Sun DSMIT client for SunOS: SunOS V4.1.3; TCP/IP HP DSMIT client for HP-UX: HP-UX V9.0; TCP/IP.

Product No.	Description	ОТС
5696-902	DSMIT for AIX V4	\$5,000
	DSMIT for DSMIT client (AIX/6000*† SunOS or HP-UX)	\$300


[†] License required per DSMIT client.

Run more jobs in less time with greater balance of your workstation resources

LoadLeveler V2.1

Fax Document 5865





LoadLeveler manages individual systems as a single computational.

- Scalable job management from the "supercomputing" RS/6000 SP System down to workstations on end-user desktops
- Administration from a single point of control
- Job requirements are easily specified and matched with available resources
- LoadLeveler's Central Manager can automatically recover on other designated machines with no loss of job information.

Control the scheduling and managing of your serial and parallel batch jobs. Manage individual systems as a single resource, dispatch jobs to various systems in the network seamlessly, and balance the workload for gains on productivity, cycle utilization and return on investment.

LoadLeveler V2.1 includes the Resource Manager function from PSSP, and supports multiple adapter windows along with Parallel Environment V2.4 multiple user space tasks per adapter function for parallel job exploitation of SMP nodes.

tentralized manual	RS/6000 with minimum 30MB free disk space available on at least one LoadLeveler node; 15-20MB disk space must be available for each node in a cluster (for local log and work files).
Software Prerequisites:	AIX V4.3.2 or later, compatible releases.


Feature	Product No.	Description	ОТС
0001	5765-D61	Program Package (Incl. 1 User)	\$2,200
0002	A SHIP OF SHIP WAS	1 User Pack	\$1,900
0003		5 User Pack	\$9,700
0004	A155-	10 User Pack	\$16,000
0005	any through 16M	50 User Pack	\$48,000
1001		UPG V1.3 to V2.1 Program Package (Incl. 1 User)	\$330
1002		UPG V1.3 to V2.1, 1-User Pack	\$285

Call for special educational discounts
Two-Month Unconditional Guarantee

Enhanced SNA and TCP/IP connectivity for your AIX users

SecureWay Communications Server for AIX V5.0

Fax Document 8985



- Integrated TN3270E Server with load balancing provides SNA 3270 application access to TCP/IP clients
- Includes Host On-Demand Entry which provides easy 3270 SNA application access from any Java-enabled Web browser
- Multiprotocol support provides flexible access to TCP/IP, network computing and SNA applications
- High Performance Routing (HPR) improves network performance and reliability, including rerouting sessions around network outages, without disrupting the user session
- Dependent LU Requester (DLUR) allows dependent LUs to take advantage of APPN networks, leveraging your investments in 3270 and other Dependent LU applications
- Easy-to-use Motif graphical user interface provides simplified configuration and management
- Channel attachment support now included in the base product.

IBM SecureWay Communications Server for AIX, a SecureWay Software offering, meets the challenge of today's changing business environment. It provides highly flexible SNA and TCP/IP interoperability for RS/6000 customers who need to build or connect to SNA networks, integrate TCP/IP with SNA, connect over WANs or LANs, connect to new Internet or intranet solutions and/or exploit the capabilities of Advanced Peer-to-Peer Networking* (APPN*). With SecureWay Communications Server for AIX V5.0, you choose applications based on your business needs, not on your network. It brings you true networking – interconnecting people and applications – even when platforms and network configurations are diverse.

Hardware Prerequisites:	RS/6000 or other AIX platform with 32MB memory, 32MB available hard disk minimum. Appropriate communication adapters, cables and device drivers: Token-Ring Adapter, Ethernet Adapter, SDLC Adapter, X.25 Adapter, FDDI Adapter, ATM Adapter, ESCON Channel Adapter and Block Multiplexer Channel Adapter.
Software Prerequisites:	AIX V4.1.5 or later (not compatible with AIX V3.2.X).


Product No.	Description	ОТС
04L0743	SecureWay Communications Server for AIX Program Package CD-ROM	\$995
4302129	1 registered user	\$69
4302130	5 registered users	\$328
4302131	10 registered users	\$642
4302132	50 registered users	\$3,174

A hot, new way to secure your e-business

SecureWay Firewall for AIX



Update



- Safeguards your intranet as you access the Internet
- All 3 standard firewall architectures built into one product
- Enhanced hardware-platform support including SMP on RS/6000.

The data in your company's intranet is one of your most valuable assets. Keep it from falling into the wrong hands with IBM SecureWay Firewall for AIX. This comprehensive network security system is positively the best you can buy. The IBM Corporation has been using SecureWay Firewall for the past 10 years to protect its data.

Three firewalls for the price of one

We put all three leading firewall architectures – Application Gateway Proxy, SOCKS Circuit-Level Gateway and Expert Filtering - into this one solution. No more depending on a single firewall architecture to satisfy your security requirements. The three architectures work together to provide you with optimum security, reliability and flexibility.

Innovative support features

- The first firewall to offer SOCKS V5 security protocol standard
- One of the first firewalls to provide a hardened operating system platform to help reduce configuration errors
- Virtual Private Network (VPN) capability
- Java-based GUI for easy administration.


Hardware Requirements:	RS/6000 POWERstation and POWERserver 64MB of memory, 100MB of disk space	18
Software Requirements:	V4.3.2	

Product No.

Please call for product number and pricing information

A complete boundary security solution

SecureWay Boundary Server





- **IBM eNetwork Firewall Version 3.3**
- Security Dynamic ACE/Server and SecurID tokens (2-user license and 2 tokens)
- Content Technologies MIMEsweeper: MAILsweeper, and WEBsweeper
- SurfinGate 4.03 from Finjan: SurfinGate Server; SurfinConsole; SurfinGate database.

Secure boundaries are needed everywhere – between your company's internal departments and between your company and the outside world.

This security not only protects your network, applications and information, but it extends their reach. Proper boundary security doesn't just mean controlling who accesses your network. It also means controlling the information entering or leaving your network.


IBM SecureWay Boundary Server brings together a complete boundary security solution. It provides firewall protection, virtual private networking (VPN) and content security. Managed by the SecureWay Policy Director, it provides centralized control of user authentication and access to Web objects, including HTML pages, graphics, applications written in Java and CGI and database queries. SecureWay Boundary Server brings together best-of-breed technology from the security industry into an integrated solution with IBM support and services standing behind it.

Product No.

Available only through IBM Passport Advantage Contract. Call for product numbers, pricing and contract information.

Link your RS/6000 to a System/370 or System/390 for fast, easy file sharing

3270 Host Connection Program for AIX



- Reliable RS/6000-to-host connectivity over a wide range of coax, LAN, WAN and channel networks
- Concurrent access to multiple hosts and multiple host sessions
- Support of 3278/79 display emulation using **ASCII terminals, graphical displays and Xstations**
- **3286/87 printer emulation on most printers** supported by AIX V4
- Friendly graphical interface allows fast start-up by an icon from AIX Windows Desktop Application Manager
- Functionality equivalent to HCON V1.3.2 for AIX V3.2.5
- Industry-standard HLLAPI (High Level Language **Application Programming Interface) support,** using C, FORTRAN and COBOL languages
- Provides extensive International Language Support for both single- and multi-byte character sets as well as support for Arabic and Hebrew languages, including multiple concurrent sessions in different national languages.

Do your RS/6000 users require 3270 emulation and host file transfer capabilities between AIX and your IBM host systems? This versatile program offers an implementation of IBM's popular HCON product running under AIX V4. By enabling a subset of IBM 327X functions on AIX V4, it allows your RS/6000 platform to connect to a System/370 or System/390 and appear to the host as an attached 3270 display terminal or printer.

	Hardware Prerequisites for AIX V4	Software Prerequisites for AIX V4
For SNA Node 2.1 (Low Entry Networking) for LU 1, 2 and 3 types:	4-port multiprotocol adapter, multiprotocol adapter/A, X.25 adapter, Token-Ring adapter or Ethernet adapter	Communications Server for AIX
For TCP/IP for display session using TELNET:	Token-Ring, Ethernet, FDDI, using the appropriate 3172 or 8232 controller, X.25 (using 37x5), BMCA or ESCON	AIX V4.1 or later
For other attachments:	DFT connection to 37x4 using 3270 connection adapter or 5088/6098 connection using Host Interface Adapter	AIX V4.1 or later

Product No.	Description	ОТС
5765-398	3270 HCON for AIX	\$1,195

Two-Month Unconditional Guarantee

Easy point-to-point connection between RS/6000 and IBM host

ESCON Channel Connectivity for AIX V1.1

- Offloads host system activities to RS/6000
- High-speed host system connectivity
- Supports Client Input Output/Sockets (CLIO/S) V2.1, a data transfer protocol utilizing the ESCON or Block Multiplexer channels in the TCP/IP environment for high-speed file and data transfers
- Supports Multiple Path Channel (MPC) over **ESCON** to provide even greater throughput.

These versatile products enable the RS/6000 to access an IBM host channel, providing a point-to-point connection between the RS/6000 and an IBM host. Either ESCON or Block Multiplexer channel environments are supported and each supports both SNA and TCP/IP environments.

Hardware Prerequisites:	ESCON Channel Adapter or Block Multiplexer Channel Adapter
Software Prerequisites:	For TCP/IP environments: AIX V4.1.2. or later

Feature	Product No.	Description	ОТС
4000	5765-603	ESCON Channel Connectivity for AIX	\$2,500
4000	5765-604	Block Multiplexer Channel Connectivity for AIX	\$2,500

Bring NDS to Internet/intranet PC clients and browsers

Novell Network Services V4.1 for AIX

- Distributed NDS database that provides global access to all network resources and a single point of administration for the enterprise
- Advanced network security to control access to network resources
- Novell's distributed file and print services for PC clients
- RS/6000 network interoperability with other NetWare, NT, UnixWare and HP/UX servers running NetWare V4 NDS
- Support for both NetWare-IP and IPX/SPX that extends full NDS functionality over TCP/IP networks
- Support for multiple network types, including Ethernet, Token-Ring and FDDI
- AIX Versions 4.2.1 and 4.3 support.

Now you can deliver the full complement of Novell Directory Services (NDS) to your Internet/intranet PC clients and browsers – and bring the power, reliability and scalability of the RS/6000 server family to your NDS network. The IETF Lightweight Directory Access Protocol (LDAP) – compliant Novell Network Services V4.1 for AIX running on RS/6000 servers consolidates PCs for NetWare 3 and 4 services, and extends the power of NDS from PC LANs to Internet and intranet environments.

NDS enables the RS/6000 to act as server for both Internet and PC client applications designed to run on DOS 5.0, OS/2 2.1, Windows 3.11, Windows 95, Windows NT 3.5 or later versions of these operating systems.

Hardware Prerequisites:	Server workstation with a minimum of 32MB of memory and 1GB of disk space. It is recommended that the server have 64MB of memory or 1GB of disk space.
Software Prerequisites:	AIX Version 4.2.1 or 4.3

Feature	Product No.	Description	отс
4001	5765-C95	Server	\$0
4003		5 Connects	\$1,095
4004		10 Connects	\$2,095
4005		25 Connects	\$3,695
4006		50 Connects	\$4,995
4007		100 Connects	\$6,995
4008		250 Connects	\$12,495
4009		500 Connects	\$24,995

RS/6000 news via email...at no charge

iSource Web site



Imagine... a no-charge, e-mail delivery service that keeps you up-to-date on all of the latest news and promotions on the IBM products and e-business solutions that interest you. It's here, and it's called iSource.

With iSource, you create your own customized subscription to any combination of the following types of information:

- Announcement Letters and Redbook Abstracts
- The "Focusing On You" News Digest
- Special Promotions
- Press Releases

Announcement Letters and the News Digest are e-mailed to you once a week. Promotions and Press Releases are sent as they become available.

Here's how to get started:

- Visit the iSource Web site at: http://www.ibm.com/iSource and select "Subscribe" from the toolbar, or
- Send an e-mail to: **info@iSource.ibm.com** with the word **SUBSCRIBE** in the body of your note (leave the subject line blank)

iSource is available at absolutely no cost to you. You can modify or cancel your subscription at any time.


visit

www.ibm.com/Shop

call 800 426 2255 today

The award-winning Java development program

IBM VisualAge for Java V2.0



- New HPC allows you to optimize code for specific server platforms (OS/2, Windows NT, AIX, OS/400* and OS/390)
- Additional Enterprise Access Builders provide Java applications connectivity to CICS, DB2, SAP R/3, RMI and JDBC-enabled relational databases
- Automated object-to-relational mapping
- Integration with SanFrancisco Application Business Components, Tivoli, eSuite and Component Broker
- Enhanced remote debugging tool permits you to test and debug multi-tier, multi-language applications across heterogeneous server platforms
- Support for JDK 1.1.6
- Data Access JavaBeans enables Java applications to access JDBC-enabled relational databases
- Increased support for AS/400 and System/390 Java application development
- New support for AIX 4.2 and 4.3 workstations as a development platform
- New Open Tool Integrator APIs
- Integrated, Java team-programming support including integration with VisualAge TeamConnection*, ClearCase and PVCS.



You need to build the best Java applications, applets, servlets, and JavaBean components possible. So use the very best Java programming environment on the market today to do it: IBM VisualAge for Java V2.0. This new version of IBM's award-winning VisualAge for Java gives you a complete solution for developing scalable e-business applications, managing component-based development for large project teams, and extending existing enterprise applications to the Web – without rewriting them. The solution includes a new High Performance Compiler (HPC), connections to more enterprise systems, team programming support and exploitation of the very latest Java technology.

V2.0 is immediately available in three editions, an Entry Edition, Professional Edition and Enterprise Edition. And to help you make the most of V2.0, our VisualAge Developer Domain Subscription for Java offers you a single access point for everything you need to build mission-critical Java applications – including Java-related samples, education, support, and the opportunity to network with a community of Java professionals.

Visit our Web sites at: www.ibm.com/software/ad and www.ibm.com/software/vadd

Product No.	Description	ОТС
31L1786	VisualAge for Java, Professional Edition for OS/2 and Windows V2.0	\$99
31L1885	VisualAge for Java, Enterprise Edition for OS/2 and Windows V2.0	\$2,999
31L1953	VisualAge for Java, Enterprise Edition for AIX V2.0	\$2,999
31L1797	VisualAge for Java, Professional Edition V2.0 Competitive Upgrade	\$29

Improved programmer productivity and enhanced portability

VisualAge C++ Professional for AIX V4



VisualAge C++ Professional for AIX V4

- Robust visual RAD environment that includes Visual Builder and Data Access Builder
- Fully incremental development facilities with incremental, compilers and linker
- Rich set of IBM Open Class† Libraries that includes over 500 portable classes with over 5,000 methods.

If you need a powerful rapid application development (RAD) tool for your heterogeneous environment, you couldn't do better than VisualAge C++ Professional for AIX V4 product. It provides standards-compliant, 64-bit enabled IBM C and C++ batch compilers, an incremental development environment and easy-to-use visual programming tools for developing AIX applications. The unusually productive VisualAge C++ Professional for AIX V4 enables RAD using visual construction from parts, solid code generation, and cross-platform support.

The visual programming tools include Visual Builder and Data Access Builder, a graphical debugger, memory management and debug memory management routines, tools for creating and compiling resources, online help and a powerful, full-text search engine.

Hardware Prerequisites:	Any system which runs AIX V4.1.5 or later configured with SVGA display (1024 x 768 recommended), CD-ROM, and mouse or other pointing device. It requires a minimum of 96MB RAM (128MB or higher recommended), with 128MB swap/paging space and 650MB of disk space (or 260MB for just the C and C++ Compilers for AIX V3.6.4).
Software Prerequisites:	IBM AIX V4.1.5 or later for RS/6000 and a frames-capable browser like Netscape Communicator V4.0.4 or later to access the HTML-based help. Data Access Builder requires a database with the appropriate ODBC database driver and DB2 V2.1.2.

Product No.	Description	ОТС
30L8178	VisualAge C++ Professional V4	\$2,499
30L8179	1 registered user	\$2,479
30L8180	Product Upgrade C Set++* for AIX V3.1 or IBM C and C++ Compilers V3.6	\$949
30L8183	1 registered user	\$929

Enhanced performance fully exploits 64-bit SMP architecture

C for AIX V4.4



- Programming support for SMP architecture, including automatic parallelization of sequential loops and explicit parallelization of C code
- State-of-the-art, 64-bit enabled compiler and graphical debugger
- 32-bit source and binary compatibility
- Conformance to C programming language industry standards.

IBM C for AIX V4.4 provides a functionally rich software development environment that allows you to prepare now for your expanding development requirements and future business needs. C for AIX V4.4 has been designed to exploit the 64-bit RS/6000 Symmetric Multiprocessing (SMP) architecture, but it allows both 32-bit and 64-bit applications to execute at the same time and share access to files, memory, and inter-process communications resources. It also provides facilities that assist in the porting of applications from 32-bit to 64-bit environments.

C for AIX V4.4 offers an application development environment for constructing high-performance applications.

Hardware Prerequisites:	Any system which runs AIX configured with at least one supported SVGA display, keyboard, mouse and CD-ROM drive. It requires at least 32MB of memory, 42MB of disk space for all tools and documentation and 32MB of swap/paging space.
Software Prerequisites:	IBM AIX V4.1.5 or later as well as browser such as Netscape V3.0 or Internet Explorer V3.0 or later to access HTML-based help. Please note that 64-bit applications will run only on AIX V4.3.

Product No.	Description	ОТС
31L0488	C for AIX, Version 4.4	\$799
31L0497	Use Authorization (1)	\$779
31L0491	Upgrade from C for AIX V3 or C Set ++ for AIX V3	\$299
31L0498	Use Authorization (1) Upgrade	\$279
31L0494	Upgrade from IBM C for AIX V4	\$99
31L0499	Use Authorization (1) Upgrade	\$79

Appropriate media charges apply


Two-Month Unconditional Guarantee

Note: For additional Passport Advantage information, ordering information, and charges, contact your IBM representative or authorized reseller

Award winner for enterprise scalability and mission-critical operations

IBM VisualAge Generator V3.1





- Native Oracle 7 support
- VisualAge Generator Java Gateway support on OS/390 and AIX
- New built-in floating point arithmetic, exponentiation and logarithmic functions for mathematical operations
- Ability to load the VisualAge Generator Server run time, into VM shared saved segments.

VisualAge Generator V3.1 is an extremely powerful high-end application development environment used to build and deploy multitier client/server applications. It offers versatile solutions with scalable, multiplatform exploitation across networked systems.

Development can be done on Windows NT or OS/2 for deployment to the following N-Tier client/servers: AIX, OS/400, VSE, MVS, Windows (NT, 3.1, 95) HP-UX VM and OS/2. VisualAge Generator V3.1 includes support for the entire DB2 family and non-IBM relational databases via ODBC, plus middleware support for APPC (LU6.2), LU2, TCP/IP, Named Pipes, DCE and CICS. It also leverages MQSeries.

	486 90MHz Pentium** processor or higher, 64MB RAM (minimum); 180MB hard disk space, CD- ROM drive for installation.
Software Prerequisites:	Windows NT 4.0 or OS/2 Warp 4.0

Product No.	Description	ОТС
04L9680	VisualAge Generator Developer V3.1 (Windows NT - OS/2) (Includes unlimited use of Single-User run times for OS/2 and Windows)	\$6,499
04L9681	VisualAge Generator Server V3.1 (Multi-User - Server for Windows, OS/2, HP-UX, or AIX)	\$1,499
04L9723	VisualAge Generator V3.1 Documentation Kit (Should be ordered for each developer.) (Hard copy books.)	\$20

Media CD-ROM - except Documentation Kit.

Transforming application development for the 21st century

IBM VisualAge TeamConnection Enterprise Server V3.0





- Increase team productivity while shortening development schedules
- Build and distribute applications in a distributed environment across multiple production platforms.

VisualAge TeamConnection Enterprise Server is a repository-based software configuration management (SCM) system designed for a team programming environment. It uses IBM's award-winning DB2 Universal Database and repository technology to maintain the integrity of your development assets while scaling to fit your needs. With VisualAge TeamConnection you can manage and control your development projects, increase your team's productivity and improve overall software quality.


Hardware and Software Prerequisites:	Dependent upon the environment. Call 800 426-2255 for specific details.
---	---

Product No.	Description	ОТС
04L3809	VisualAge TeamConnection Enterprise Server V3.0 Program Package with 1 Server Access License [†]	\$3,249
04L3810	VisualAge TeamConnection Enterprise Server V3.0 Additional License – 1 Server Access License [†]	\$3,149

[†] One Server Access License must be purchased for each active user. Server access represents a single user accessing the VisualAge TeamConnection Enterprise Server at any single point in time.

Develop complex applications quickly

IBM VisualAge Smalltalk Enterprise V5.0



New features in VAST V5.0 include:

- Increased code library size (to 16GB on UNIX and Windows NT, 4GB on NetWare and 2GB on OS/2) with improved usability
- Enhanced Web Connection support for OS/390, JavaScript, dynamic HTML and test launching.

IBM VisualAge Smalltalk Enterprise V5.0 (VAST) combines the simplicity of visual construction with the power of an object-oriented environment to enable you to develop complex applications in a fraction of the time previously required. It provides full life-cycle support – from requirements and modeling to integration of transaction-enabled objects with legacy data – via a persistence framework.

Use the VAST Composition Editor to build, test and debug client, server and Web server applications - then integrate your objects with TXSeries, CICS and MQSeries middleware.

Hardware Prerequisites:	66MHz Pentium or RISC System/6000* uniprocessor (AIX) or SunSPARC uniprocessor or HP PA RISC uniprocessor, 32MB RAM for OS/2 and Windows, 64MB RAM for UNIX, 175MB disk space for stand alone, 130MB for Manager library.
Software Prerequisites:	OS/2 Warp V4, Windows 95 or NT 4.0, AIX 4.2.1 or 4.3, Solaris 2.5.1, 2.6 or HP-UX 10.1 or 10.2.

Product No.	Description	OTC
04L8642	VisualAge Smalltalk Enterprise V5.0	\$4,999
04L9030	VisualAge Smalltalk Server Workbench V5.0	\$4,999
39L8990	VisualAge Smalltalk Enterprise V5.0, Upgrade	\$1,499
39L8993	VisualAge Smalltalk Enterprise Server Workbench V5.0, Upgrade	\$1,500

Increase productivity with new IBM VisualAge Smalltalk add-ons

VisualAge Smalltalk Add-Ons

VisualAge Smalltalk UML Designer

IBM VisualAge Smalltalk Unified Modeling Language (UML) Designer is a tool for engineering application models and requirements to improve overall quality and maintainability. You can now define requirements, document use cases, create and print object model diagrams, and both generate and reverse-engineer Smalltalk code with VisualAge Smalltalk UML Designer.

VisualAge Smalltalk ObjectExtender

IBM VisualAge Smalltalk ObjectExtender is an extensive and powerful persistence framework that provides a complete solution for building robust, scalable persistence support for object models. A rich set of integrated tools – code generation, import and export facilities, debug and monitoring tools, etc. – makes the persistence effort minimal, allowing you to focus on your solution rather than your infrastructure.

VisualAge Smalltalk Servers for OS/2, Windows NT and AIX

With their standards-based Distributed Object Infrastructure and middleware, VisualAge Smalltalk Servers enable enterprise programmers to develop object-oriented Smalltalk applications that run in a CICS transactional, enterprise-computing environment on Windows NT, OS/2, AIX and MVS Server.


Features include:

- Support for Java RMI and IIOP communications over TCP/IP for AIX, Windows NT, OS/2 and Windows 95 (client only)
 e-business applications
- Process control objects (Actors) on AIX, Windows NT and OS/2
- Homogeneous Smalltalk messaging on AIX, Windows NT and OS/2
- Running of CICS transactions written in Smalltalk on AIX, Windows NT and OS/390

Product No.	Description	отс
04L9032	VisualAge Smalltalk Object Extender V4.5	\$3,999
04L9033	VisualAge Smalltalk UML Designer V4.5	\$3,599
04L9034	VisualAge Smalltalk Server	\$1,499

Highly optimized compiler to exploit SMP architecture

XL Fortran for AIX Version 6



New features include:

■ Support for the full implementation of the Fortran 95 standard

Support for the new IBM POWER3 architecture.

IBM's XL Fortran V6.1 for AIX (XLF for AIX) is a highly optimized, native compiler designed to exploit the RS/6000 line of symmetric-multiprocessing (SMP) hardware. Customers have the option of automatically parallelizing their Fortran code, or explicitly parallelizing it through the use of directives. This compiler also supports 64 bit programming.

XL Fortran V6.1 provides additional support for the Open MP Fortran API, provides a technical preview of the new IBM Distributed Debugger, and continues to:

- Support both Fortran 90 and FORTRAN77 programming
- Support 64-bit pointers and addressability for serial and SMP codes
- Exploit IBM POWER, POWER2 and POWERPC architectures.

Hardware Prerequisites:	th XL Fortran and XL Fortran RTE: RS/6000 with a CD-ROM ve, a minimum of 80MB RAM, 50MB of fixed-disk storage d 64MB paging space.	
Software Prerequisites:	Both XL Fortran and XL Fortran RTE: AIX V4.1 or later (for RS/6000), AIX V4.2.1 or AIX V4.3.2 or later (for RS/6000 SP and SMP), AIX V4.3 (for 64-bit).	

Visit our Web site at: www.software.ibm.com/ad/fortran

Part No.	Feature	Product No.	Description	ОТС
31L3111	2000	5765-D78	Program Package	\$1,599
39L9093	2002	5765-D78	Registered User - Single	\$1,589
39L9091	2006	5765-D78	Program Package Upgrade	\$799
39L9094	2008	5465-D78	Registered User – Single for Upgrade	\$789
31L3113	1006	5465-D77	XL Fortran RTE for AIX V6.1	\$299
White and			Theire I Area Committee Dancer	1000

Improved Fortran performance on parallel AIX systems

XL High Performance Fortran for AIX Version 1

New features include:

■ Complete function of XL Fortran for AIX V6.1

Use IBM's XL High Performance Fortran V1.4 for AIX (XL HPF for AIX) to boost the performance of engineering and scientific applications on RS/6000 Scalable POWERparallel* systems or clustered RS/6000s running under AIX V4.1.3 or later. The XL HPF for AIX compiler exploits the Message Passing Interface (MPI) Standard provided under the IBM Parallel Environment for AIX V2 to improve the performance of HPF programs.

Hardware Prerequisites:	RS/6000 SP system or cluster with at least one supported display, keyboard and mouse. Minimum of 80MB of RAM, 50MB fixed disk storage and 64MB of paging space for compilation.
Software Prerequisites:	AIX V4.1.3 or later, IBM Parallel Environment for AIX V2.1 or later

0010	5765-613	Program package with 1-user pack	\$6,995
0011	5765-613	5-user pack	\$24,975
0012	5765-613	10-user pack	\$32,975
0013	5765-613	50-user pack	\$109,975
XL High	Performance F	ortran V1 Run-Time Environment f	or AIX
4001	5765-612	1 license per SP Node or RS/6000	\$295
1000	5705 040		***

Description

OTC

4020 5765-612 1 license per SP Node or RS/6000 **\$298**

Breathe new life into your COBOL applications on the AIX desktop

COBOL Set for AIX

Product No.

- Optimized for creating mission-critical client/server applications
- Native Oracle and Sybase support
- ODBC support

Feature

Millennium Language Extension of Year 2000.


COBOL Set for AIX provides a wide number of enhancements including object-oriented language extensions across multiple platforms. With its client/server enablers, you can run COBOL in the AIX environment while accessing host data, as well as remote data, from DB2, CICS, VSAM/SAM MVS files and OS/400 record files.

Hardware Prerequisites:	RS/6000 with at least one supported display, keyboard and mouse.
Software Prerequisites:	Call for specific requirements.

Product No.	Description	отс
28H2176	CD-ROM	\$895
33H4408	8mm tape	\$1,045

Speed Year 2000 testing and cut maintenance costs

IBM C and C++ Maintenance and Test Toolsuite Version 1.0



- State-of-the-art software testing, debugging and maintenance capabilities
- Software maintenance tool to isolate featurerelated source code for testing
- Dynamic program slicing debugger that graphically localizes bugs for test personnel
- Software performance enhancement tool that provides detailed analysis of performance.


CMTT is a software comprehension and diagnostic system designed specifically to assist in finding Year 2000 problems and testing converted programs - as well as performing ongoing software testing and maintenance. CMTT can help you reduce development costs, while improving productivity and software quality.

Product No.	Description	Description	Price
04L6465	Program Package CD-ROM	Windows NT, Windows 95	\$2,499
04L3725	One Install	Windows NT, Windows 95	\$2,349
04L3731	One Install Software Advantage	Windows NT, Windows 95	\$2,349
04L3763	Media Pack	Windows NT, Windows 95	\$12
04L6472	Program Package CD-ROM	AIX and Sun Solaris	\$2,499
04L3714	One Install	AIX and Sun Solaris	\$2,349
04L3716	Additional Users	AIX and Sun Solaris	\$2,349
04L3761	One Install Software Advantage	AIX and Sun Solaris	\$2,349
04L7226	Additional Users Software Advantage	AIX and Sun Solaris	\$2,349
04L7227	Additional Users Upgrade Protection- OTC Software Advantage	AIX and Sun Solaris	\$719
04L3764	IBM C and C++ Maintenance and Test Toolsuite V1.0	AIX and Sun Solaris	\$12

Boost your programming success

AIX Distributed Computing Environment (DCE)

Fax Document 1548



- DCE V2.2 for AIX
- DCE V2.2 Cell Directory Services for AIX
- DCE V2.2 Security Services for AIX
- DCE Base Services.

The DCE for AIX family is an integrated suite of modular products designed to support transparent internetworking and resource sharing in heterogeneous computing environments. DCE architecture masks the physical complexity of the network and provides a layered model built from the bottom, supplier of services (the operating system), to the top, consumers of services (applications).

Minimum DCE development environment: AIX V4.3 for Client on every machine, plus one DCE Security Services and one Cell Directory Services in the network.

Dependent upon the environment. Supports AIX Versions 4.1.5, 4.2.1 and 4.3. Call 800 426-2255 for specific requirements.
--

Product No.	Description	OTC
5765-D14	DCE V2.2 for AIX	\$3,999 [†]
5765-D17	DCE V2.2 Base Services	\$149 [†]

[†] Prices for 3XX Processor. Please call us for prices for your specific requirement. Note: DCE Base Services (Client) are integrated with AIX V4.3.

Let IBM Global Services help you expand your business capabilities

IBM Global Services



■ IBM Global Services offers diverse, customized solutions to help you meet and beat the challenges of operating a successful business. We help you achieve substantial, measurable benefits to make you more competitive.

24 hours a day, 7 days a week

IBM AIX Support Line and IBM Consult Line

Fax Document 9034 - AIX Support Line Fax Document 9156 - Consult Line



IBM AIX Support line

IBM AIX Support Line is your direct line to productivity improvement. Using IBMLink, the Internet, or a toll-free 800-telephone number, you can contact our RS/6000 technical specialists day or night for answers and advice on your system's current operation and program releases.

- Total ordering flexibility with a "satisfaction guarantee"
- 24-hour/7-day coverage available

Prices Vary - Call for a Custom Quote

IBM Consult Line

Call IBM to schedule a conference call with you and the experts that have a vast wealth of knowledge and experience in I/S technological issues. Areas of expertise include:

- Availability and recovery
- Performance and capacity planning
- Systems Management
- Communications
- Migration & Implementation
- Database design

\$240[†] per hour

† Prices subject to change without notice.

IBM Global Services is the world's largest information technology services provider. IBM has an unsurpassed breadth of capabilities, and more than 120,000 professionals helping companies of all sizes, solve real business problems and create new business opportunities.

The people of IBM Global Services understand technology and know how to leverage it for business. You can count on us to create and deliver solutions that get results – solutions that will help you tackle challenges such as e-business transformation, Year 2000 readiness, the European Economic Monetary Union (EMU) transition, critical skills shortages and ever-escalating competitive pressures. Below are some of our global service offerings for 1999.

For more information on IBM Global Services visit www.ibm.com/services/. Also, many of our services can be ordered via our SHOPIBM Web site at www.direct.ibm.com.

System support from IBM specialists

IBM Customer Technical Advocate Service and IBM ServiceSuite

Fax Document 5018 - IBM Customer Technical Advocate Fax Document 698007 - Service Suite

IBM Customer Technical Advocate Service

Are you looking for a support specialist who knows your system environment - a technical advocate who has been dedicated specifically to your account? Welcome to the Customer Technical Advocate Service! Your IBM technical advocate wil contact you monthly to review your requirements while maintaining an up-to-date account profile to help eliminate red tape and expedite problem resolution.



- Single point of contact at all phases of support
- Includes remote system access for hands-on diagnosis

As little as \$300 a month

IBM ServiceSuite


With IBM ServiceSuite, we make it easy to select the services that best meet your unique support needs with two packaged solutions:

- Base Package Required
- Advanced Package Base package plus IBM Operational Support Services - Support Line, Alert and SystemExpert

Call for a Custom Quote

Accelerate the production and deployment of your online store

IBM SmoothStart Services for Net.Commerce for AIX and Windows NT



- Delivers a speedy and effective installation and configuration
- Allows easy access to system experts
- Provides basic skills instruction for your staff
- Choice of database DB2 or Oracle.

Our services specialists help accelerate the productive creation and deployment of your online store. When we're finished, you have a storefront on the Internet for marketing up to 100% of your products that takes orders and accepts payment information electronically.

Our Net.Commerce service specialist team conducts an installation planning session with you to understand your needs for your online storefront. We then install, configure and customize the Net.Commerce software to meet your requirements.

SmoothStart Services for Net.Commerce for Oracle

This SmoothStart Service for Net.Commerce is designed to offer prospective customers on a limited budget a fast e-Commerce solution including the utilization of their existing Oracle Database.

Call for Custom Quote.

Your link to an easy installation

IBM SmoothStart Services

Fax Document 7939 - Domino on RS/6000 Fax Document 9189 - Domino Go Webserve

IBM SmoothStart for AIX HACMP

For your link to a smooth installation, our services specialists will help ensure your AIX High Availability Cluster Multi-Processing (HACMP) software is installed, configured and tested. It features a fully coordinated installation and on-site skills instruction.



800

Price starts at \$25,000

Domino on RS/6000

IBM will plan, install and configure Lotus Domino for your server. Your server will be configured for basic communications using TCP/IP and Domino client installation and registration, which supports five LAN-attached clients (AIX, DOS/Windows 3.1, OS/2 Warp, OS/2 Warp Connect, Windows 95 or Windows NT).

Price starts at \$2,500

Domino Go Webserver

An IBM services specialist will install, configure and customize your Lotus Domino Go Webserver and perform verification testing of your target network.

Price starts at \$3,200

IBM Payment Server Software services

Installation Services for Payment Server for



- Installation Planning
- Software installation and configuration
- Operational customization.

This service provides a skilled services specialist who will help the customer design, install, configure, register and review the IBM Payment Server Software.

We offer both pre-packaged and customized solutions to meet your total business requirements such as e-business, migration services, systems management, operational support, installation and planning services, connectivity and network services.

Call for Custom Quote

Visit our Web site at: www.ibm.com/services/pss/us

Help enhance productivity with IBM Global Services

High Availability Server Assessment for Small and Medium Businesses



An IBM Service specialist performs the system assessment by working with your representatives from technical support, application development and operations. In a workshop format, we review your specific availability requirements, assess current practices, identify new options and techniques, and recommend further enhancements to minimize planned and unplanned system outages. A workshop and summary report help define high priority tasks.

Call for Custom Quote

Be proactive in securing your Internet, intranet and extranet networks

Internet Emergency Response Service

Fax Document 1132



Internet Emergency Response Service helps you become proactive in securing your Internet, intranet and extranet network environments. Our comprehensive service portfolio helps you evaluate your security posture, detect misuse and security violations, and respond to security incidents. The Internet Emergency Response Service gives you the backing and confidence of a global team of network security experts who not only have the extensive knowledge of the numerous threats to Internet security, but also the advanced techniques for confronting and managing them.

Highlights:

- Ongoing testing of your Internet environment to ensure its integrity and safety
- Uncovers potential security vulnerabilities
- Provides real-time intrusion detection option for immediate notification of unauthorized access
- Around-the-clock incident management

Call for Custom Quote

Plan to recover quickly

Business Recovery Services

Fax Document 2417 - Protection Express
Fax Document 4242 - Global Consulting Services
Fax Document 1752 - Recovery Services for RS/6000

Access: www.ibm.com/services/pss/us for more services information



Protection Express for RS/6000

Protection Express is an affordable offering for the small- and medium- sized business market. It offers you the option to have a system shipped to your site in the event of a disaster or unexpected interruption or to visit a Business Recovery Services center if your facility is unavailable. With Protection Express, test time is optional and can be purchased in eighthour blocks. With it, comes a two day disaster recovery plan development workshop to help you build an efficient recovery plan.

Highlights:

- No "disaster declaration fee"
- Optional use of hotsite in the event of a disaster
- Recovery plan development workshop

Global Consulting Services

Experienced IBM Business Recovery Consultants are trained to help understand your business and analyze its critical components - from personnel and processes to technology and facilities. Then, we can develop a comprehensive protection program designed to shield your company from the effects of events that can disrupt your ability to reliably deliver products and services to the marketplace.

Highlights:

- Quantitative Risk Analysis for your organization
- Environment Analysis to evaluate your I/T environment
- Plan Development and Implementation

Recovery Services for your RS/6000

An unplanned outage doesn't have to be a major business disaster. We can help you quickly resume operation of your business when disaster strikes. IBM professionals provide RS/6000 customers with a full range of continuity services including consulting, planning, recovery management, hotsite and QuickShip to fine-tune your recovery strategy.

Highlights:

- 12 hours of test time are included in your BRS subscription with additional test time available based on your needs
- Option for shipping most systems when disaster strikes
- Several recovery centers available
- No "disaster declaration fee"/Competitively priced

Call for a Custom Quote for any of these services.

Stay Current with IBM Products

IBM AIX Essentials

IBM's new computer-based multimedia training courses offer you convenient and effective AIX education when and where you want it.

The new IBM AIX Essentials series offers a dynamic training experience for those who need convenient and cost-effective AIX education. The series consists of five new, content-rich, computer-based multimedia training courses based on highly acclaimed, instructor-led AIX classes that have been successfully taught for years by IBM Education and Training.

These technology-based training courses incorporate the latest computer-based training innovations to offer you a

thorough AIX learning experience. The AIX Essentials series emphasizes hands-on learning – including a wealth of simulations within each course – to effectively teach you exactly what you need to know about the AIX system.

Save \$490 by ordering all five courses.

Each course can also be ordered individually.

Professional Certification Program & Classroom Training also available! Call **800 IBM-TEACH**.

For schedules and locations near you, call us at 800 IBM-TEACH!

S/6000 Course Title	Course Code	Product No.	Duration	Price 1 - 5 Users
AIX Essentials (all five courses)	S5050	5639-E05	57 hours	\$3,995
AIX Basics	S5051	5639-E04	15 hours	\$1,025
AIX System Administration	S5052	5639-E02	20 hours	\$1,775
AIX TCP/IP Communications	S5053	5639-E07	14 hours	\$1,015
AIX Desktop Environment for Users	S5054	5639-E03	6 hours	101 VE \$375
AIX Version 4.3 Feature Overview	S5055	5639-E06	2 hours	\$295



Features, features, features

ShopIBM is packed with features designed for you:

- In-depth information on thousands of products
- Money-saving promotions and Internetexclusive deals
- A toll-free number for shopping assistance
- Industry-leading site security and privacy protection.

Shop by day. Shop by night

Shop online 24 hours a day (your order will be processed Monday to Friday between 8AM-8PM ET). We accept credit cards or purchase orders to complete your purchase. It's as simple as that!

Visit ShopIBM at:

www.ibm.com/Shop

and discover the easy way to shop

visit

www.ibm.com/Shop

call 800 426 2255 today

Finance your RS/6000 directly from IBM

Choose the plan that's best for you

Leasing

- Low monthly payments can increase buying power by making your information system acquisition more affordable
- Protecting yourself against technological obsolescence with flexible mid-lease and end-of-lease options can make it easier to upgrade your equipment. That way, you won't be locked into outdated equipment
- Your lines of credit can be preserved for other growth opportunities.
 Leasing allows you to pay for the use of equipment without having to take on all the risks of owning it. This means you can increase your borrowing capacity while improving key ratios, such as debt-to-equity and return-on-assets
- Budget allocation may be simpler without interest amortization or depreciation to calculate and manage. What's more, leases can often be approved faster as part of operating budgets versus undergoing a capital budget approval process
- Leasing can provide tax advantages depending on your business situations and lease structure. Check with your tax counsel for further information

Rental Program

- Peak loads
- Special test situations, such as Year 2000
- Evaluations of specific IBM equipment before making larger investment decisions
- Software development or application pilot situations

Direct Purchase

- Call to see if you qualify for corporate discounts
- Use your IBM customer number and be billed for your purchase
- Charge purchases of less than \$10,000 to American Express, MasterCard or Visa

[†] IBM Global Financing offerings are provided through IBM Credit Corporation in the U.S. and IBM Canada Ltd. and other IBM subsidiaries and divisions worldwide. IBM Global Financing oferings are available qualified commercial and governmental customers.



RS/6000 Enterprise Server Model S80

Installment Purchase

If you prefer to own, IBM Global Financing offers purchase financing to help you acquire new IBM hardware, software and services.

- Free up your capital by financing your new purchases
- Stretch your payments for up to 60 months

Visit our Web site at: www.financing.ibm.com

Alpha Index

TAR THE STATE OF T	
Adapters35	, 44-47
Add-ons and Upgrades	
Memory	
AIX	52
Add-ons and Upgrades	
Cables	. 44-45
Certified C2 for AIX V43.1	54
Communications Adapters and Cables	. 44-47
Disk Drives	. 35-36
Disk/Tape Drives	
Displays 2000 mm	07
IBM InfoWindow II 3153 ASCII/ANSI	
Display Station	50
Drives	
Disk	. 35-36
Disk/Tape	
Optical	34
Tape	
Education	
Enterprise Server Model H70	
Enterprise Server Model H50	20
Global Services	
e-business	73
RS/6000 Services for Installation and Migration	
System Management and Support	/ 4
Graphics Accelerator	20
GXT3000P POWER GXT2000P	3∠ 31
Hardware	
Hardware Add-ons and Upgrades	30
Enterprise Server Model B50	16
Enterprise Server Model S80	24
Enterprise Servers	. 20-22
Graphic Peripherals	33
Graphics Accelerators	. 31-32
HA-H70 Cluster Server	21
POWER GXT130P	
RS/6000 Enterprise Servers	
RS/6000 Enterprise Server Upgrades	23
RS/6000 Nodes: High, Thin and Wide	27
RS/6000 SP Attached Servers: Models S80	
and S70 Advanced	14.07
ServersSMP Servers	. 14-2/
Workstations	
HA-S70 Advanced	
Input Device	
iSource	
Nodes (RS/6000 SP)	
NUUCS (N3/0000 3F)	

Optical Disk Optical Disk Drives Peripherals Printers	34
Printers Printers Servers HA-S70 Advanced IBM Fibre Channel RAID Storage Server Server Upgrades	42-43 . 18-23, 26
ShopIBM	
AIX	55 58 58 66 67 70 62-68 56 56 60 60 60 60 60 60 60 60 60 6
SpaceBall Storage	30
Disk Drives Disk/Tape Drives Enterprise Storage Server (ESS) IBM Fibre Channel RAID Storage Server Optical Disk Drives Tape Drives Ultra2 SCSI LVD Adapters UltraSCSI Adapters	36 36 34 38-4
Fape Drives Workstations	



Year 2000 readiness tips Points to consider


- Potential business impact
- What you need to do to get your RS/6000 systems ready
- How it affects your RS/6000

The current RS/6000 family is Year 2000 ready, but that doesn't mean your RS/6000 installation is ready for the Year 2000 – even if you do have a completely current system. You still have to fix and test all of the software that runs on your RS/6000 for Year 2000 readiness. And, if you have older RS/6000 systems or are running earlier versions of AIX, you have even more work to do.

We can help make your Year 2000 job easier – a special informational workbook outlines what you need to know, including how to test your software and where to go for help.

Visit the Web and pull down your copy today at:

http://www.software.ibm.com/year2000/papers/aixy2k.html



Trademarks:

The following terms are registered trademarks or trademarks of IBM Corporation in the United States or other countries or both: ADSTAR, Advanced Function Common Control Unit, Advanced Peer-to-Peer Networking, AIX, AIXwindows, AIX/6000, APPN, AS/400, Business Partner, CICS, C Set ++, DB2, DRDA, ESCON, GXT150M, IBM, IMS, InfoWindow, IPDS, LANStreamer, LoadLeveler, Magstar, MQSeries, MVS, Micro Channel, NetView, OS/2, OS/390, OS/400, Pennant, Portmaster, POWER2, POWERparallel, PowerPC, PowerPC 604, PowerPC 604e, Print Services Facility, Proprinter, PSF, R/3, RISC System/6000, RS/6000, SmoothStart, SP, S/370, S/390, System/370, System/390, SystemGuard, TeamConnection, TURBOWAYS, Ultimedia, VisualAge, WebSphere and XWindows System and are denoted by a single asterisk (*). Tivoli is a registered trademark of Tivoli Systems Inc. Tivoli Systems, Inc. is a subsidiary of IBM Corporation. Java is a trademark of Sun Microsystems, Inc. UNIX is a registered trademark in the United States and other countries licensed exclusively through X/Open Company Limited. Windows, Windows NT and Windows 95 are trademarks of Microsoft Corporation. Other company, product and service names, which may be denoted by a double asterisk (**), may be trademarks or service marks of others.

Benchmarks:

Values shown in the Power Lineup chart are the results of development-level systems using the AIX operating system. All performance data was obtained in a specific environment and is presented "as is" for illustrative purposes only. Although these values should be indicative of generally available systems, no warranties or guarantees are stated or implied by IBM. IBM recommends application-oriented testing for performance predictions and offers the above commonly reported benchmarks only as an initial indicator. Additional information on these tests is available from your IBM local Branch Office or IBM Authorized Reseller.

QppD is the power metric of TPC-D and is based on a geometric mean of the 17 TPC-D queries, the insert test and the delete test. QppD is scaled based on database size from 30GB to 1TB.

QthD is the throughput metric of TPC-D and is a classical throughput measure characterizing the ability of the system to support a multiuser workload in a balanced way. In the background, there is an update stream that runs a series of insert/delete operations. QthD is scaled based on the database size from 30GB to 1TB.

\$/QphD is the price/performance metric for the TPC-C benchmark, where QphD is the geometric mean of QppD and QthD. The price is the five-year cost of ownership for the tested configuration and includes maintenance and software support.

 \it{tpmC} : TPC Benchmark C throughput as measured in transactions per minute during a valid TPC-C** run.

\$/tpmC: TPC Benchmark C price/performance ratio, where the fiveyear total cost of ownership for hardware, software and maintenance is divided by the throughput tpmC.

Rel OLTP Perf. Relative OLTP Performance is an estimate of commercial throughput using an IBM analytical model. This model simulates some of the system's operations of the CPU, caches and memory in an OLTP environment, but does not simulate the disk or network I/O operations. Although general database and operating systems parameters are used, the model does not represent specific databases or AIX versions. With these limitations, ROLTP may be used to compare RS/6000 performance. The Model 250 is the reference system and has a value of 1.0.

Details on the configurations and operating systems used for specific SPEC benchmarks shown can be found at:

www.specbench.org

LINPACK details can be found at:

www.rs6000.ibm.com/ hardware/perf_notes.html

TPC results can be found on the TPC home page at: www.tpc.org

The NotesBench Mail workload models actively simulate users reading and sending mail. A simulated average user will execute a prescribed set of functions 4 times per hour and will generate mail traffic about every 90 minutes. Performance metrics are:

NotesMark – transactions/minute (TPM) with the minimum Notemark being at least 1.3 times the number of Mail Only users.

NotesBench users – number of client (user) sessions being simulated by the NotesBench workload.

\$/NotesMark - ratio of total system cost divided by the NotesMark (TPM) achieved on the Mail workload.

\$/User - ratio of total system cost divided by the number of client sessions successfully simulated for the Mail NotesBench workload measured. Total system cost is the price of the server under test to the customer, including hardware, operating system and Domino Server licenses.

VolanoMark is a 100% Pure Java server benchmark characterized by long-lasting network connections and high thread counts. In this context, long-lasting means the connections last several minutes or longer, rather than just a few seconds. The VolanoMark benchmark creates client connections in groups of 20 and measures how long it takes for the clients to take turns broadcasting their messages to the group. At the end of the test, it reports a score as the average number of messages transferred by the server per second. For more information about the VolanoMark benchmark, see http://www.volano.com

VolanoMark 2.1.2 local performance test measures throughput in messages per second. The final score is the average of the best two out of three results.

Terms and Conditions:

IBM hardware products are manufactured from new parts, or new and used parts. Regardless, our warranty terms apply.

All performance data contained in this publication was obtained in a specific operating environment and is presented as an illustration only. Results obtained in other environments may vary.

All prices shown are IBM suggested list prices. Dealer prices may vary.

WHEN EVERY SECOND COUNTS

HIGH-AVAILABILITY SOLUTIONS FROM IBM

Your mission-critical applications must remain instantly available to customers and employees around the clock – 24 hours a day, 7 days a week, 365 days a year.

IBM provides a wide variety of affordable high-availability solutions – the latest and most powerful of which is our new HA-S80 – and a unique Enterprise Resource Planning (ERP) Performance Protection Plan (PPP).

IBM High-Availability Solutions include AIX and HACMP (High Availability Cluster Multiprocessing) software, built-in hardware and software redundancy, automatic preventive maintenance alerts and system restart, non-disruptive maintenance, and hot-swappable disks with cooling and power components.

The ERP PPP ensures that your ERP system – from SAP, BAAN PeopleSoft or Oracle – will meet your defined workload requirements for 2 full years after installation. If it doesn't, IBM will provide a processor and/or memory upgrade at no additional charge.



RS/6000 HA-S80 Cluster Server

X

HA-S80

New The high-availability version of the most powerful UNIX enterprise server ever.

Customers requiring the ultimate in high-availability performance need look no further than this clustered version of the 6- to 24-way, copper microprocessor technology-based S80.

HA-S70 ADVANCED

A highly scalable and available enterprise server for critical business applications.

This powerful cluster server is designed for mission-critical applications and can be attached to an RS/6000 SP to deliver four times the database processing power of other SP nodes.

SEE PAGE 21


HA-H70

A 64-bit, high-availability cluster server solution at the right price

Here's an economical, robust enterprise server designed for easy growth that can be scaled to accommodate up to four servers per cluster.

SEE PAGE 22

FOR MORE DETAILS, VISIT OUR WEBSITE AT: WWW.RS6000.IBM.COM/SOLUTIONS/HA





©International Business Machines Corporation 1999

Returned Mail Only IBM Direct Dept. RC000 411 East Wisconsin Avenue Milwaukee, WI 53202-9846 Bulk Rate U.S. Postage PAID IBM CORP.

If not deliverable as addressed, please route to MIS manager.

Priority Code

